

Rpt. 11b.

EXIT LON.
25/6/19Glasgow Report No. 38867
27872

THU, 26 JUN. 1919

Clear Skies
NOT WRITTEN

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.—STEAM SHIPS.

PARTICULARS RELATING TO ALL STEAM SHIPS EITHER FLUSH DECKED, OR WITH TOP GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, OR WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE

Counselor No. 390. Standard 85 Type

Port of Survey Glasgow
Date of Survey White Building
Name of Surveyor Henry Gibbs

Ship's Name.	Port of Registry and Nationality.	Official Number.	Gross Tonnage.	Date of Build.	Particulars of Classification.
"BENYORLICH"	Leith British	142010		1919	100A1 (contemplated)
Number in Register Book					

Registered dimensions from Ship's Register.	LENGTH.	BREADTH.	DEPTH.	UNDER DECK TONNAGE.
	400.6	52.25	28.5	4817.88
Length on Loadline.	399.5	Frame Depth 10 Rule 6 Excess 4	Ceiling + .20 Sheer + 1.13	Peak Tanks 3 drops in tank + .12
RECTED DIMENSIONS.	399.5	-.66		

efficient of fineness - .78 /
any modification necessary - .02 & DB
Para. 4 (a) to (e)* - .76 /
efficient as corrected - .76 /

Stem 120 { 180 / 2 = 90 Mean
Sternpost 60 }
Stem at $\frac{1}{2}$ of the length from Stern 67.5 { 101 / 2 = 50.5 Mean
Sternpost 33.5 } $\div 5.5 = 9.8$
Individual mean Sheer 9.0 + 9.8 = 9.0 - 9.0 -
Standard mean Sheer [Table, Para. 18] 10.95 / Correction 10.95 /
Difference 10.95 / 4 = - 10.25 /
if limited as Para. 18 (f) -

Fall in Sheer { At front of bridge house
Amidships { At after end of forecastle ✓

Fall in Sheer { Para. 18 (d) $\div 2 =$
Length uncovered ✓ Correction

ALLOWANCE FOR DECK ERECTIONS :—
Board, Table C $4 - 9 \frac{1}{2}$
Correction for Length, if required (Para. 12, 13, and 14) $+ 2 \frac{1}{2}$
 $4 - 11 \frac{3}{4}$
Board by Table A, corrected for sheer, and for length, if required (Para. 12, 13, and 14) $7 - 5 \frac{1}{2}$
Difference $2 - 5 \frac{1}{2}$
Percentage as below 32.28%
 32.18%

Correction for R. Q. Dk. if engine and boiler openings not covered by bridge house (Para. 11)
Allowance for Deck Erections - 9.5 /

	Length.	Length allowed.	Height.
Bridge House	39.25	39.25	7-11 $\frac{1}{2}$
+ Raised Q. Dk.	112.66	112.66	-
Poop	49.25	49.25	-
Total	200.69	201.16	$2 \frac{2}{3}$
Length of Ship		399.5	= 5035
Corresponding percentage (Para. 11, 12, 13, or 14)	18		
	32.289		

FREEBOARD recommended amidships from centre of Disc to top of Statutory Deck Line, Wood (Iron) Deck :—

Fresh Water Line	above centre of Disc
Indian Summer Line	" " "
Winter Line	below "
Winter North Atlantic Line	" "

* If the frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside of ceiling should be reported if possible.
† In vessels obtaining an allowance for deck erections under Para. 11 where the sheer drops abaft amidships the height of the R.Q.D. is to be taken from the level of the top of the amidship beam.
§ In flush-decked vessels the total standard mean sheer means the sheer measured at the stem and stern-post. In vessels having poops and forecastles, it means the sheer measured at points distant one eighth of the vessel's length from stem and stern-post.

1m. 2.17. T.

Moulded Depth as measured.....

31.0"

NOTE.—If the depth is measured when vessel is afloat, the details of measurement should be reported.

Addition for Keel below base line for draught record 27.8 inches.

CORRECTION FOR LENGTH.

Length of Ship on Loadline	399.5
Length in Table	372.0
Difference	27.5
Correction for 10ft, Table A.	1.6
× Difference divided by 10	+ 4.2
If $\frac{6}{10}$ ths length covered divide by 2	+ 2.5

CORRECTION FOR IRON DECK.

Proportion covered, if less than $\frac{7}{10}$ ths length covered50
Thickness of usual wood deck, less stringer32
	- 1 $\frac{3}{4}$ "

CORRECTION FOR ROUND OF BEAM.

Breadth at Gunwale amidships	52.0
Round of Beam	13
Normal round	13
Difference	$\checkmark \div 2 =$
Proportion of Deck uncovered (Para. 19)	

NOTE.—The round of beam should be reported on the full breadth of vessel at the gunwale.

Freeboard, Table A	7-11
Correction for Sheer	- 10.2
Correction for Length	+ 4.2
Allowance for Deck Erections	7-5.5
Correction for Round of Beam	- 9.2

7-11
- 10.2
+ 4.2
7-5.5
- 9.2

Correction for fall in Sheer (if any)	
Correction for Iron Deck (if required)	- 1 $\frac{3}{4}$
Additions for non-compliance with provisions of Para. 11 (d) and (e)	
Other Corrections (if any)	

6.6
6.05
5.7

Winter Freeboard	6.6
Summer Freeboard	6.05
Indian Summer Freeboard	5.7
N.A. Winter Freeboard	

6.6
6.05
5.7

Correction necessary because clearside amidships, measured in accordance with the Statute is not taken at the intersection of the wood or iron deck with side.

1 $\frac{3}{4}$

Winter Freeboard from deck line	6-7 $\frac{3}{4}$
Summer " " " "	6-5 $\frac{1}{2}$
Indian Summer " " " "	5-8 $\frac{3}{4}$
N.A. Winter " " " "	

6-7 $\frac{3}{4}$
6-5 $\frac{1}{2}$
5-8 $\frac{3}{4}$

State dimensions of freeing port area on back of this form.

The Surveyor should state whether the fall in sheer as reported is measured relatively to the straight line of keel or to the water line. If measured relatively to water line the vessel's draft at time of survey, and also the usual load draft forward and aft should be reported.

MAILED

RECEIVED

15-8-19

W343-0035

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

2020

15

Do all the Frames extend to the top height in the Poop? Yes Raised Quarter Deck? Bridge House? Yes Forecastle? Yes

To what height do the Reverse Frames extend? Bulk angle frames.

Has the Poop or Raised Quarter Deck an efficient Iron Bulkhead at the fore end? Yes

Give particulars of the means for closing the openings in Bulkhead Hunged doors.

Is the Poop or Raised Quarter Deck connected with the Bridge House? No

Give particulars of the means for closing the openings in Bulkhead No openings.

What is the thickness of the Bridge Front plating? .40 and Coaming plate? .44

Give scantlings and spacing of the Stiffeners 9 x 3½ x .56 Bwd spaced 30° apart ✓

Are bracket plates fitted at each end of the Stiffeners? Yes

Are hor'l. brackets fitted connecting Bridge Bulk'd. with Bulwarks? Yes

Has the Bridge House an efficient Iron Bulkhead at the after end? Yes

How are the openings closed? Storm boards full height in permanent channels.

Is the Forecastle at least as high as the main or top-gallant rail? Yes

Are the Engine and Boiler openings covered by a Bridge, Poop, Raised Quarter Deck, or enclosed by a Strong Iron or Steel Deckhouse? Yes

If the openings are not so protected are the exposed parts of the Casings efficiently constructed?

Give thickness of plating; scantlings and spacing of Stiffeners

What is the height of the exposed Casings? Are suitable means provided for closing all openings in them in bad weather? Yes

Are the Weather Deck Hatchways efficiently constructed and at least equal to the requirements of Section 28 of the Rules for 1904-5? Give particulars below:—

Position and Size.		N° 1. 32·6+20·0	N° 2. 24·0+20·0	N° 3. 10·10+18·0	18·34·8+20·0	N° 5. 28·2+20·0		
Item.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.
COAMING. Height above top of DECK	30		30		24		30	
Thickness Sides.....	.44		.44		.44		.44	
Thickness Ends.....	.44		.44		.44		.44	
SHIFTING BEAMS OR WEB PLATES.	Number..... Section and Scantlings..... Material.....	6 18x36 715 11-4x3x.44	6 same as N° 1.	3 10x30 715 3x3x.40	6 same as N° 1	5 same as N° 1		
* FORE AND AFTERS.	Number..... Section and Scantlings..... Material.....	96 fore & afters						
HATCHES Thickness..... Remarks.....	10x3½x.46	Bwd along sides	2½	sends of N° 1-2-4x5	2½	2½	2½	5 hatches

* The depth of Fore and Afters should be stated from the underside of the hatches in all cases.

(If the sill of the lowest side scuttle will be less than 6 inches above the Indian Summer Load Line if assigned under the tables, state vertical distance from top of deck at side amidships to lower edge of lowest side scuttle.)

The following information is to be given in all Cases of vessels dealt with under Paras. 11, 12 (under 15 feet Moulded depth) and under Shelter Deck Rules.

What is the thickness of the Bridge Sheerstrake? Strake between Main and Bridge Sheerstrakes?

Delete the words { The Crew are, are not, berthed in the bridge house.
that do not apply { The arrangements to enable them to get backwards and forwards from their quarters are, are not satisfactory.


Length of Bulwarks in well

Area of Freeing Ports required by Para. 11 (e) each side of vessel = Sq. ft.

Ft. Tenths. Ft. Tenths. No.

x	x	{ Freeing Ports (each side of vessel)	=	Sq. ft.
x	x		=	Sq. ft.

Total deficiency or excess = Sq. ft.



Show hereon line of Floors or Tank Top with position of any Breaks in same; also height of Peak Tank tops, &c., &c.

State any special features in the construction of the Vessel Standard B Type Vessel.

This is a sister vessel to S/S "CLAN SKENE" Gls report of Freeboard request enclosed.

Owners Messrs W Thomson & C

Address

Fee £ 7 : 7 : 0

Received by me 16.9.17 R.R.N.

© 2020



Lloyd's Register
Foundation