

Form No. 1A

W1347-0026(212)

GENERAL REMARKS—(continued).

Rpt. 4.

Date of visit

The

Signal

O

12

No., D

Wheth
Fore

Numb

Numb

Rigge

Stern

Build

Galle

Head

Fram

ves

Numb

Numb

and

Total t
to

No of
sets of
Engines

Gms

No. of
Shafts

Gms

Und

Spa

Tun

For

Br

Por

Sid

De

Ch

Sp

Es

No

No

Co

Co

Co

Co

Co

Co

Co

Co

Co

Co

Co

Co

Co

Co

WEB-FRAMES
" " No. of
WEB-FRAMES
" " No. of
" " Size of
BRACKET P
Web Frame

BULKHEAD

W.T.BULKHEAD
after

" COLLISION
PARTITION
LONGITUDE

Are the outside
Are the Sluice

STRAKE

FLAT PLATE KEEL
(If Bar Keel, state)

GARBOARD OF A

State actual
thickness in
wa. of Double
Bottom.

E

C

D

E

F

G

H

J

K

L

M

N

O

P

Q

R

S

T

U

V

W

X

Y

Z

THICKNESS OF

CLEAR OF LONG

DO. OF STEEL

DECK OF FLAT

" She

Length and

POOP SIDES

SHORT BRIDGE

FORECASTLE

Upper Deck

Stringer

Bridge

Second Deck

Stringer

FRAME

REVERSE

LOWER

Bowsprit

Foremast

MA

MA

MA

MA

MA

MA

MA

MA

MA

MA

MA

MA

MA

MA

MA

MA

MA

MA

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop 50.5 ft., R.Q.D. — ft., Bridge 114 ft., Forecastle 38.5 ft. (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as should appear in the Register Book) 1st (H.C.) & Macform 2nd (H.C.) in Nos 1, 2, 4 & 5 Holds.

Official No. 142272 ; Signal Letters State if Machinery is fitted aft No

How are the surfaces preserved from oxidation? Inside Paint Cement Outside Paint

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors Cell No

Where Fitted.	*Length. Feet.	Water Capacity. Tons.	Where Fitted.	*Length. Feet.	Water Capacity. Tons.
Double bottom, aft,	129	425	Fore peak tank,		125
Double bottom, under Engines and Boilers,	36	175	After peak tank,		200
Double bottom, if under Engines only,			Deep tank, aft,		
Double bottom, if under Boilers only,			Deep tank, forward,		
Double bottom, forward,	181.5	696	Other tanks, if fitted,		
Total capacity of double bottom		1296	(If necessary, furnish further information by sketch.)		

* The wells are not to be included in the lengths of the tanks. State whether the above have been tested as required by the Rules. Yes

Order for Special Survey No. 2960

Date 21st May, 1918.

No. 395 in builder's yard.

DATES OF SURVEYS held while building
(1918). June 10, 12, 14, 21, 25, 27. July 18, 22, 24, 26, 30. Aug. 2, 7, 9, 14, 19, 21, 28. Sept. 2, 5, 26. Oct. 1, 4, 9, 11, 15, 21, 24, 25, 29.
Nov. 1, 4, 5, 8, 14, 15, 21, 25, 28. Dec. 6, 10, 11, 13, 16, 17, 23, 24, 27 (1919). Jan. 10, 13, 14, 16, 22, 24, 27, 28, 29. Feb. 3, 7, 11, 14, 18, 19, 25, 27. Mar. 4, 10, 13, 18, 21, 26, 28. Apr. 1, 3, 7, 8, 10, 11, 16, 18, 21, 24, 25, 28, 30. May 1, 2, 5, 6, 9, 13, 15, 16, 19, 23, 27, 28, 29. June 6, 24, 26, 27. July 2, 17, 22, 24, 28, 29, 30.

Total No. of Visits 110.

Surveyor's Signature J.D. Mares

Lloyd's Register

Foundation