









GENERAL

# PARTICULARS OF LONGITUDINAL FRAMING.

FRAMING.		AMIDSHIPS.			ENDS.			AMIDSHIPS.			ENDS.			RIVETING.						
		In Ship.			In Ship.			Per Rule or as approved.			Per Rule or as approved.			Rivets in Longitudinal Frames.	Spacing of Rivets on each side of Transverses and Bulkheads.	Rivets in Brackets to Bulkheads.				
		Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Diam.	Spang.	Inches.	Number.	Diameter.	
Framing of <b>主, L, 中, 尾</b> .....		<i>Bull angles</i>																		
Frames in Bridge 'tween Decks ...		6	3	36				6	3	36										
Frames from Uppermost Continuous Deck		9	3 1/2	44	9	3 1/2	44	9	3 1/2	44	9	3 1/2	44	7/8	3 1/4	↑ see letter rec 27/12/22				
Framing from Awning, Shelter or Upper Deck to Margin Plate.		" 2	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	
		" 3	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	
		" 4	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	
		" 5	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	
		" 6	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	
		" 7	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
		" 8	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
		" 9	10	3 1/2	44	10	3 1/2	44	10	3 1/2	44	10	3 1/2	44	"	"	"	"	"	"
		" 10	10	3 1/2	48	10	3 1/2	48	10	3 1/2	48	10	3 1/2	48	"	"	"	"	"	"
		" 11	10	3 1/2	54	10	3 1/2	54	10	3 1/2	54	10	3 1/2	54	"	"	"	"	"	"
Spacing of Longitudinal Frames		Amidships 30			Ends 30			Amidships 30			Ends 30									
Double Bottoms L, L or C		Tank Top Longitudinals			Bottom			Amidships			At Ends									
		<i>Channels</i>												<i>Longs scuttles rec 27/12/22</i>						
		15 x 4 1/2 x 4			15 x 4 1/2 x 4			15 x 4 1/2 x 4			15 x 4 1/2 x 4			7/8 5 1/4						
		x 4 x 63			x 4 x 63			x 4 x 63			x 4 x 63			7/8 3 1/2						
		30			30			30			30			<i>Throughout No 1 Tank</i>						
Transverses.																				
In Bridge 'tween Decks		Depth and Thickness			Face Angles			Lugs to Shell												
		15 38			3 1/2 3 1/2 40			3 1/2 3 1/2 40			3 1/2 3 1/2 40			3/4 3 3/8						
In Awning Upper 'tween Decks.		Depth and Thickness			Face Angles			Lugs to Shell												
		18 40			3 1/2 3 1/2 44			3 1/2 3 1/2 44			3 1/2 3 1/2 44			7/8 5						
In Hold.		Depth and Thickness			Face Angles			Lugs to Shell												
		36 46			7 3 1/2 48			7 3 1/2 48			7 3 1/2 48			7/8 4						
		Brackets																		
		40			40			40			40									
Spacing of Transverse Frames		7-9 1/2 8-3			7-9 1/2 8-3			7-9 1/2 8-3			7-9 1/2 8-3									
		<i>joggled</i>																		
Longitudinal Beams of L, L or C		Bridge Deck			Upper			Second			Third									
		6A			6 3 38			6 3 38			6 3 38			Transverse Beams.						
		6 3 38			6 3 38			6 3 38			6 3 38			11 x 38 3 1/2 x 35 1/4 11 x 38 3 1/2 x 35 1/4 20 x 40 7 x 32 1/4 11 x 48 3 1/2 x 35 1/4 5"						

The particulars of framing in peaks (if ordinary), Floors, Centre Girder, Side Girders and Margin Plate and their angle attachments, etc., to be entered in their respective places provided for on the Report Forms.

NOTE:—This slip to be pasted on the fourth page of the Report, and reference to same to be made under framing, etc., on the first page.

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop *113.25* ft., R.Q.D. — ft., Bridge *32.0* ft., Forecastle *44.68* ft. (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated.

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as should appear in the Register Book) *2 Stks (Steel) + wood frame long framing*

Official No. *146652*; Signal Letters *K.N.B.S.* State if Machinery is fitted aft *Machinery aft*

How are the surfaces preserved from oxidation? Inside *Cement, Paint & Bitumastic* Outside *Saint*

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors. *Cellular*

Where Fitted.	*Length.	Water Capacity.	Where Fitted.	*Length.	Water Capacity.
	Feet.	Tons.		Feet.	Tons.
Double bottom, aft,			Fore peak tank,	20'-0"	141
Double bottom, under Engines and Boilers,	90'-5"	422	After peak tank,	24'-2"	188
Double bottom, if under Engines only,			Deep tank, aft,		
Double bottom, if under Boilers only,			Deep tank, forward,	46'-3"	699
Double bottom, forward,			Other tanks, if fitted,		
			(If necessary, furnish further information by sketch.)		

\* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules *Yes*

Order for Special Survey No. *919*

Date *24-3-1921*

No. *282* in builder's yard.

DATES OF SURVEYS held while building

1921. Feb 3. 14. 25. Mar 4. 17. 23. Apr 1. 14. 21. 28. May 6. 13. 19. 24. June 3. 8. 17. July 8. Aug 5. 12. 19. 25. Sept 6. 8. 23. Oct 10. 27. Nov 4. 8. Dec 1. 6. 12. 20.

1922. Feb 6. 8. 16. 17. 24. 25. 27. 28. Mar 2. 14. 7. 9. 13. 14. Apr 6. 13. May 15. 17. 19. 23. 26. 31. June 2. 6. 9. 12. 14. 15. 16. 19. 21. 23. 27. July 10. 13. 14. 28. Aug 2. 8. 16. 24. 29. Sept 1. 22. 26. 28. Oct 3. 12. 18. 17. 20. 24. Nov 7. 17. 24. 29. Dec 1. 5. 7. 8. 9.

Surveyor's Signature *J. H. Mackintosh*

Total No. of Visits *96*