

S. S. CITY OF BENARES

PARTICULARS OF PROTECTION TO OPENINGS, ETC.

GLASGOW REPORT No. 57455

HATCHWAYS ON FREEBOARD AND SUPERSTRUCTURE DECKS

Description of Hatchway		Boat Deck	Casing Top	Boat Deck	Casing Top						
Dimensions of Hatchway		103 Hatch	110 4 Hatch	103 Hatch	110 4 Hatch						
COAMINGS	Height above Deck	33"	33"	33"	33"						
	Thickness	1 1/4"	1 1/4"	1 1/4"	1 1/4"						
	Stiffeners	7 x 3 x 36/34	9 x 3 1/2 x 40	7 x 3 x 36/34	9 x 3 1/2 x 40						
	Brackets, Stays	2" Round	None	2" Round	None						
HATCH BEAMS	Number	Three	Two	Three	Two						
	Spacing	3'-10"	3'-5 1/2"	3'-10"	3'-5 1/2"						
	Scantling and Sketch	4 x 3 x 3 x 42	4 x 3 x 3 x 42	4 x 3 x 3 x 42	4 x 3 x 3 x 42						
	Bearing Surface	3	3	3	3						
FORE AND AFTERS	Number										
	Spacing										
	Unsupported Lengths										
	Scantling* and Sketch	✓	✓	✓	None						
HATCH COVERS	Material	Wood	Wood	Wood	Wood						
	Thickness	3"	3"	3"	3"						
	How fitted	Trap	Trap	Trap	Trap						
	Bearing Surface	3"	3"	3"	3"						
Spacing of Cleats		24"	24"	24"	24"						
Number of Tarpaulins		Three	Three	Three	One						

RETAIN



© 2020

Lloyd's Register Foundation

W369-0115

Particulars of fiddler, funnel and ventilator coamings

Bridge, Forward Bulkhead

Rivets to