

Form No. 15. WEB FRAMES. FORGINGS & CASTINGS. BULKHEADS. STIFFENERS. PLATING. RIVETING. STRAKES. BUTTS. LOWER MASTS. RIGGING. SAILS.

EQUIPMENT No. 34678. LETTER 4. ANCHORS. TONNAGE U.D.K. OR PLATING No. FOR TRAWLERS. CHAIN CABLES. HAWSERS AND WARPS. Boats. Steering Gear. Pumps. Windlass. Engine Room Skylights. Coal Bunker Openings. Number of Scuppers. Ceiling in Holds. Cargo Hatchways. State size No. 1 Hatch. Number of Web Plates. Bulwarks. The foregoing is a correct description. Builder's Signature. Correspondence. Workmanship. Is the riveted work properly closed? Are the liners between the frames and plates solid single pieces? Are the butts of plating properly shifted and strapped? Have all the upper and weather decks been tested as required by the Rules (Sec. 26, par. 20)? Have all the gutterways been tested as required by the Rules (Sec. 26, par. 20)? General Remarks. This vessel has been built in accordance with the approved plans. The hull, upper and lower, of above date, and in general conformity with the Rules for the class contemplated. No vibration pump has been fitted. Steam steering gear tried & found efficient. Auxiliary means of steering provided for by means of wire ropes led to wheel. 3 Forging reports and 3 Plans are forwarded herewith. Standard "A" vessel. The Surveyor should state the Number of Report and Name of any Sister Vessel. Plans to be forwarded with F.E. Report showing vessel as built. The amount of Entry Fee. Special Survey Fee. Travelling Expenses, if any. State whether the Vessel has been built under Special Survey. Committee's Minute. Character assigned. Lloyd's Register of Shipping. W 374-0027(1212)

GENERAL REMARKS—(continued).

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop 49 ft., R.Q.D. ✓ ft., Bridge 113 ft., Forecastle 40 (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated ✓

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as should appear in the Register Book) 15k (one) —
 Official No. 142845; Signal Letters State if Machinery is fitted aft No
 How are the surfaces preserved from oxidation? Inside Paint & Cement Outside Paint

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors All 5 B m

Where Fitted.	*Length. Feet.	Water Capacity. Tons.	Where Fitted.	*Length. Feet.	Water Capacity. Tons.
Double bottom, aft,	117.0	342	Fore peak tank,		168
Double bottom, under Engines and Boilers,	39.0	159	After peak tank,		279
Double bottom, if under Engines only,		✓	Deep tank, aft,		✓
Double bottom, if under Boilers only,		✓	Deep tank, forward,		✓
Double bottom, forward,	179.23	557	Other tanks, if fitted,		✓
Total capacity of double bottom		1058	(If necessary, furnish further information by sketch.)		

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules. Yes

Order for Special Survey No. 1266


Date 14 Oct. 1918

No. 677 in builder's yard.

DATES OF SURVEYS held while building

1918 Dec. 5. 9. 11. 12. 13. 16. 17. 18. 20. 24. 30. 1919 Feb. 13. Mar. 4. 7. 11. 18. 20. 24. 25. 26. 28. Apr. 1. 4. 8. 10. 14. 17. 24. 25. 28. May 1. 5. 6. 9. 14. 19. 21. 23. 26. 29. Jun. 2. 6. 12. 16. 18. 20. 24. 27. Jul. 2. 4. 7. 8. 9. 15. 17. 18. 24. 28. 29. 30. Aug. 5. 12. 13. 26. 27. 28. Sep. 3. 8. 10. 11. 15. 18. 19. 22. 23. 24. 25. 26.

Surveyor's Signature



© 2020

Total No. of Visits 49

Baker's Register Foundation