

REPORT ON BOILERS.

Sld. No. 32744
No. 16405.


Received at London Office

NOV 27 1939

Report of written report 12/9/39 When handed in at Local Office 16/9/39 Port of **MIDDLESBROUGH**
 Survey held at **Stockton-on-Tees** Date, First Survey **15th August** Last Survey **8/9/1939**
 on the **M/V BEIGNON** (Number of Visits **4**) Tons { Gross **5218** Net **3004**
 Built at **Sunderland** By whom built **Wm. Beckett & Co. Ltd.** Yard No. **653** When built **1939**
 Engines made at **Sunderland** By whom made **Wm. Beckett & Co. Ltd.** Engine No. **653** When made **1939**
 Boilers made at **Stockton** By whom made **Stockton Chemical Eng'g Co. Riley Booth** Boiler No. **6373** When made **1939**
 Nominal Horse Power _____ Owners **Polisement S. & Co. Ltd.** Port belonging to **London**

ULTITUBULAR BOILERS - MAIN, AUXILIARY, OR DONKEY.

Manufacturers of Steel **Steel Company of Scotland Ltd** (Letter for Record **S**)
 Total Heating Surface of Boilers **1660 sq ft** Is forced draught fitted **No.** Coal or Oil fired **Oil**
 No. and Description of Boilers **1 - Single Ended** Working Pressure **120 lbs.**
 Tested by hydraulic pressure to **230 lbs** Date of test **8/9/39** No. of Certificate **6976** Can each boiler be worked separately **Yes.**
 Area of Firegrate in each Boiler _____ No. and Description of safety valves to each boiler **Two direct Spring.**
 No. of each set of valves per boiler { per Rule **15.340"** as fitted **19.20"** Pressure to which they are adjusted **120** Are they fitted with easing gear **Yes.**
 In case of donkey boilers, state whether steam from main boilers can enter the donkey boiler **No.**
 Smallest distance between boilers or uptakes and bunkers or woodwork _____ Is oil fuel carried in the double bottom under boilers **No.**
 Smallest distance between shell of boiler and tank top plating **2' 10"** Is the bottom of the boiler insulated **Yes.**
 Largest internal dia. of boilers **11'-10 5/8"** Length **11'-6"** Shell plates: Material **Steel** Tensile strength **29-33**
 Thickness **1/16"** Are the shell plates welded or flanged **No** Description of riveting: circ. seams { end **DR** inter **3 3/8"**
 Long. seams **T.R.D.B.S** Diameter of rivet holes in { circ. seams **1 1/16"** Pitch of rivets { **5 3/8"**
 Percentage of strength of circ. end seams { plate **68.51** rivets **45.45** Percentage of strength of circ. intermediate seam { plate **84.88** rivets **83.38**
 Percentage of strength of longitudinal joint { plate **84.88** rivets **83.38** Working pressure of shell by Rules **123.5 lbs**
 Thickness of butt straps { outer **9/16"** inner **1/16"** No. and Description of Furnaces in each Boiler **2 - Corrugated (Dighton)**
 Material **Steel** Tensile strength **26-30** Smallest outside diameter **3'-8 1/16"**
 Length of plain part { top _____ bottom _____ Thickness of plates { crown **13/32"** Description of longitudinal joint **Weld**
 Dimensions of stiffening rings on furnace or c.c. bottom _____ Working pressure of furnace by Rules **131 lbs.**
 End plates in steam space: Material **Steel** Tensile strength **26-30** Thickness **27/32"** Pitch of stays **17" x 16"**
 How are stays secured **D. Nuts & washers** Working pressure by Rules **142 lbs**
 Tube plates: Material { front **Steel** back **Steel** Tensile strength { **26-30** Thickness { **13/16"**
 Mean pitch of stay tubes in nests **9 7/8"** Pitch across wide water spaces **14"** Working pressure { front **139 lbs** back **244**
 Girders to combustion chamber tops: Material **Steel** Tensile strength **28-32** Depth and thickness of girder _____
 At centre **7 - 2 @ 5/8"** Length as per Rule **29 7/16"** Distance apart **9"** No. and pitch of stays _____
 In each **2 @ 9"** Working pressure by Rules **134 lbs** Combustion chamber plates: Material **Steel**
 Tensile strength **26-30** Thickness: Sides **19/32"** Back **9/16"** Top **19/32"** Bottom **7/8"**
 Pitch of stays to ditto: Sides **9" x 10"** Back **9 1/2" x 8 3/4"** Top **9" x 9"** Are stays fitted with nuts or riveted over **Nuts**
 Working pressure by Rules **125 lbs** Front plate at bottom: Material **Steel** Tensile strength **26-30**
 Thickness **27/32"** Lower back plate: Material **Steel** Tensile strength **26-30** Thickness **27/32"**
 Pitch of stays at wide water space **13 1/2" x 9 1/2"** Are stays fitted with nuts or riveted over **Nuts.**
 Working Pressure **210 lbs** Main stays: Material **Steel** Tensile strength **28-32**
 Diameter { At body of stay, **2 1/4"** No. of threads per inch **6** Area supported by each stay **2470 sq in**
 Working pressure by Rules **121 lbs** Screw stays: Material **Steel** Tensile strength **26-30**
 Diameter { At turned off part, **1 1/2"** No. of threads per inch **9** Area supported by each stay **900 sq in**
 Working pressure by Rules _____



Working pressure by Rules 125 lb Are the stays drilled at the outer ends No Margin stays: Diameter 15 1/8"
 No. of threads per inch 9 Area supported by each stay 100 sq" Working pressure by Rules 148 lb
 Tubes: Material L.W. Iron External diameter 2 3/4" Thickness 5/16" No. of threads per inch 9
 Pitch of tubes 3 3/4" x 3 3/4" Working pressure by Rules S. 274 lbs. P 160 lbs. Manhole compensation: Size of opening
 shell plate 20" x 16" Section of compensating ring 4" x 1" No. of rivets and diameter of rivet holes 44 - 15/16"
 Outer row rivet pitch at ends 6 1/2" Depth of flange if manhole flanged ✓ Steam Dome: Material None
 Tensile strength _____ Thickness of shell _____ Description of longitudinal joint _____
 Diameter of rivet holes _____ Pitch of rivets _____ Percentage of strength of joint Plate
 Internal diameter _____ Working pressure by Rules _____ Thickness of crown _____ No. and diameter
 stays _____ Inner radius of crown _____ Working pressure by Rules _____
 How connected to shell _____ Size of doubling plate under dome _____ Diameter of rivet holes and
 of rivets in outer row in dome connection to shell _____

Type of Superheater _____ Manufacturers of Tubes
Steel castings
 Number of elements _____ Material of tubes _____ Internal diameter and thickness of tubes _____
 Material of headers _____ Tensile strength _____ Thickness _____ Can the superheater be shut off
 the boiler be worked separately _____ Is a safety valve fitted to every part of the superheater which can be shut off from the boiler
 Area of each safety valve _____ Are the safety valves fitted with easing gear _____ Working pressure as
 Rules _____ Pressure to which the safety valves are adjusted _____ Hydraulic test pressure
 tubes _____, castings _____ and after assembly in place _____ Are drain cocks or valves fitted
 to free the superheater from water where necessary _____

Have all the requirements of Sections 14 to 22 inclusive for boilers been complied with Yes. for and on behalf of
STOCKTON CHEMICAL ENGINEERS & RILEY BOILERS LTD.
The foregoing is a correct description,
S. H. Riley Manufacture
DIRECTOR.

Dates of Survey During progress of work in shops - - Aug. 15. 22. Sept. 1. 3. Are the approved plans of boiler and superheater forwarded herewith 20-5-39
while building During erection on board vessel - - - (If not state date of approval.)
 Total No. of visits Four.

Is this Boiler a duplicate of a previous case ✓ If so, state Vessel's name and Report No. _____

GENERAL REMARKS (State quality of workmanship, opinions as to class, &c.) This boiler has been constructed under special survey in accordance with the Rule requirements & approved plan & was found satisfactory under an hydraulic pressure of 230 lbs/sq. in.

The materials & workmanship are good.
The boiler is to be forwarded to Sunderland to be fitted on board.

This boiler has been securely fixed on board the vessel.
Examined under steam & safety valves adjusted to working pressure in accordance with rule requirements.

In recommendation please see Melus. Rpt.
W. H. Brown.

Survey Fee £ 11 : 2 : - When applied for, 16-9-1939.
 Travelling Expenses (if any) £ 02 : 05 : - When received, 13-11-1939.

R. J. Easthope
 Engineer Surveyor to Lloyd's Register of Shipping

Committee's Minute

FRI. 1 DEC 1939

Assigned See FE. machy rpt.

