

Sheer { Stem..... 104 }  $156 \div 2 = 78.0$ ...Mean  $\frac{52.20}{36/34.67}$

Proportion covered, if less than  $\frac{7}{10}$  this len  
Thickness of usual wood deck less string

ENQUIRY NO. 6323.

FREEBOARD PARTICULARS.

Under Deck Tonnage ..... 5,000.  
Sheer at Aft Perpendicular ..... 4' 4".  
" "  $\frac{1}{8}$  L. from Aft ..... 2' 5 $\frac{1}{4}$ ".  
" " Midships ..... ----  
" "  $\frac{1}{8}$  L. from Forward ..... 4' 10 $\frac{1}{2}$ ".  
" " Fore Perpendicular..... 8' 8".

Length of Erections.

Shelter Deck with 8' 0" Tonnage Space.

Camber of Freeboard Deck ..... 13 $\frac{1}{2}$ ".



© 2020

Lloyd's Register  
Foundation

W404-0133

† In vessels obtaining an allowance for deck erections under Para. 11 where the sheer drops abaft amidships the height of the R.Q.D. is to be taken from the level of the top of the amidship beam.  
‡ In flush-decked vessels the total standard mean sheer means the sheer measured at the stem and stern-

|| The Surveyor should state whether the fall in line of keel or to the water line. If measure