

Pinion Shafts, diameter at bearings

External
Internal

1st

{ 14 1/4" 2nd { 8 1/2" }
2 1/2"

diameter at bottom of teeth of pinion 1st

216

(Received at London Office.....19....)

5291

Place

Newcastle-on-Tyne

Date

22 August

1928

We request that the Committee of Lloyd's Register will instruct
Society's Surveyors to survey during construction and installation
the twin sets of Bauer Wach Low Pressure Turbines and Gear, our Engines
1322 intended for s.s. "PORT SYDNEY".

We undertake to arrange for every facility to be given to the
Surveyors to carry out the duty in question, and we agree to pay the fees
the Surveyors' services, in addition to the actual travelling and other
expenses incurred by the Surveyors in connexion therewith.

This request is made upon the terms of the Rules and Regulations
Lloyd's Register of Shipping, which provide that:—

While the Committee use their best endeavours to ensure that the functions of the Society are properly executed, it is to be
understood that neither the Committee nor the Society are under any circumstances whatever to be held responsible for any inaccuracy
in any report or certificate issued by the Society or its Surveyors, or in any entry in the Register Book or other publication of the
Society, or for any error of judgment, default, or negligence of the Surveyors, or other Officers or Agents of the Society.

the Secretary,

Lloyd's Register of Shipping,

71, Fenchurch Street, London, E.C.3.

FOR

SWAN, HUNTER & WIGMAN, RICHARDSON, LTD.



© 2019

DIRECTOR

Lloyd's Register
Foundation
W. H. Smith
31/8/28

Is Forced Draft fitted

No. and Description of Boilers

W412-0246