



© 2019
Lloyd's Register
Foundation

Single Sc. CANADA

2 off	15 HP	compound wound	electromotors	for the engine room fans
1 "	4 HP	shunt	"	" " for peak pumps.
1 "	1.5 "	compound	"	"
1 "	3.5 "	"	"	" } work shop machinery
1 "	0.3 "	"	"	"
1 "	3 "	"	"	" " radio
1 "	5 "	"	"	" " engine room hoist
3 "	85 "	"	"	" " CO ₂ compressor (cargo)
1 "	24 "	"	"	" " CO ₂ — — (provisions)
2 "	7 "	"	"	" " CO ₂ cooling water pumps
3 "	12 "	"	"	" " brine pumps (cargo)
1 "	2.7 "	"	"	" " brine pumps (provisions)
8 "	25 "	"	"	" " 3 tons winches
4 "	35 "	"	"	" " 7 tons winches - warping winch
5 "	33 "	"	"	" " 5 tons winches
1 "	62 "	"	"	" " winchless
1 "	16 "	"	"	"
2 "	12 "	"	"	"
2 "	7.5 "	"	"	" " fans in refrigerated holds
2 "	3.6 "	"	"	"
1 "	1.4 "	"	"	"
2 "	Aeroto screw fans, Dia 17.5, Series 82 of 796			
2 "	2.2 HP	compound wound	electromotor	
3 "	3.5 "	"	"	"
1 "	1.25 "	"	"	"
1 "	1.8 "	"	"	" " for Thomsen ventilators
1 "	1.9 "	"	"	"
1 "	0.9 "	"	"	"
1 "	0.6 "	"	"	"

Further a number of small electromotors have been fitted for laundry & galley machinery etc.

1 off 60 HP series wound electromotor for the steering gear.

The above is a correct description.

AKTIESELSKABET
NAKSKOV SKIBSVÆRFT

Rising *Christiansen*

W420-0046 3/3