

Lloyd's Register of Shipping.
SURVEYS FOR FREEBOARD.

PARTICULARS IN RESPECT OF STEAM SHIPS HAVING SPAR OR
AWNING DECKS.

Port of Survey _____
Date of Survey 22/07/29
Name of Surveyor _____

Ship's Name.	Port of Registry and Nationality.	Official Number.	Gross Tonnage.	Date of Build.	Particulars of Classification.
"Bogo"					
Number in Register Book					

Number in Register Book				
Registered dimensions from Ship's Register.	LENGTH.	BREADTH.	DEPTH.	UNDER DECK Tonnage.
Length on LOADLINE		Frame Depth Rule „	Ceiling Sheer	Peak Tanks
CORRECTED DIMENSIONS.	239.66			

Moulded Depth as measured 17-3 Main Deck.
 " " " Spar or Awning Deck.

Addition for Keel below base line for draught record.....inches.

NOTE.—If the depth is measured when vessel is afloat, the details of measurement should be reported

Co-efficient of fineness	
Any modification necessary	}
[Para. 4 (a) to (e)*]	
Co-efficient as corrected	

	CORRECTION FOR LENGTH:—
Length of Ship on Load Line.....	239.66
Length in Table	207.00
Difference.....	32.66
Correction for 10ft.....	5
× Difference ÷ 10 =	1.63
	+ 13/4

Allowance for strength in excess of Lloyd's rules =

State particulars—

Height of 'Tween Decks.....
(From top of beam to top of beam at side)
Correction for Height of 'Tween Decks in Spar-decked Ships.....

Freeboard Table ~~B~~ or C
Correction for Length.....
Correction for Height of 'Tween Decks in Spar-decked Ships.....

Correction for Strength in excess of Lloyd's rules.....

Correction for Iron Deck if required.....

Other Corrections (if any).....

Winter Freeboard.....	242	0.37
Summer Freeboard.....		
Indian Summer Freeboard.....		
N. A. Winter Freeboard.....		

Correction necessary because clearside amidships measured
in accordance with the Statute is not taken at inter-
section of the wood or steel deck with side

Winter Freeboard from Deck Line	0 - 4 1/2
Summer " "	
Indian Summer "	
N.A. Winter "	

FRESH WATER LINE	above centre of Disc
INDIAN SUMMER LINE	" "
WINTER LINE	below " "
WINTER NORTH ATLANTIC LINE	" "

NOTE.—All vessels equal in strength to Lloyd's Spar-decked rule, or which, although in excess of that rule, do not come up to Lloyd's requirements for Ships of full scantlings to the upper deck, are to be considered as Spar-decked Ships, the freeboard for which will vary with up to Lloyd's requirements for a Spar-decked Vessel, are to be considered as Awning-decked Ships, the freeboard for which will vary with their strength.

Do all the Frames extend to the top Height in the Spar deck?

Awning deck?

Do all the Frames extend to the top height in the Poop?

Bridge House?

Forecastle?

To what height do the Reverse Frames extend?

Has the Poop an efficient Iron Bulkhead at the fore end?

Give particulars of the means for closing the openings in Bulkhead

Is the Poop connected with the Bridge House?

Has the Bridge House an efficient Bulkhead at the fore end?

Give particulars of the means for closing the openings in Bulkhead

What is the thickness of the Bridge Front plating?

and Coaming plate?

Give scantlings and spacing of the Stiffeners

Are bracket plates fitted at each end of the Stiffeners?

Are hor'l. brackets fitted connecting Bridge Bulk'd. with Bulwarks?

Has the Bridge House an efficient Iron Bulkhead at the after end?

How are the openings closed?

Is the Forecastle at least as high as the main or top-gallant rail?

Has the Forecastle an efficient Iron or Wood Bulk'd. at after end?

Are the Engine and Boiler openings covered by a Bridge, Poop, or enclosed by a Strong Iron or Steel Deckhouse?

If the openings are not so protected are the exposed parts of the Casings efficiently constructed?

Give thickness of plating; scantlings and spacing of Stiffeners

What is the height of the exposed Casings?

Are suitable means provided for closing all openings in them in bad weather?

Are the Weather Deck Hatchways efficiently constructed and at least equal to the requirements of Section 28 of the Rules for 1904-5? Give particulars below:—

Position and Size.		Ship.		Rule.		Ship.		Rule.		Ship.		Rule.	
Item.		Ship.		Rule.		Ship.		Rule.		Ship.		Rule.	
COAMING.	Height above top of DECK												
	Thickness { Sides.....												
	{ Ends.....												
SHIFTING BEAMS OR WEB PLATES.	Number												
	Section and Scantlings												
	Material												
* FORE AND AFTERS.	Number												
	Section and Scantlings												
	Material												
HATCHES Thickness													
Remarks.....													

* When the Fore and Afters are of wood the depth should be stated from the underside of the hatches.

(If the sill of the lowest side scuttle will be less than 6 inches above the Indian Summer Load Line if assigned under the tables, state vertical distance from top of deck at side amidships to lower edge of lowest side scuttle.)



Show hereon line of Floors or Tank Top with position of any Breaks in same; also height of Peak Tank tops, &c., &c.

State any special features in the construction of the Vessel

Builder's name and yard number

Names of sister vessels

Owners

Address

Fee £

Received by me



© 2019

Lloyd's Register
Foundation