

Kpt. 13.

REPORT ON ELECTRIC FITTINGS.

No. 81948.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

-8 NOV 1927

Date of writing Report

19

When handed in at Local Office

5/11/1027

Port of

Newcastle-on-Tyne

No. in Survey held at

Newcastle.

Reg. Book. Supp.

Date, First Survey Aug. 16.

Last Survey

Sept. 21.

1927.

39985

on the

British Endeavour

(Number of Visits.....)

Built at

Newcastle.

By whom built

Armstrong Whitworth & Co.

Card No. 1025

Tons

Gross

Net

When built 1927

Owners

British Tanker Co. Ltd

Port belonging to

London

Electric Light Installation fitted by

Armstrong Whitworth & Co. Ltd

Contract No. 1025

When fitted 1927.

System of Distribution

Dontle wire

Pressure of supply for Lighting

110

volts, Heating

volts, Power

volts.

Direct or Alternating Current, Lighting

Direct

Power

If alternating current system, state frequency of periods per second

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off

Yes

Generators, do they comply with the requirements regarding rating

Yes

are they compound wound

Yes

are they over compounded 5 per cent.

Yes

if not compound wound state distance between each generator

Where more than one generator is fitted are they arranged to run in parallel

No

is an adjustable regulating resistance fitted in series with each shunt field

Yes

Are all terminals accessible, clearly marked, and furnished with sockets

Yes

are they so spaced or shielded that they cannot be accidentally earthed, short circuited, or touched

Yes

Are the lubricating arrangements of the generators as per Rule

Yes

Position of Generators

On dynamo flat at after end of engine room

is the ventilation in way of the generators satisfactory

Yes

are they clear of all inflammable material

Yes

if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the generators

and

are the generators protected from mechanical injury and damage from water, steam or oil

Yes

are their axes of rotation fore and aft

Yes

Earthing, are the bedplates and frames of the generating plant efficiently earthed

Yes

are the prime movers and their respective generators in metallic contact

Yes

Main Switch Boards, where placed

On dynamo flat at after end of engine room

If the generators and main switchboard are not placed in the same compartment, is each generator provided with a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes

Yes

are they protected from mechanical injury and damage from water, steam or oil

Yes

if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards

are they constructed wholly of durable, non-ignitable non-absorbent materials

Yes

is all insulation of high dielectric strength and of permanently high insulation resistance

Yes

if semi-insulating material is used, are all conducting parts insulated from the slab

with mica or micaite or other non-hygroscopic insulating material, and the slab similarly insulated from its framework

Yes

and is the frame effectively earthed

Yes

Are the fittings as per Rule regarding:— spacing or shielding of live parts

Yes

accessibility of all parts

Yes

absence of fuses on back of board

Yes

proportion of omnibus bars

Yes

individual fuses to voltmeter, pilot or earth lamp

Yes

connections of switches

Yes

Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches

+ Double pole fuses on dynamo mains + on each outgoing circuit

Instruments on main switchboard

one

ammeters

one

volts

synchronising device for paralleling purposes.

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system

Earth lamps

coupled to earth through switches & fuses


Switches, Circuit Breakers and Fusible Cut-outs, do these comply with the requirements of the Rules

Yes

Joint Boxes Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule

Yes

W421-0149 1/2



© 2019

Lloyd's Register Foundation

Cables: Single, twin, concentric, or multicore *single twin* are the cables insulated and protected as per Tables IV or V of the Rules *Yes*

Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load *3.9 volts*

Cable Sockets and other connections, are the ends of all cables having a sectional area of 0.04 square inch and above provided with soldering sockets *Yes*

Paper Insulated Cables. If cables are paper covered, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound *Yes*

Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage *Yes*

Support and Protection of Cables, state how the cables are supported and protected *head covered & armoured clipped up with galvanised iron clips along fore & aft gangway & in engine room. head cut in cabins*

If cables are run in wood casings, are the casings and caps secured by screws *Yes* are the cap screws of brass *Yes* are the cables run in separate grooves *Yes* If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VIII *Yes*

Refrigerated Chambers, if lights are fitted, are the cables and fittings in accordance with the special requirements *Yes*

Joints in Cables, state if any, and how made, insulated, and protected *none made*

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tube or watertight glands *Yes*

Bushes in Beams and Non-watertight Partitions, where armoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed *Yes* state the material of which the bushes are made *lead*

Earthing Connections, state what earthing connections are fitted and their respective sectional areas *Yes*

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule *Yes*

Emergency Supply, state position and method of control of the emergency supply and how the generator is driven *none fitted*

Navigation Lamps, are these separately wired *Yes* controlled by separate switch and separate fuses *Yes* are the fuses double pole *Yes*

are the switches and fuses grouped in a position accessible only to the officers on watch *Yes*

has each navigation lamp an automatic indicator as per Rule *Yes*

Secondary Batteries, are they constructed and fitted as per Rule *Yes*

Fittings, are all fittings on weather decks, in storerooms and engine rooms and where exposed to drip or condensed moisture, watertight *Yes* are any fittings placed in spaces in which goods are liable to be stored in close proximity to them; if so, how are they protected *Yes*

are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected *gaslight guarded*

pendants fitted in pump room roof. how are the cables led *in gaslight pipe wholly outside the pump room.*

where are the controlling switches situated *in lobby to bridge space.*

Searchlight Lamps, No. of *Yes* whether fixed or portable *Yes* are their fittings as per Rule *Yes*

Are Lamps, other than searchlight lamps, No. of *Yes* are their live parts insulated from the frame or case *Yes* are their fittings as per Rule *Yes*

Motors, are their working parts readily accessible *Yes* are the coils self-contained and readily removable for replacement *Yes* are the brushes, brush holders, terminals and lubricating arrangements as per Rule *Yes* are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material *Yes*

are they protected from mechanical injury and damage from water, steam or oil *Yes* are their axes of rotation fore and aft *Yes*

if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated forced draught, drip or flame proof type *Yes*

Yes if not of this type, state distance of the combustible material horizontally or vertically above the motors *Yes* and *Yes*

Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed and fitted as per Rule *Yes*

Lightning Conductors, where lightning conductors are required, are these fitted as per Rule *Yes*

Ships carrying Oil having a Flash Point less than 150° F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings *Yes*

section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings *Yes*

If portable lamps for use in dangerous spaces are supplied, are they of a type approved by the Home Office *Yes*

PARTICULARS OF GENERATING PLANT.

DESCRIPTION OF GENERATOR.	No of	RATED AT				DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.	
		Kilowatts.	Volts.	Ampères.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.
MAIN	2	10	110	91	340	single cylinder steam engine		
AUXILIARY								
EMERGENCY								
ROTARY TRANSFORMER								

LIGHTING AND HEATING CONDUCTORS.

Ref. No.	DESCRIPTION.	No. of Conductors.	Effective Area of each Conductor. Sq. Ins.	COMPOSITION OF STRAND.		Total Maximum Current. Amperes.	Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
				No.	Diameter.				
	MAIN GENERATOR	2	.07592	19	.072	91.0	40	V.I.R	head covered
	EQUALISER CONNECTIONS								
	AUXILIARY GENERATOR								
	EMERGENCY GENERATOR								
	ROTARY TRANSFORMER								
	AUXILIARY SWITCHBOARDS								
	ENGINE ROOM								
	BOILER ROOM	2	.00701	7	.036	12.6	30	50	50
	ACCOMMODATION	2	.06	19	.064	27.6	600	50	50
	50 crew's bio box	2	.01462	7	.052	8	400	50	50
	50 midships	2	.00455	7	.029	10.8	20	50	head covered
	Pump room	2	.00455	7	.029	8.8	20	50	50
	Eng. Acc.	2	.00701	7	.036	10.0	150	50	head covered
	Navigation	2	.02214	7	.064	12.5	720	50	50
	WIRELESS	2	.01462	7	.052	15	680	50	50
	SEARCHLIGHT								
	MASTHEAD LIGHT	2	.00299	3	.036	.5	320	50	Turn 15° arm'd
	SIDE LIGHTS	2	.00194	3	.029	.5	100	50	head covered
	COMPASS LIGHTS	2	.00194	3	.029	.25	40	50	50
	STERN LIGHTS	2	.00299	3	.036	.5	720	50	Turn 15° arm'd
	CARGO LAMPS	2	.00299	3	.036	1.6	80	50	50
	ARO LAMPS								
	HEATERS								

MOTOR CONDUCTORS.

Ref. No.	DESCRIPTION.	No. of Motors.	Effective Area of each Conductor. Sq. Ins.	COMPOSITION OF STRAND.		Total Maximum Current. Amperes.	Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
				No.	Diameter.				
	BALLAST PUMP								
	MAIN BILGE LINE PUMPS								
	GENERAL SERVICE PUMP								
	EMERGENCY BILGE PUMP								
	SANITARY PUMP								
	CIRC. SEA WATER PUMPS								
	CIRC. FRESH WATER PUMPS								
	AIR COMPRESSOR								
	FRESH WATER PUMP								
	ENGINE TURNING GEAR								
	ENGINE REVERSING GEAR								
	LUBRICATING OIL PUMPS								
	OIL FUEL TRANSFER PUMP								
	WINDLASS								
	WINCHES, FORWARD								
	WINCHES, AFT								
	STEERING GEAR—								
	(a) MOTOR GENERATOR								
	(b) MAIN MOTOR								
	WORKSHOP MOTOR								
	VENTILATING FANS								



© 2019

Lloyd's Register Foundation

W421-0149 2/2

All Conductors are of annealed copper conforming to British Standard Specification No. 7.
The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.
The foregoing is a correct description.

Sir W. G. Armstrong Whitworth & Co. Ltd. Electrical Engineers.

Date *4/11/27.*

COMPASSES.

Distance between electric generators or motors and standard compass *244 feet*

Distance between electric generators or motors and steering compass *240 feet.*

The nearest cables to the compasses are as follows:—

A cable carrying *.25* Amperes *on the* ~~feet from~~ standard compass *8* feet from steering compass.

A cable carrying *.25* Amperes *8* feet from standard compass *on the* ~~feet from~~ steering compass.

A cable carrying *4.5* Amperes *11* feet from standard compass *8* feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power *yes*

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted *yes*

The maximum deviation due to electric currents was found to be *nil* degrees on *all* course in the case of the standard compass, and *nil* degrees on *all* course in the case of the steering compass.

SIR W. G. ARMSTRONG, WHITWORTH & CO. LTD.
ARMSTRONGS SHIPBUILDING MANAGERS LTD.

W. G. Armstrong
MANAGING DIRECTOR

Builder's Signature.

Date *4-11-27*

Is this installation a duplicate of a previous case *no* If so, state name of vessel

General Remarks (State quality of workmanship, opinions as to class, &c.)

The above installation is in accordance with the Society's Rules. The vessel is eligible in my opinion for notation elec light, wireless

It is submitted that
this vessel is eligible for
THE RECORD.

elec. light
W. T. Badger
18/11/27.

Total Capacity of Generators *20* Kilowatts.

The amount of Fee ... £ *17 : 10 :* *13-42665-127*

Travelling Expenses (if any) £ :

When received,
£ *10.0.0 - 25/10/27*
£ *7.10.0 - 7/11/27*

W. T. Badger

Surveyor to Lloyd's Register of Shipping.

Committee's Minute

Assigned

Elec Lt