

Preliminary
Lloyd's Register of Shipping.
SURVEYS FOR FREEBOARD.—STEAM SHIPS.

Index No. 31215
(For London Office only.)

PARTICULARS RELATING TO ALL STEAM SHIPS EITHER FLUSH DECKED, OR WITH TOP GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, OR WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.

Port of Survey _____
Date ~~at Survey~~ 15th April 1924
Name of Surveyor _____

Ship's Name. <u>Hawthorn Leslie & Co's</u> <u>S.S. No 535</u>	Port of Registry and Nationality.	Official Number.	Gross Tonnage.	Date of Build.	Particulars of Classification. <u>+100 A.1. Contemplated.</u> <u>Revised Rules</u>
Number in Register Book _____					

Registered dimensions from Ship's Register.	LENGTH.	BREADTH.	DEPTH.	UNDER DECK TONNAGE.
	<u>225.0</u>	<u>32.14</u>	<u>14.46</u>	
Length on LOADLINE.	<u>225.0</u>	mean Frame Depth <u>6 3/4</u> Rule " <u>4</u> <u>2 3/4</u> <u>x 2 = 46</u>	Ceiling <u>fitted</u> Sheer <u>✓</u> <u>Level Tank</u>	Peak Tanks
CORRECTED DIMENSIONS.	<u>225.0</u>	<u>31.68</u>	<u>14.46</u>	

Moulded Depth as ~~measured~~ ^{given} 16'-6"
Addition for Keel below base line for draught record.....inches.

NOTE.—If the depth is measured when vessel is afloat, the details of measurement should be reported.

16-6
8
14-3
2-8
14-5 1/2

CORRECTION FOR LENGTH.

Length of Ship on Loadline..... 225.0
Length in Table 198.0
Difference 27.0
Correction for 10ft., Table A. 1.0 Table C.
x Difference divided by 10 2.7 (if required.)
If 1/10ths length covered divide by 2 1.35
+ 1 1/4"

CORRECTION FOR IRON DECK.

Proportion covered, if less than 2/10ths length covered609
Thickness of usual wood deck, less stringer 3" - 2"

CORRECTION FOR ROUND OF BEAM.

Breadth at Gunwale amidships..... 32.0
Round of Beam 8"
Normal round..... 8"
Difference ✓ ÷ 2 =
Proportion of Deck uncovered (Para. 19)

NOTE.—The round of beam should be reported on the full breadth of vessel at the gunwale.

Co-efficient of fineness.....
Any modification necessary {
[Para. 4 (a) to (e)]* }
Co-efficient as corrected69 Given by Builders

Sheer { Stem..... 43 } 65 ÷ 2 = 32.5...Mean
at { Sternpost ... 22 }
Sheer at 1/2 of the length from { Stem } 32.5
Sternpost } 32.5...Mean
Gradual mean Sheer 32.5
Standard mean Sheer [Table, Para. 18] 32.5 Correction
Difference..... ✓ ÷ 4 = ✓
§ If limited as Para. 18 (f)

Rise in Sheer { At front of bridge house.....
from amidships {
[Para. 18 (e)] { At after end of forecastle

¶ Fall in Sheer {
Para. 18 (d) } ÷ 2 =
Length uncovered Correction

ALLOWANCE FOR DECK ERECTIONS:—

Freeboard, Table C..... 0' 4 3/4"
Correction for Length, if required (Para. 12, 13, and 14)
Freeboard by Table A, corrected for sheer, and for length, if required (Para. 12, 13, and 14) } 2" 8 3/4"
Difference 2" 1"
Percentage as below..... 41.35%
10.33

Correction for R. Q. Dk. if engine and boiler openings not covered by bridge house (Para. 11) Covered by Bridge
Allowance for Deck Erections - 10 1/4"

	Length.	Length allowed.	Height.
Forecastle.....	<u>24.0</u>	<u>24.0</u>	<u>4.0</u>
Bridge House	<u>61.0</u>	<u>61.0</u>	<u>4.0</u>
† Raised Qr. Dk.....	<u>52.0</u> <u>3.25</u> <u>x .609 = 1.98</u>	<u>52.0</u>	<u>3.10</u>
Poop.....			

Total 134.0 x .609
Length of Ship 225.0

Corresponding percentage { 41.35% well 85ft long
(Para. 11, 12, 13, or 14) }

FREEBOARD recommended amidships from centre of Disc to top of Statutory Deck Line, ~~Wood~~ (Steel) Deck:—

Fresh Water Line	above centre of Disc	...
Indian Summer Line	" " "	...
Winter Line	below " "	...
Winter North Atlantic Line	" " "	...

Correction necessary because clearside amidships, measured in accordance with the Statute is not taken at the intersection of the ~~wooden~~ steel deck with side.

Winter Freeboard 1" 9 3/4"
Summer Freeboard 2.3 1/2 2 1/4 1" 4 1/2"
Indian Summer Freeboard 1" 5 1/4"
N. A. Winter Freeboard 3 1/2 2" 1 1/4"

Winter Freeboard from deck line 1" 11 1/4"
Summer " " " 1" 9"
Indian Summer " " " 1" 6 3/4"
N. A. Winter " " " 2" 2 3/4"

§ If the frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside of ceiling should be reported if possible.
† In vessels obtaining an allowance for deck erections under Para. 11 where the sheer drops abaft amidships the height of the R.Q.D. is to be taken from the level of the top of the amidship beam.
§ In flush-decked vessels the total standard mean sheer means the sheer measured at the stem and stern-post. In vessels having poops and forecastles, it means the sheer measured at points distant one-eighth of the vessel's length from stem and stern-post.

† State dimensions of freeing port area on back of this form.

‡ The Surveyor should state whether the fall in sheer as reported is measured relatively to the straight line of keel or to the water line. If measured relatively to water line the vessel's draft at time of survey, and also the usual load draft forward and aft should be reported.