



N.B.—If this Report is copied by Copying Press, especial care must be taken that the copying paper is not so much damped as to spread the ink, or to cause it to show through to the other side.

THE SURVEYORS ARE REQUESTED NOT TO WRITE ACROSS THIS MARGIN.

When Anchors or Cables are supplied, the particulars are to be reported in the following form:—

**ANCHORS.**

Number of Certificate.	Anchors.*	WEIGHT, EX. STOCK.			WEIGHT OF STOCK.			TEST PER CERTIFICATE.			WEIGHT REQUIRED BY RULE.			Description of Anchor.	Makers.	Where and when tested and Superintendent.
		Cwts.	qrs.	lbs.	Cwts.	qrs.	lbs.	Tons	Cwts.	qrs.	lbs.	Cwts.	qrs.			
95031.	1st Bower ...	11	2	30	3	1	8	13	12	3	0.			LOCKJAW TYPE.	J. Wright & Co.	N. 6. 3. 36. H. Green.
	2nd "														Tipton. Staff.	
	3rd "															
	Collective Weight.															
	Stream .....															
	Kedge.....															

\* When a bower anchor is supplied it must be clearly stated whether it is a 1st, 2nd, or 3rd bower.

**CHAIN CABLES.**

Number of Certificate.	Length and size supplied.		Test per Certificate.		WEIGHT OF CHAIN CABLE.		Length and size per Rule.		Description.	Makers of Cables.	When and where tested and Superintendent.
	Length.	Diam.	Statutory.	Breaking.	Supplied.	Per Rule.	Length.	Diam.			
103131	15	1 1/8"	15 1/2	30 1/2	10. 3. 9.				Short Link J. Wright & Co. Tipton	15. 1. 26. N. H. Green	
103132	15	1 1/8"	15 1/2	30 1/2	10. 3. 0.				" " " " "	" " " " "	
102942	90	1 1/8"	15 1/2	30 1/2					" " " " "	14. 11. 25. N. J. a. Reef.	
	Iron Stream Chain or Steel Wire...										

90 fathoms only put on board, not 120 as per Certificate - also see En. letter 25/11/34