

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.—STEAM SHIPS.

PARTICULARS RELATING TO ALL STEAM SHIPS EITHER FLUSH DECKED, OR WITH TOP GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, OR WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.

Port of Survey

Date of Survey

Name of Surveyor

| | | | | | | | | |
|---|-------------------------|---|--|--|--|--|---|--|
| Ship's Name. "DICIDO" | | Port of Registry and Nationality. Helsingborg Swedish | | Official Number. 5309 | Gross Tonnage. | Date of Build. 1903-5 h.t. | Particulars of Classification. + 100 A1 | |
| Number in Register Book 394 | | | | | | | | |
| Registered dimensions from Ship's Register. | LENGTH. 250.0 | BREADTH. 37.25 | DEPTH. 18.9 | UNDER DECK TONNAGE. 1420.71 | Moulded Depth as measured..... 21' 2" | | | NOTE.—If the depth is measured when vessel is afloat, the details of measurement should be reported. |
| Length on LOADLINE. | 250. | Frame Depth 8 Rule = - .5 | Ceiling <i>filter</i> Sheer 7.49 | Peak Tanks <i>included</i> | Addition for Keel below base line for draught record..... 1.3 inches. | | | |
| CORRECTED DIMENSIONS. | 250 | 36.75 | 19.39 | 1420.71 | CORRECTION FOR LENGTH. | | | |
| Co-efficient of fineness..... .80 | | Any modification necessary { [Para. 4 (a) to (e)]* CPB. | | Co-efficient as corrected78 | | Length of Ship on Loadline..... 250 | | |
| | | | | | | Length in Table 254 | | |
| | | | | | | Difference 4 | | |
| | | | | | | Correction for 10ft., Table A. 1.2 Table C. .6 | | |
| | | | | | | × Difference divided by 1048 (if required.) .24 | | |
| | | | | | | If 1/10ths length covered divide by 2 - 1/2 - 1/4 | | |
| | | | | | | CORRECTION FOR IRON DECK. | | |
| | | | | | | Proportion covered, if less than 1/10ths length covered472 | | |
| | | | | | | Thickness of usual wood deck, less stringer 3 1/2 - 1 3/4 | | |
| | | | | | | CORRECTION FOR ROUND OF BEAM. | | |
| | | | | | | Breadth at Gunwale amidships..... 36 | | |
| | | | | | | Round of Beam 9 1/4 | | |
| | | | | | | Normal round..... 9 | | |
| | | | | | | Difference ÷ 2 = | | |
| | | | | | | Proportion of Deck uncovered (Para. 19) | | |
| | | | | | | Freeboard, Table A 4' 3 1/4" | | |
| | | | | | | Correction for Sheer - 4 1/2" | | |
| | | | | | | Correction for Length 3' 10 3/4" | | |
| | | | | | | Allowance for Deck Erections - 7 3/4" | | |
| | | | | | | Correction for Round of Beam..... 3' 2 1/2" | | |
| | | | | | | Correction for fall in Sheer (if any)..... | | |
| | | | | | | Correction for Steel Deck (if required) - 1 3/4" | | |
| | | | | | | Additions for non-compliance with provisions of { Para. 11 (d) and (e) † 3' - 0 3/4" | | |
| | | | | | | Other Corrections (if any) | | |
| | | | | | | Winter Freeboard 3' - 0 3/4" | | |
| | | | | | | Summer Freeboard 2' - 9 3/4" | | |
| | | | | | | Indian Summer Freeboard 2' - 6 3/4" | | |
| | | | | | | N. A. Winter Freeboard 3' - 2 3/4" | | |
| | | | | | | Correction necessary because clearside amidships, measured in accordance with the Statute is not taken at the intersection of the wood or steel deck with side. Nil | | |
| | | | | | | Winter Freeboard from deck line | | |
| | | | | | | Summer " " " " | | |
| | | | | | | Indian Summer " " " " | | |
| | | | | | | N. A. Winter " " " " | | |

SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, **W**, Steel, Deck:—

33.50 = .851 metres

Tropical Fresh Water Line above Centre of Disc ... **8.07** = **2.05** m
 Fresh Water Line " " ... **5.07** = **1.29** m
 Tropical Line " " ... **3** = **.76** m
 Winter Line below " " ... **3** = **.76** m
 Winter North Atlantic Line " " ... **5** = **1.27** m

Tropical Fresh Water Freeboard ... **.646**
 Fresh Water " " ... **.722**
 Tropical " " ... **.775**
 Winter " " ... **.927**
 Winter North Atlantic " " ... **.978**

130 SEP 1932

W434-0043

RECEIVED 19 APR 1938

RECEIVED 14 SEP 1932

MARKING FORM

RECEIVED 8 - SEP 1932

Lloyd's Register Foundation