

BOILER

TRACING-10059- — SCALE- 1 INCH TO A FOOT. — SCHEDULE L.

- WRITTEN DIMENSIONS ONLY TO BE TAKEN



LYDD'S	2255(15-2) x 81-18 146.625.	162.3 LBS.
WORKING PRESSURE		160 "
TEST	"	320 "
HEATING SURFACE ON TUBES		1095 sq ft
"	" OTHER PARTS	285 "
"	" TOTAL	1378. "
EX. FRONT TUBE PLATE		1355 "
EFFEC: AREA OF STAYS.		
3 1/4" STAY TUBES	5" 9 THRS PER IN.	2.17 SQUINS
3 1/2" " "	4" 9 " " "	1.64 " "
2 3/4" MAIN STAYS	6 THRS PER IN.	5.05 " "
2 1/4" " " "	6 " " "	3.26 " "
1 3/4" SCREWED	11 " " "	2.10 " "
1 5/8" " " "	11 " " "	1.79 " "
PLATES-RIVETS & STAYS - ALL STEEL		
TUBES, WROUGHT IRON.		
HOLES TO BE DRILLED IN PLACE AFTER BENDING		
TENSILE STRENGTH OF SHELL PLATE, NOT LESS THAN		29 TONS PER SQ
"	" MAIN STAYS	27 " "

MANHOLE 1'-4" x 1'-0"
DOUBLING 2'-6" x 2'-2" x 15' 16"

J.A.S.
22/7/02

CONTRACT N° 1454.2 OF

S. S. "Dixido"

Sunderland! No. 21216



© 2019

Lloyd's Register
Foundation

4

C 1454



© 2019


Lloyd's Register
Foundation

Craig Tappan
94

Sicid.

Mdt. 3578.

RETAIN



© 2019

Lloyd's Register
Foundation
W434-0057