

Rpt. 13.

S. S. Kabinda
ex Belgier

No. 15250

REPORT ON ELECTRIC FITTINGS.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

Date of writing Report 15th Sept. 1927. When handed in at Local Office 17/9 1927

Port of Antwerp.

No. in Survey held at Antwerp
Reg. Book.Date, First Survey 6th Sept.Last Survey 14th Sept.

1927.

25805 on the

S/S "KABINDA"

(Number of Visits 2)

Tons { Gross 5077.
Net 3122.

Built at Belfast

By whom built Harland & Wolff, Ltd.

Yard No. ✓

When built 1917-8.

Owners Cie. Africaine de Nav. S.A.

Port belonging to

Antwerp.

Electric Light Installation fitted by Clebs Vanale et Industrielle

Contract No. ✓

When fitted ✓

System of Distribution

Compound wound direct current ✓

Pressure of supply for Lighting

100 V.

volts, Heating

volts, Power

volts.

Direct or Alternating Current, Lighting

Direct ✓

Power

If alternating current system, state frequency of periods per second

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off

yes ✓

Generators, do they comply with the requirements regarding overload

yes ✓

are they compound wound

yes ✓

are they over compounded 5 per cent.

yes ✓

if not compound wound state distance between each generator

Where more than one generator is fitted are they arranged to run in parallel

is an adjustable regulating resistance fitted in series with each shunt field

Are all terminals accessible and clearly marked

yes

are they so spaced or shielded that they cannot be accidentally earthed, or short circuited

yes

Are the lubricating arrangements of the generators as per Rule

yes

Position of Generators

at engine room plat form

is the ventilation in way of the generators satisfactory

yes

are they clear of all inflammable material

yes

if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the generators

are the generators protected from mechanical injury and damage from water, steam or oil

yes

are their axis of rotation fore and aft

yes

Earthing, are the bedplates and frames of the generating plant efficiently earthed

yes

are the prime movers and their respective generators in metallic contact

yes

Main Switch Boards, where placed

on lower part of watertight bulkhead at after end of engine room

If the generators and main switchboard are not placed in the same compartment, is each generator provided with a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes

yes

are they protected from mechanical injury and damage from water, steam or oil

yes

if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards

are they constructed wholly of durable, incombustible non-absorbent materials

yes

is all insulation of high dielectric strength and of permanently high insulation resistance

yes

if semi-insulating material is used, are all conducting parts connected to one pole insulated from the slab with mica or micanite and the slab similarly insulated from its framework

yes

frame effectively earthed

yes

Are the following fittings as per Rule, viz.:— spacing or shielding of live parts

accessibility of all parts

yes

absence of fuses on back of board

yes

proportion of omnibus bars

individual fuses to voltmeter, pilot or earth lamp

yes

connections of switches

yes

Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches

For generator

double pole and fuse to each pole for each circuit

Instruments on main switchboard

one

ammeters

one

volts meters

synchronising device for paralleling purposes.

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system

two test

earthing clamps

Switches, Circuit Breakers and Fusible Cut-outs, do these comply with the requirements of the Rules

yes

Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule

yes

W435-0067 (1/2)

© 2019

Lloyd's Register
Foundation

Insulation of Cables, state type of cables, single or twin single are the cables insulated and protected as per Tables III or IV of the Rules yes

Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load 2%

Cable Sockets and other connections, are the ends of all cables having a sectional area of 0.007 square inch and above provided with soldering sockets yes

Paper Insulated Cables, If cables are paper covered, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound —

Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage yes

Support and Protection of Cables, state how the cables are supported and protected sheet plating with clips with brass screws and galvanised pipes

If cables are run in wood casings, are the casings and caps secured by screws —, are the cap screws of brass —, are the cables run in separate grooves —. If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VI yes

Refrigerated Chambers, if lights are fitted, are the cables and fittings in accordance with the special requirements —

Joints in Cables, state if any, and how made, insulated, and protected none

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands yes

Bushes in Beams and Non-watertight Positions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed yes state the material of which the bushes are made fire

Earthing Connections, state what earthing connections are fitted and their respective sectional areas —

—, are their connections made as per Rule —

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule — yes 8 e. Engine Room 3 e. Boiler Room

Emergency Supply, state position and method of control of the emergency supply and how the generator is driven —

Navigation Lamps, are these separately wired yes, controlled by separate switch and separate fuses yes

are the fuses double pole yes, are the switches and fuses grouped in a position accessible only to the officers on watch yes

has each navigation lamp an automatic indicator as per Rule yes, are separate screens provided for the use of oil and electric side lights yes

are separate oil lanterns provided for the mast head lights and side lights yes

Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight yes

are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected none

are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected none

—, how are the cables led —

where are the controlling switches situated on main switch board

Searchlight Lamps, No. of none, whether fixed or portable —, are their fittings as per Rule —

Arc Lamps, other than searchlight lamps, No. of none, are their live parts insulated from the frame or case —, are their fittings as per Rule —

Motors, are their working parts readily accessible —, are the coils self-contained and readily removable for replacement —

are the brushes, brush holders, terminals and lubricating arrangements as per Rule —, are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material —

are they protected from mechanical injury and damage from water, steam or oil — are their axis of rotation fore and aft —

if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type —, if not of this type, state distance of the combustible material horizontally or vertically above the motors — and —

Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed as per Rule yes

Lightning Conductors, where lightning conductors are required, are these fitted as per Rule none

Ship carrying Oil having a Flash Point less than 150° F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings —

If portable lamps for use in dangerous spaces are supplied, are they of a type approved by the Home Office —

PARTICULARS OF GENERATING PLANT.									
DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY.	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.		
		Kilowatts.	Volts.	Amperes.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.	
MAIN	100	100	100	850	Single cylinder steam engine	—	—	—
AUXILIARY					—	—	—	—
EMERGENCY					—	—	—	—
ROTARY TRANSFORMER									

LIGHTING AND HEATING CONDUCTORS.									
Ref. No.	DESCRIPTION.	No. of Conductors.	Effective Area of each Conductor. Sq. Ins.	COMPOSITION OF STRAND.		Total Maximum Current. Amperes.	Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
				No.	Diameter.				
	MAIN GENERATOR...		70 1/2	19	2.177	70	8 m.	rubber	—
	AUXILIARY GENERATOR							—	—
	EMERGENCY GENERATOR							—	—
	ROTARY TRANSFORMER...							—	—
	AUXILIARY SWITCHBOARDS							—	—
	ENGINE ROOM		4	6	0.36	5	6	lead annealed	—
	BOILER ROOM		8	3	0.36	2	25	—	—
	Accommodation		10	7	0.56	25	50	—	—
	WIRELESS		10 1/2	4	0.52	25	40 m.	rubber	lead annealed
	SEARCHLIGHT		1	2 1/2	3	0.36	0.6	45 m.	—
	MASTHEAD LIGHT...		1	2 1/2	3	0.36	0.6	10 m.	lead
	SIDE LIGHTS		1	2 1/2	3	0.36	0.2	6 m.	—
	COMPASS LIGHTS		1	2 1/2	3	0.36	0.6	50 m.	lead
	POOF LIGHTS		7	(32) 2 1/2	3-7	0.36	14	—	—
	CARGO LIGHTS							—	—
	ARC LAMPS							—	—
	HEATERS							—	—

MOTOR CONDUCTORS.									
Ref. No.	DESCRIPTION.	No. of Motors.	Effective Area of each Conductor. Sq. Ins.	COMPOSITION OF STRAND.		Total Maximum Current. Amperes.	Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
				No.	Diameter.				
	BALLAST PUMP							—	—
	MAIN BILGE LINE PUMPS							—	—
	GENERAL SERVICE PUMP							—	—
	EMERGENCY BILGE PUMP							—	—
	SANITARY PUMP							—	—
	CIRC. SEA WATER PUMPS							—	—
	CIRC. FRESH WATER PUMPS							—	—
	AIR COMPRESSOR							—	—
	FRESH WATER PUMP							—	—
	ENGINE TURNING GEAR							—	—
	ENGINE REVERSING GEAR							—	—
	LUBRICATING OIL PUMPS							—	—
	OIL FUEL TRANSFER PUMP							—	—
	WINDLASS							—	—
	WINCHES, FORWARD							—	—
	WINCHES, AFT							—	—
	STEERING GEAR							—	—
	WORKSHOP MOTOR							—	—
	VENTILATING FANS							—	—

All Conductors are of annealed copper conforming to British Standard Specification No. 7.

The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.

The foregoing is a correct description.

Electrical Engineers.

Date

COMPASSES.

Distance between electric generators or motors and standard compass

20 m. approx.
18 m. "

Distance between electric generators or motors and steering compass

The nearest cables to the compasses are as follows:—

A cable carrying 3 Ampères 20 m. feet from standard compass 5 m. feet from steering compass.

A cable carrying 0.3 Ampères 8 m. feet from standard compass 1 m. feet from steering compass.

A cable carrying 0.3 Ampères 1 m. feet from standard compass 8 m. feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power. *to be adjusted at sea*

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted? ☒

The maximum deviation due to electric currents was found to be ☒ degrees on ☒ course in the case of the standard compass, and ☒ degrees on ☒ course in the case of the steering compass.

Builder's Signature.

Date

Is this installation a duplicate of a previous case? If so, state name of vessel

General Remarks (State quality of workmanship, opinions as to class, &c.)

The workmanship & materials are good.
The electric lighting installation has been completely overhauled.
Cables & wires renewed throughout the vessel, & when tried under working conditions, was found satisfactory, & eligible in my opinion to remain as classed in the R.B.

It is submitted that
this vessel is eligible for
THE RECORD. Elec. light.

J.W.D.
20/9/27

Total Capacity of Generators 10 Kilowatts

The amount of Fee *Francs 2088.-* { When applied for, 17-9-1927

Taxes 41.80 { When received, 1-10-1927

A.L. Silditch.
Surveyor to Lloyd's Register of Shipping.

Committee's Minute

Assigned

Elec light



© 2019

Lloyd's Register
Foundation