Rpt. 110.

Index No. 33118
(For London Office only.)

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.—STEAM SHIPS.

PARTICULARS RELATING TO ALL STEAM SHIPS ~~EITHER FLUSH DECKED, OR~~ WITH TOP GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, ~~OR WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.~~

Port of Survey
Date of Survey
Name of Surveyor

Ship's Name.	Port of Registry and Nationality.	Official Number.	Gross Tonnage.	Date of Build.	Particulars of Classification.
Josephine Charlotte. Number in Register Book	Antwerp. Belgian		3422	1929/4	+ 100 A1.

	Length.	Breadth.	Depth.	Under Deck Tonnage.
~~red~~ s from gister.	339.96	48.58 British method 48.74	23.04	2952.06
on INE.	340.0	Frame Depth 7¾ Rule „ 5½ / 1¼ ×2 = .37. Spacing fitted	Ceiling fitted Sheer +.61 To tank top 23.35	Peak Tanks } Incl. For 7" framing in tween decks -8.0 tons For 11" framing in mach. space +5 tons
TED IONS.	340.0	48.37	23.96	2949.06

Moulded Depth as measured..... 25'-7"

NOTE.—If the depth is measured when vessel is afloat, the details of measurement should be reported.

Addition for Keel below base line for draught record...1.25....inches.

Correction for Length.

Length of Ship on Loadline.....	340.0		
Length in Table	307.0		
Difference	33.0		
Correction for 10ft., Table A.	1.316	Table C.	.7
× Difference divided by 10	4.34	(if required.)	2.31
If $\frac{6}{10}$ths length covered divide by 2	+4¼		+2¼

Correction for Iron Deck.

Proportion covered, if less than $\frac{7}{10}$ths length covered	.528	
Thickness of usual wood deck, less stringer	3½	−1¾

Correction for Round of Beam.

NOTE.—The round of beam should be reported on the full breadth of vessel at the gunwale.

Breadth at Gunwale amidships.....	48'-6"	
Round of Beam	12¼" over 48.6" beam	
Normal round.....	12¼	
Difference	✓	÷ 2 =..... ✓
Proportion of Deck uncovered (Para. 19)		

Freeboard, Table A		5 - 7¾
Correction for Sheer	−	5½
		5 - 2¼
Correction for Length	+	4¼
		5 - 6½
Allowance for Deck Erections	−	10¾
		4 - 7¾
Correction for Round of Beam.....		✓
Correction for fall in Sheer (if any).....		✓
Correction for Steel Deck (if required)	−	1¾
		4 - 6
Additions for non-compliance with provisions of Para. 11 (*d*) and (*e*) ‡		✓
Other Corrections (if any)		✓

Winter Freeboard	4 - 6
Summer Freeboard 4¼	4 - 1¾
Indian Summer Freeboard	3 - 9½
~~N. A. Winter Freeboard~~	✓

Correction necessary because clearside amidships, measured in accordance with the Statute is not taken at the intersection of the wood or steel deck with side. ✓

Winter Freeboard from deck line .....
Summer „ „ „ „ .....
Indian Summer „ „ „ .....
~~N.A.~~ Winter „ „ „ „ .....

S.T.B. 7.6.32

SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, ~~Wood,~~ Steel, Deck :— 49.75" ✓ = 1264 mm ✓

~~Tropical Fresh Water Line above Centre of Disc~~			~~10.34"~~ = ~~262 mm~~	~~Tropical Fresh Water Freeboard~~		~~39.41" = 1002~~
Fresh Water Line	„	„	5.84" ✓ = 148 " ✓	Fresh Water	„	43.91" = 1116 " ✓
Tropical Line	„	„	4.5" ✓ = 114 " ✓	Tropical	„	45.25" = 1150 " ✓
Winter Line	below	„	4.0" ✓ = 102 " ✓	Winter	„	53.75" = 1366 " ✓
~~Winter North Atlantic Line~~	„	„	✓	~~Winter North Atlantic~~	„	✓

9. JUN 1932

Fm,2,32.

F.Nr. = 7639 / 40 × 32.73 = 5.84

MARKING FORM RECEIVED 11 AUG 1931

MARKING FORM RECEIVED 21 MAR 1934

MARKING FORM RECEIVED 10 FEB 1933

W435-0229

RETAIN

© 2019 Lloyd's Register Foundation

Stem..... 84 / Sternpost ... 48 } 132 ÷ 2 = 66.0 ...Mean

at ⅛ of the length from Stem 46¼ / Sternpost 26⅜ } 72.62 ÷ 2 = 36.31 ...Mean ÷ .55 = 66.0

al mean Sheer .....
rd mean Sheer [Table, Para. 18] ..... 66.0 / 44.0 Difference..... 22.0 ÷ 4 = 5.5 Correction
mited as Para. 18 (*f*) ..... − 5½

in Sheer amidships . 18 (*e*)] At front of bridge house..... 10"
At after end of forecastle ..... 50"

in Sheer a. 18 (*d*) ÷ 2 = ✓ Correction
n uncovered .....

Allowance for Deck Erections :—

ard, Table C.....		2 - 8½
ion for Length, if required (Para. 12, ~~13, and 14~~)	+	2¼
		2 - 10¾
ard by Table A. corrected for sheer, and for length, if required (Para. ~~11~~, 12, ~~13, and 14~~)		5 - 6½
		2 - 7¾
nce		
age as below.....		34.24%
		10.87

ion for R. Q. Dk. if engine and boiler openings not covered by bridge house (Para. 11) ✓
nce for Deck Erections ..... − 10¾

	Length.	Length allowed.	Height.
tle.....	37.5 + 5.40	39.05	8.0
House	105.75	105.75	8.0
d Qr. Dk.....	✓	✓	✓ ...
.....	34.75	34.75	8.0
Total		179.55	= .528
of Ship		340	
onding percentage . ~~11~~, 12, ~~13, or 14~~)	34.24		