11c. Almrow 30439

14/10

B.T. COPY WRITTEN

Index No. 30524
(For London Office only.)

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.

RETAIN

PARTICULARS IN RESPECT OF STEAM SHIPS ~~HAVING SPAR OR AWNING DECKS.~~

complete Shelter Deck - No tonnage opening

Port of Survey

Date of ~~Survey~~ 21-9-32

Name of Surveyor

Ship's Name.	Port of Registry and Nationality.	Official Number.	Gross Tonnage.	Date of Build.	Particulars of Classification.
CASTLEMOOR	London British	146613	6574·25	1922	+ 100 A1, Shelter Deck with freeboard.

Number in Register Book

	Length.	Breadth.	Depth.	Under Deck Tonnage.
Registered dimensions from Register.	420·0	54·0	34·35	6274·89
Deductions	420·0	Frame Depth 12 Rule " 7/5 = ·84 Spacing fitted	Ceiling fitted Sheer +·89 Tank props to side ·27/2 +·13	Peak Tanks } incl.
Corrected dimensions.	420·0	53·16	35·37	6274·89

Moulded Depth as measured ..... 29·0 ..... Main Deck.

" " " ..... 37·0 ..... Spar or Awning Deck.

Addition for Keel below base line for draught record ..... inches.

NOTE.—If the depth is measured when vessel is afloat, the details of measurement should be reported.

Coefficient of fineness ..... ·79

Deduction if modification necessary [Para. 4 (a) to (e)*] ..... −·02 C.D.B.

Coefficient as corrected ..... ·77 ·76 to Main Deck.

CORRECTION FOR LENGTH :—

~~Length of Ship on Load Line~~	420·0
~~Length in Table~~	348·0
~~Difference~~	72·0
Correction for 10ft.	7
× Difference ÷ 10 =	5·04
	+5"

Allowance for strength in excess of Lloyd's rules = 31"

Particulars— Vessel constructed with deep channel frames, L2×3½×3½×·56×·60 ded to shelter deck in pairs at hatch ends, ngle at every third frame as indicated the approved plans.

The intermediate frames in Shelter Tween are scarphed to the main frames.

Two complete steel decks.

eams, on every frame at Upper & er decks

Seven W.T. Bkds (one to Shelter Dk) & two tial bulkheads on frames 58 & 128

Height of 'Tween Decks ..... 8·0

(From top of beam to top of beam at side)

Correction for Height of 'Tween Decks in Spar-decked Ships .....

Freeboard Table A or C ..... 3 - 11½

Correction for Length ..... + 5

4 - 4½

Correction for Height of 'Tween Decks in Spar-decked Ships ..... 8 - 0

12 - 4½

Correction for Strength in excess of Lloyd's rules ..... − 2 - 7

9 - 9½

~~Correction for Steel Deck if required~~ ..... − 3½

9 - 6

Other Corrections (if any) .....

	Length		Height.	State if open or closed at ends.
~~Forecastle~~		×		
~~Bridge~~		×		complete shelter deck without erections
~~Poop~~		×		

at Stem ..... 120 } 84 mean " at ⅛ length from Stem ..... 66 } 46·25 mean "

Sternpost ... 48 " " " Sternpost ... 26½

Drop in Sheer abaft amidships .....

46·25 / ·55 = 84·09

52·00

36 | 32·09

·89

Round of Spar-deck Beam 1.3

" Main-deck " 1.3

Winter Freeboard	9 - 6
Summer Freeboard	8 - 11½
Indian Summer Freeboard	8 - 5
~~N.A. Winter Freeboard~~	—

Correction necessary because clearside amidships measured in accordance with the Statute is not taken at intersection of the wood or steel deck with side ..... NIL

Winter Freeboard from Deck Line .....

Summer " " " .....

Indian Summer " " .....

~~N.A.~~ Winter " " " .....

SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, ~~Wood~~, Steel, Shelter Deck :— 8'- 11¼"

Tropical Fresh Water Line above Centre of Disc	14¼"	Tropical Fresh Water Freeboard	7'- 9"
Fresh Water Line " "	7¾"	Fresh Water "	8'- 3½"
Tropical Line " "	6½"	Tropical "	8'- 4¾"
Winter Line below "	6½"	Winter "	9'- 5¾"
~~Winter North Atlantic Line~~ " "	—	~~Winter North Atlantic~~ "	—

28 SEP 1932

F.W. = 13866 / 40×45·02 = 7¾"

MARKING FORM RECEIVED 14 OCT 1932

MARKING FORM RECEIVED 14 AUG 1933

MARKING FORM RECEIVED 5 JUL 1934

W439-0137

RETAIN

© 2021 Lloyd's Register Foundation