

Length
Breadth

55.55

Upper most continuous deck to top of keel
Do. Long Bridge to top of keel

Port of Registry
If surveyed while building, aft

COPY

Rpt. 12.

FREEBOARD VERIFICATION FORM FOR STEAMERS.

When received in London Office

Port SUNDERLAND

Vessel's Name STONEGATE

Official No. _____ No. in Reg. Book _____

Port of Registry (For Foreign Vessels) _____

Iron or Steel _____ State whether Classed by Lloyd's Register Yes

Name of Owners _____ Date of Verification 29.12.27

I have to report that the Freeboard from the centre of disc to the top of the statutory deck line, and the lines in connection therewith, as given below, assigned by the Committee to this vessel, have been correctly marked on the vessel's sides, in accordance with the printed instructions:—

From centre of disc to top of statutory deck line	3	ft.	8	ins.
From centre of disc to top of statutory deck line } at awning or part-awning deck . . . }		ft.		ins.
Fresh Water line above centre of disc . . .			7	ins.
Indian Summer line above centre of disc . .			6	ins.
Winter line below centre of disc			5 $\frac{1}{2}$	ins.
Winter North Atlantic line below centre of disc				ins.
Distance between the top of statutory deck line on vessel's side and the intersection of the continuation of upper side of wood or steel deck with the vessel's side	}	at main-spar or upper dk.	1 $\frac{3}{4}$	ins.
		at awning or pt.-awning dk.	-----	ins.

NOTE.—It should be clearly shown whether the statutory deck line is set off from a wood or steel deck.

Surveyor.

(To be filled up in London Office.)

Statement No. _____ Date of Committee's Minute 9.12.27

Particulars for record in Register Book.	{	Moulded Depth	28	ft.	4	ins.
		Freeboard	3	ft.	8	ins.
		Corresponding Draught	25	ft.	0 $\frac{1}{2}$	ins.

Freeboards compared and found correct by _____ Date _____

Is fee paid? _____ Form for Certificate _____

Instructions _____ Date _____

Certificate written _____ Noted for posting _____

2m, 11, 21.—T.



© 2020

Lloyd's Register Foundation

W443-0277

Condition of Class, Tonnage Opening Fitted

breadth and thickness at margin plate. 2' 8" x 1 1/2"

Spacing 27"

Small, illegible blue stamp or mark.

RETAIN



© 2020

Lloyd's Register
Foundation

Breadth

Depth

FRAMES, Spa

"

"

DE FRAMI

Frame Amte

"

Reversed F

"

Depth of F

Frames in

" " S

" "

Framing in

diameter

State if Fra

ATING A

LENGTH

WARD.

GLE BOT

loors, De

He

iddle Li

" "

" "

" "

ide Keels

" "

" "

UBLE B

olid Floo

" "

racket