

Index
(For London)

Name of Surveyor J. H. Kay Jr.

Particulars of Classification.

✱ 100A1-1.23
1 DK. (IRN) 1 DEEP FRAMING.

NOTE. — If the depth is measured when vessel is afloat, the details of measurement should be reported.

CORRECTION FOR LENGTH.

If $\frac{6}{10}$ ths length covered divide by 2

CORRECTION FOR IRON DECK.

Thickness of usual wood deck, less stringer

CORRECTION FOR ROUND OF BEAM.

NOTE. — The round of beam should be reported on the full breadth of vessel at the gunwale.

Co-efficient as corrected

8 If limited as I
.....

Para. 18 (e)] of forecastle

Length uncovered Correction

ALLOWANCE FOR DECK ERECTIONS :—

Correction for _____, if required (Para. 12, 13, and 14)

Difference

Percentage as below.....

Allowance for Deck Erections

(Para. 11, 12, 13, or 14) }

FREEBOARD recommended amidships from centre of Disc to top of Statutory Deck Line, Wood (Iron) Deck :—

Winter North Atlantic Line " " "

* If the frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside of ceiling should be reported if possible.

† In vessels obtaining an allowance for deck erections under Para. 11 where the sheer drops abaft amidships the height of the R.Q.D. is to be taken from the level of the top of the amidship beam.

§ In flush-decked vessels the total standard mean sheer means the sheer measured at the stem and stern-post. In vessels having poops and forecastles, it means the sheer measured at points distant one-eighth of the vessel's length from stem and stern-post.

N. A. Winter Freeboard

N. A. Winter " " "




† State dimensions of freeing port area on back of this form.

The Surveyor should state whether the fall in sheer as reported is measured relatively to the straight line of keel or to the water line. If measured relatively to water line the vessel's draft at time of survey, and also the usual load draft forward and aft should be reported.

measured relatively to the straight
or line the vessel's draft at time of
reported.

W444-0190

Do they extend to the top height of the Poop or Raised Quarter Deck?
 How high do the Reverse Frames extend?
 Is the Poop or Raised Quarter Deck an efficient Iron Bulkhead at the fore end?
 Give particulars of the means for closing the openings in Bulkhead
 Is the Poop or Raised Quarter Deck connected with the Bridge House?
 Give particulars of the means for closing the openings in Bulkhead
 What is the thickness of the Bridge Front plating? and Coaming plate?
 Give scantlings and spacing of the Stiffeners
 Are bracket plates fitted at each end of the Stiffeners?
 Has the Bridge House an efficient Iron Bulkhead at the after end?
 How are the openings closed?
 Is the Forecastle at least as high as the main or top-gallant rail?
 Are the Engine and Boiler openings covered by a Bridge, Poop, Raised Quarter Deck, or enclosed by a Strong Iron or Steel Deckhouse?
 If the openings are not so protected, the exposed parts of the Casings efficiently constructed
 Give thickness of plating; scantlings and spacing of Stiffeners
 What is the height of the exposed Casings?
 Are suitable means provided for closing all openings in them in bad weather?
 Are the Weather Deck Hatchways efficiently constructed and at least equal to the requirements of Section 28 of the Rules for 1901-5? Give particulars below:—

Position and Size.		No. 1: 20'-0" x 14'-0"		No. 2: 24'-0" x 14'-0"		No. 3: 24'-0" x 14'-0"		No. 4: 24'-0" x 14'-0"	
Item.		Ship.	Rule.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.
COAMING.	Height above top of DECK	32"		32"		32"		32"	
	Thickness {	Sides.....	.44"	.44"	.44"	.44"	.44"	.44"	.44"
		Ends.....	.44"	.44"	.44"	.44"	.44"	.44"	.44"
SHIFTING BEAMS OR WEB PLATES	Number	ONE		10		TWO		TWO	
	Section and Scantlings								
	Material	STEEL		STEEL		STEEL		STEEL	
* FORE AND AFTERS.	Number	THREE		THREE		THREE		THREE	
	Section and Scantlings	CENTRE: 6 1/2" x 40 SIDES: 2 1/2" x 26 x .34		CENTRE: 6 1/2" x 40 SIDES: 2 1/2" x 26 x .34		CENTRE: 6 1/2" x 40 SIDES: 2 1/2" x 26 x .34		CENTRE: 6 1/2" x 40 SIDES: 2 1/2" x 26 x .34	
	Material	STEEL		STEEL		STEEL		STEEL	
HATCHES Thickness		3"		3"		3"		3"	
Remarks									