

W446-0202

of Upper
eam, Actual

PARTICULARS OF LONGITUDINAL FRAMING.

29 SEP 1924

FRAMING.				AMIDSHIPS.			ENDS.			AMIDSHIPS.			ENDS.			RIVETING.		Rivets in Brackets to Bulkheads.	
				In Ship.			In Ship.			Per Rule or as approved.			Per Rule or as approved.			Rivets in Longitudinal Frames.		Spacing of Rivets on each side of Transverses and Bulkheads.	
				Ins.			Ins.			Ins.			Ins.			Diam. Speng.		Inches.	
				Ins.			Ins.			Ins.			Ins.			Ins.		Inches.	
Framing from Awning, Shelter or Upper Deck to Margin Plate.																			
ming of L, L or C																			
mes in Bridge 'tween Decks...																			
mes from Uppermost Continuous Deck																			
No. 1																			
" 2																			
" 3																			
" 4																			
" 5																			
" 6																			
" 7																			
" 8																			
" 9																			
" 10																			
" 11																			
" 12																			
" 13																			
" 14																			
" 15																			
" 16																			
Spacing of Longitudinal Frames																			
Amidships																			
At Ends																			
Double Bottom																			
Tank Top																			
Bottom																			
Spacing of Longitudinals																			
Amidships																			
At Ends																			
Transverses.																			
In Bridge																			
Face Angles																			
Lugs to Shell*																			
In Awning, Shelter or Upper 'tween Decks.																			
Depth and Thickness																			
Face Angles																			
Lugs to Shell*																			
In Hold.																			
Depth and Thickness																			
Face Angles																			
Lugs to Shell*																			
Brackets																			
Spacing of Transverse Frames																			
State if joggled or liners.																			
Longitudinal Beams of																			
Bridge Deck																			
Awg. or Shltr. Dk.																			
Upper																			
Second																			
Third																			

The particulars of framing in peaks (if ordinary), Floors, Centre Girder, Side Girders and Margin Plate and their angle attachments, etc., to be entered in their respective places provided for on the Report Forms.

NOTE:—This slip to be pasted on the fourth page of the Report, and reference to same to be made under framing, etc., on the first page.