

Form No. 13. WEB FRAMES. FORGINGS or CASTINGS. BULKHEADS. COLLISION PARTITION LONGITUDINAL. PLATING. RIVETING. FRAMES. REVERSED FRAMES. MASTS, SPARS, &c. Lower Masts. Main Mast. Mizzen Mast. Topmasts, Yards and Remainder of Spars. Rigging, Material and Size, Shrouds. Sails.

EQUIPMENT No. 50480 LETTER 27 ANCHORS. CHAIN CABLES. HAWSERS AND WARPS. Correspondence. Workmanship. General Remarks. The vessel has been built in accordance with the plans approved by the Committee. The double bottom tanks in way of holds and fore & after peak tanks have been arranged for the carriage of oil fuel as per approved plan. The approved plans seven in number together with eleven casting & forging reports are enclosed herewith.

WEB
FRAMES, In
" No. of S
FRAMES.
" FRAMES
" No. of
Size of
KET
Fram
KHEA
ULKH
LISIO
TION
TUDIN
outside
Sluice
STRAK
PLATE K
Keel, state
ARD OR
actual
oss in
Double
om.
I
I
C
F
J
F
I
M
M
ur.
C
F
Q
R
S
T
U
V
W

GENERAL REMARKS—(continued).

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop ft., R.Q.D. ft., Bridge ft., Forecastle

(in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated
2 Dks (Stl) and Shelter Dk (Stl-Ws) 3rd Dk (Stl) in No. 1 Hold.
No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given a
should appear in the Register Book) 8 Bulkheads 7 to Shelter Deck 1 to Upper Deck.
Official No. 143663 ; Signal Letters State if Machinery is fitted aft no.
How are the surfaces preserved from oxidation? Inside Paint & Portland Cement & Bitumastic Outside Paint.

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors Cellular.

Where Fitted.	Length. Feet.	Water Capacity. Tons.	Where Fitted.	Length. Feet.	Water Capacity. Tons.
Double bottom, aft,	88	OIL 220 WATER 240	Fore peak tank,		OIL 73
Double bottom, under Engines and Boilers,	112	FRESHW. 520	After peak tank,		44
Double bottom, if under Engines only,			Deep tank, aft,		
Double bottom, if under Boilers only,			Deep tank, forward,		
Double bottom, forward,	210	OIL 770 WATER 840	Other tanks, if fitted,		
	Total capacity of double bottom	1600	(If necessary, furnish further information by sketch.)		

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules Yes.

Order for Special Survey No. 618

Date 27th March 1917

No. 509 in builder's yard.

DATES of Surveys held while building

from 19th March 1917 to 2nd September 1920.

Surveyor's Signature

E. Kendall

© 2020

Total No. of Visits 87

Lloyd's Register Foundation