

5927 -

LLOYD'S REGISTER OF BRITISH AND FOREIGN SHIPPING.

SURVEYS FOR FREEBOARD.

WED. 13 JAN 1904

Particulars in respect of steam ships with top gallant forecastles, having long poops or raised quarter decks connected with bridge houses, or short poop and bridge house disconnected, or bridge house.

Under Naval Auscros

No. 23-

Ship's Name.

Rosina

Number in Register Book

Gross
Tonnage.

2573.33

Official
Number.Greek
Vessel30^{ft} Rule10^{ft} laid

Date of Build.

1904

Port of Survey

Antwerp

Date of Survey

Jan. 9th 1904

Name of Surveyor

H. P. Cornick

					Particulars of Classification,
					Class contemplated
					100 A.1.

Registered Length	318	Breadth	44.6	Depth	20.79
Length on Loadline	319	as measured off ship.		Moulded Depth as measured	23.6"
Breadth	44.6	Tonnage for peak tank			
	19.4	= 20 tons.			
	12.76				
	12.76				
Depth	20.79	21.08 to inner bottom			
	12.80466				
	995918				
	284548				
	2957.87.646	2431630000 L.822			
		2366301168			
		653288320			
Co-efficient of fineness	822 : 81	591575292			
Any modification necessary	Cell 513.	61713928			
Co-efficient as corrected	802	say 80			
	.79				

Sheer at Stem...	87'	130	÷ 2 = 65	Mean 62.73 if gradual
at Sternpost...	43"			
Sheer at $\frac{1}{8}$ of the length from Sternpost	47	67	$\div 2 = 33\frac{1}{2}$	
Standard Sheer (Table, Para. 16)	41.9			
Difference	20.83		$\div 4 = 5.2075$	
	19.0		$- 5\frac{1}{4} 4\frac{3}{4}$	

Rise in Sheer	At front of bridge house
from amidships	At after end of forecastle
[Para. 16 (e)]	

ALLOWANCE FOR DECK ERECTIONS:

Freeboard, Table C	2' 9 $\frac{1}{2}$ " $\frac{1}{4}$
Correction for Length, if required (Para. 12 and 13)	+ 2' 11 $\frac{1}{4}$ " $\frac{1}{2}$
Freeboard by Table A, corrected for sheer, and for length, if required (Para. 12 and 13)	5' 0 $\frac{1}{4}$ " $\frac{1}{4}$
Difference	2' 8 $\frac{3}{4}$ " $\frac{1}{4}$
Percentage as below	75.2%

Correction of R. Q. Dk. less than 4ft. high, or if engine and boiler openings not covered by bridge house

Allowance for Deck Erections

Length.	Length allowed.	Height.
Forecastle	37' 0"	37' 0"
Bridge House	200.0	200
Raised Q. Dk.		
Poop	34.8	34.8
Total	271.8	852

Length of Ship

Corresponding percentage

(Para. 11, 12, 13)

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

75.2%

ERASE WORDS WHICH DO NOT APPLY.

The Crew ~~are, are not~~, berthed in the bridge house.

The arrangements to enable them to get backwards and forwards from their quarters ~~are, are not~~, satisfactory.

Length of Bulwarks in well - ~~x~~ 2 ~~:~~ = Sq. Ft.
Freeing Ports

Ft.	Tenths.	Ft.	Tenths.	No.	{	= Sq. Ft.
x	x	x	x			

Total deficiency = Sq. Ft.
Total excess = 4.8 ft

CHARACTER OF DECK ERECTIONS.

Do all the Frames extend to the top height in the Poop? Yes

Do do do do Raised Quarter Deck? ✓

Do do do do Bridge House? Yes

Do do do do Forecastle? Yes

To what height do the Reverse Frames extend? channel frames to Poop B. & 3 decks

Has the Poop or Raised Quarter Deck an efficient Iron Bulkhead at its fore end? Portable doors

State whether the Bridge House efficiently covers the Engine and Boiler Openings Yes

Has the Bridge House an efficient Iron Bulkhead at the fore end? Portable doors at after end

Are efficient Doors fitted to the Passage Ways? Portable doors at after end

Describe how and to what extent it is Stiffened, by angle Irons, Bulk Plates, or otherwise Channel stiffeners

Has the Bridge House an efficient Iron Bulkhead at the after end? Yes, but portable doors.

Are efficient Doors fitted to the Passage Ways? Portable doors on bulkhead

Are efficient Iron Doors fitted to the Passages of the Bridge House, or is it entered from above? Yes

Has the Forecastle an efficient Iron or Wood Bulkhead at its after end? Yes, hinged door.

Are the Hatchways efficiently constructed? Yes State the height of the Coamings 3 feet

Are the Hatches solid? Yes What is their thickness? 3/2"

Are the exposed parts of the Engine and Boiler Casings efficiently constructed? Yes

State any special features in the construction of the Vessel

2 plan returned 19/1/19

*2.46
2.15
5.25*

Owners

Greeves Entricier Bros

, Address

Fee £ :

Received by me



© 2019

Lloyd's Register
Foundation