

STRENGTH TO BE INVESTIGATED.

Lloyd's Register of Shipping.

Index. No. 29230.
(For London Office only.)

SURVEYS FOR FREEBOARD.

Computation of Freeboard for Steamer, Sailing Ship, Tanker—
having Forecastle & Bridge.

(Type of Superstructures.)

Ship's Name ARAUCANIA. Nationality and Port of Registry Official Number Gross Tonnage Date of Build 1918

Moulded Dimensions: Length 170.0 Breadth Depth 16.50.

Moulded displacement at moulded draught = 85 per cent. of moulded depth.

Coefficient of fineness for use with Tables .68 (Lowest in Tables assumed) tons

Port of Survey

Date of Survey 8-10-31

Name of Surveyor

Particulars of Classification +100 A1.

Depth for Freeboard (D)

Moulded depth 16.50

Stringer plate02

Sheathing on exposed deck
 $T \left(\frac{L-S}{L} \right) =$ ✓

Depth for Freeboard (D) = 16.52

Depth correction

(a) Where D is greater than Table depth
(D—Table depth) R = $(16.52 - 11.33) \times 1.307 = +6.78$

(b) Where D is less than Table depth (if allowed)
(Table depth—D) R =

If restricted by superstructures

Round of Beam correction

Moulded Breadth (B)

Standard Round of Beam = $\frac{B \times 12}{50} =$ 7.16

Ship's Round of Beam = 8.00

Difference .84

Restricted to

Correction = $\frac{\text{Diff}^e}{4} \times \left(1 - \frac{S_1}{L} \right) =$ $\frac{.84}{4} \times .5955 = .12$

DEDUCTION FOR SUPERSTRUCTURES.

	Mean Covered Length (S)	Equivalent Enclosed Length (S ₁)	Height	Height Correction	Effective Length (E)
Poop enclosed					
„ overhang					
R.Q.D. enclosed					
„ overhang					
Bridge enclosed	<u>50.00</u>	<u>50.00</u>			<u>50.00</u>
„ overhang aft					
„ overhang forward					
F'cle enclosed	<u>17.00</u>	<u>17.00</u>	<u>6.6"</u>	<u>✓</u>	<u>17.00</u>
„ overhang	<u>3.50</u>	<u>1.75</u>			<u>1.75</u>
Trunk aft					
„ forward					
Tonnage opening aft					
„ „ forward					
Total	<u>70.50</u>	<u>68.75</u>			<u>68.75</u>

Standard Height of Superstructure 6.0

„ „ R.Q.D. 3.467

Deduction for complete superstructure 23.00

Percentage covered $\frac{S}{L} =$ 41.47%

„ „ $\frac{S_1}{L} =$ 40.45%

„ „ $\frac{E}{L} =$ 40.45%

Percentage from Table, Line A.
(corrected for absence of forecastle (if required))

Percentage from Table, Line B. 27.88
(corrected for absence of forecastle (if required))

Interpolation for bridge less than .2L (if required)

Deduction = $23 + .2788 = -6.41$

SHEER CORRECTION.

Station	Standard Ordinate	S	M	Product	Actual Ordinate	Effective Ordinate	S	M	Product
A.P.	<u>27.00</u>	1		<u>27.00</u>	<u>50.00</u>	<u>50.00</u>	1		<u>50.00</u>
$\frac{1}{6}$ L from A.P.	<u>12.01</u>	4		<u>48.04</u>	<u>22.12</u>	<u>22.12</u>	4		<u>88.48</u>
$\frac{2}{6}$ L „	<u>2.97</u>	2		<u>5.94</u>	<u>5.52</u>	<u>5.52</u>	2		<u>11.04</u>
Amidships	<u>—</u>	4		<u>—</u>	<u>—</u>	<u>—</u>	4		<u>—</u>
$\frac{3}{6}$ L from F.P.	<u>5.94</u>	2		<u>11.88</u>	<u>8.08</u>	<u>8.08</u>	2		<u>16.16</u>
$\frac{4}{6}$ L „	<u>24.02</u>	4		<u>96.08</u>	<u>32.39</u>	<u>32.39</u>	4		<u>129.56</u>
F.P.	<u>54.00</u>	1		<u>54.00</u>	<u>67.00</u>	<u>67.00</u>	1		<u>67.00</u>
Total				<u>242.94</u>					<u>362.24</u>

Mean actual sheer aft = excess

Mean standard sheer aft =

Mean actual sheer forward = excess

Mean standard sheer forward =

Length of enclosed superstructure forward of amidships = .034

„ „ aft of „ = ✓

Correction = $\frac{\text{Difference between sums of products}}{18} \left(\frac{.75 - \frac{S}{2L}}{.75} \right) =$ $\frac{119.3}{18} \times .5427 \times \frac{13}{20} = -2.34$

If limited on account of midship superstructure. $\frac{.13}{.20} \times 3.06 = 2.34$ If limited to maximum allowance of $1\frac{1}{2}$ ins. per 100 ft. ✓

Deduction for Tropical Freeboard.
Addition for Winter and Winter North Atlantic Freeboard.

Deduction for Fresh Water.

TABULAR FREEBOARD corrected for Flush Deck (if required)

Depth to Freeboard Deck = Ft.
Summer freeboard =
Moulded draught (d) = Displacement in salt water at summer load water line
 $\Delta =$
Tons per inch immersion at summer load water line
 $T =$

Correction for coefficient

Deduction for Tropical freeboard and addition for Winter freeboard = $\frac{d}{4}$ inches = Deduction = $\frac{\Delta}{40T}$ inches = Addition for Winter North Atlantic Freeboard (if required) =

	+	-
Depth Correction	<u>6.78</u>	<u>—</u>
Deduction for superstructures	<u>—</u>	<u>6.41</u>
Sheer correction	<u>—</u>	<u>2.34</u>
Round of Beam correction	<u>—</u>	<u>.12</u>
Correction for Thickness of Deck amidships	<u>—</u>	<u>—</u>
Other corrections, scantlings, etc.	<u>—</u>	<u>—</u>
	<u>6.78</u>	<u>8.87</u>
Summer Freeboard =	<u>16.21</u>	<u>—</u>

SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, Wood, Steel, Deck:—

Tropical Fresh Water Line above Centre of Disc
Fresh Water Line „ „
Tropical Line „ „
Winter Line below „ „
Winter North Atlantic Line „ „Tropical Fresh Water Freeboard
Fresh Water „ „
Tropical „ „
Winter „ „
Winter North Atlantic „ „

© 2020

Lloyd's Register
Foundation

W470-0115(1/2)

PARTICULARS OF PROTECTION TO OPENINGS, ETC.

HATCHWAYS ON FREEBOARD AND SUPERSTRUCTURE DECKS									
Description of Hatchway									
Dimensions of Hatchway									
COAMINGS	Height above Deck								
	Thickness								
	Sides								
	Ends								
	Stiffeners								
	Brackets, Stays								
HATCH BEAMS	Number								
	Spacing								
	Scantling and Sketch								
	Bearing Surface								
FORE AND AFTERS	Number								
	Spacing								
	Unsupported Lengths								
	Scantling* and Sketch								
	Bearing Surface								
HATCH COVERS	Material								
	Thickness								
	How fitted								
	Bearing Surface								
Spacing of Cleats									
Number of Tarpaulins									

*Are wood fore and afters steel shod at all bearing surfaces?
 Are battens and wedges efficient and in good condition?
 Are tarpaulins in good condition and in accordance with rule requirements?
 Are lashings provided in accordance with rule requirements?

Particulars of fiddle, funnel and ventilator coamings:—

Particulars of Flush Bunker Scuttles:—

Particulars of Companionways:—

Particulars of Ventilators in exposed positions on freeboard and superstructure decks:—

Particulars of Air Pipes in exposed positions on freeboard, raised quarter, or superstructure decks:—

Particulars of Gangway Cargo and Coaling Ports:—

Particulars of Scuppers and Sanitary Discharge Pipes —

Particulars of Side Scuttles:—

Particulars of Guard Rails:—

Particulars of Gangways, Lifelines, etc.:—

RETAIN

Particulars of Freeing Arrangements.

	Length of Bulwark	Height of Bulwark	Size of Freeing Ports	Number each side	Area each side	Rule area each side
After Well						
Forward Well						
State position of each freeing port } After Well:— (F. and A. position and height above deck edge) } Forward Well:— State whether the freeing ports are fitted with shutters, bars, or rails, and give particulars of such:— Additional area where sheer is less than standard.						

Particulars of Superstructures, Trunks, Casings, Deckhouses.

	Coaming	Plating	Stiffeners	Spacing	End Attachments of Stiffeners	Size of Openings	Height of Sills	Height of Casings
Poop Bulkhead								
Raised Quarter Deck Bulkhead ...								
Bridge, After Bulkhead								
Bridge, Forward Bulkhead								
Forecastle Bulkhead								
Trunk, Aft								
Trunk, Forward								
Exposed Machinery Casings on Freeboard or Raised Quarter Decks ...								
Exposed Machinery Casings on Superstructure Decks								
Machinery Casings within Superstructures not fitted with Class I Closing Appliances								
Deckhouses on Flush Deck Ships ...								

Particulars of Closing Appliances (state if capable of being manipulated from both sides).

Poop Bulkhead	
Raised Quarter Deck Bulkhead ...	
Bridge, After Bulkhead	
Bridge, Forward Bulkhead	
Forecastle Bulkhead	
Exposed Machinery Casings on Freeboard or Raised Quarter Decks ...	
Exposed Machinery Casings on Superstructure Decks	
Machinery Casings within Superstructures not fitted with Class I Closing Appliances	
Deckhouses on Flush Deck Ships ...	