With ~~or Without~~ Disconnected Erections.

STEEL STEAMER.

MON. 7 OCT. 1918

Received at London Office

State if Report is also sent on the Machinery of the Vessel Yes

Date of completion of report 3rd October 1918. Port of Sunderland. No. 27346

Survey held at Sunderland. Date, First Survey 31 Oct 1917 Last Survey 30th Sept 1918

On the (State if Single, Twin, or Triple Screw) single screw steamer "WAR JEMADAR." Rig none. (wireless mast)

CLASS ✠ 100 A.1. FEET.

Breadth (greatest moulded) ..... 52·0

Depth, at middle of length from top of keel to top of upper deck beams at side ..... 31·0

Transverse Number ..... 03·0

Length on deck from fore part of stem to after part of stern post ..... 400·0

Longitudinal Number 33200

Depth "d," at middle of length (See Secs. 2 & 13) .....

Proportions—Depths to Length—Upper Deck Beam at side to top of keel 12·9

" " Long Bridge Deck Beam at side to top of keel 10·38

Master James Donald Jackson.

Year of appointment (1) As Master in service of owner of present vessel:—1918. (2) As Master of this vessel 1918.

Built at Sunderland.

When built 1918. Launched 20th Aug. 1918.

By whom built Sir James Laing & Sons

Owners The Controller of Shipping.

Managers Runting & Son's (Where necessary to be entered in Reg. Book.)

Residence Milburn House, Newcastle-on-Tyne

Port belonging to London.

TONNAGE under Tonnage Deck ...

Do. between Tonnage Dk. and 3rd and 4th Dk. ...

Total under Upper Dk. 4703·43

Do. of Poop 147·09

Do. of ~~Bridge~~ Dk. Trunk 569·08

Do. of Bridge Houses 99·64

Do. of Forecastle ✓

Do. of Houses on Dk. 43·75

Do. of excess of Hatchways ✓

Do. above Crown of Engine Room .. ✓

Gross Tonnage 5563·02

Less Crew Space 210·74

Less above Crown of Engine Room .. ✓

AGE FOR FEES .. 5352·28

Engine Room 1480·17

Navigation Spaces 96·58

ter Tonnage ut on Beam .. 3445·53.

Destined Voyage not stated. If Surveyed while Building and Afloat, ~~or in Dry Dock~~ Yes.

NGTH on Deck s per Rule .... Feet. 400 Inches. 0

BREADTH— Moulded .... Feet. 52 Inches. 0

DEPTH, ACTUAL—Top of Floors to top of Upper Dk. Beams Feet. 28 Inches. 6

Do. do. do. do. ~~Second Dk. Beams~~

No. of Decks with flat laid one.

No. of Tiers of Beams two.

ensions of Ship per Register, Length 400·0 breadth 52·4 depth 28·5. Moulded depth, ft. 28 ins. 6½ To Bridge Dk. Round of Upper Dk. Beam, Actual 13. ins.

Moulded depth, ft. 31 ins. 0 To Upper Dk.

FRAMING. (See Longitudinal Framing.)

	Inches in Ship.	Inches in Ship	Inches in Ship.	Inches per Rule Or as	Inches per Rule as Approved	Inches per Rule Approved.
AME, ~~Angles, or [or~~ Bars ~~amidships~~ in fore & after holds	8	3	·38	8	3	·38
Do. in peaks	8	3	·38	8	3	·38
Do. in way of Double Bottoms at Solid Floors, in fore hold	3½	3½	·40	3½	3½	·40
" " " " at intermdt. Bkts.	B.B. & S.B. spaces.	Jelenwood Longitudinal Framing.		cystem. See		
cing of Frames from centre to centre amidships	Jelenwood Longitudinal Framing.			System See		
" " " " from ¾ length to Collision bulkhead	26			26		
" " " " in peaks..	24 and 22½		fore	peak.		
VERSED FRAME, Angles	bulb angle frames			in fore & after holds		
Do. in way of Double Bottoms at Solid Floors. fore hold	3½	3½	·40	3½	3½	·40
" " at intermdt. Bkts.						
AMING, depth of girder fore & after holds		8			8	
OORS, depth and thickness of Floor Plate at mid-line ~~for ¾ length amidships~~ in fore and after holds	50	6	·39 ·40	50	6	·39 ·40
" ~~in way of Engine and Boiler Spaces~~	7 bars	flanged		on	7.	
" thickness at the ends of vessel frames reels.			·40			·40
" depth at ¾ the half breadth, as per Rule		✓			✓	
" height extended at the Bilges	50	6	·39	50	6	·39
OORS in **Cell. Double Bottoms** fore hold	36.	Cyl.	spaces	Brine	pans	·50
" state if flanged (top & bottom)	40					
" Spacing of Solid floors	fore hold	26	22. 23½	fore hold	26	22. 23½
NTRE GIRDER, in Dbl. bottom, dpth. & thickns. fore hold	B.B. & S.B. spaces	40	15·50	40	40	15·50
" " Angles, Top ..... double. fore hold	3½	3½	·40	3½	3½	·40
" " " Bottom ..... double.	C.B.B. 6 × 6 · 50	5	·56	4½	4½	·56
" " " to Floors	C.B.B. 6 × 4 · 44	3½	·40	Boiler spaces 3½	3½	·54 ·40
~~Brackets at intermdt. frmg., wdth & thkns~~						
E GIRDERS, number on each side & thickness fore hold		one	·36		one	·36
" " state if flanged (top and bottom)		no			no	
" " Angles (top and bottom)	3½	3½	·40	3½	3½	·40
" " " to Floors	3	3	·40	3	3	·40
RGIN PLATE, depth (exclusive of flange) and thickness, fore hold	Engine space 41		·48	Boiler spaces 34		·48
" Angle to Outside Plating	fore hold 34		·48	fore hold	34	·48
" " " Floors	A.B. 3½ × 3½		·50	4	4	·48
~~Brackets at intermdt. frmg., wdth & thkns~~	C.B.B. 6 × 6		·46	Engine space 6	6	·46
Height of Outside Brackets above at bilge		24			24	
ER BOTTOM PLATING, breadth and thickness of Middle Line Strake	36	Sets.	36 Bds.	36	Sets.	36 Bds.
" " " in Engine and Boiler space	48	Sets.	·56 Bds.	48	Sets.	·56 Bds.
" " " Remainder in Holds fore hold	44	6	·36	44	6	·36
MS, Upper Deck, ~~Single Angle,~~ Bulb Angle. ~~Plate, Tee Bulb, or Channel~~ fore hold	9	3½	·46	9	3½	·46
" In way of ~~Long Bridge~~ after hold	10	3½	·50	10	3½	·50
" Spacing	every	frame	forward	alternate	frames	aft
MS, Second Deck, ~~Single Angle,~~ Bulb Angle, ~~Plate, Tee Bulb, or Channel~~	10	3½	·44	10	3½	·44
" Spacing		every		frame.		
~~**BEAMS, Third and Fourth Deck,** Single Angle,~~ Bulb Angle, Plate, Tee Bulb, or Channel						
" Angles ~~on upper edge~~						
" Spacing						
BEAMS, Poop Deck, Angle, Bulb Angle, ~~Plate,~~ ~~Tee Bulb, or Channel~~	9	3½	·40	9	3½	·40
" ~~Angles on upper edge~~	6	3½	·40			
" Spacing		every	frame.			
BEAMS, Bridge Deck, ~~Angle,~~ Bulb Angle, ~~Plate,~~ ~~Tee Bulb, or Channel~~						
" ~~Angles on upper edge~~		Longitudinals.				
" Spacing						
BEAMS, Forecastle Deck, ~~Angle,~~ Bulb Angle, ~~Plate, Tee Bulb, or Channel~~	9	3½	·46	9	3½	·46
" ~~Angles on upper edge~~						
" Spacing		every		frame.		

PILLARS.

	Inches. Size in Ship.	Inches. Spacing in Ship.	Inches per Rule. Or as	Inches per Rule. Approved.
PILLARS, In 'tween Deck, fore & after Hold and spacing	3½ dia.	48	3½ dia.	48
" " " "	2.R. 4½ dia.	52	2R. 4½ dia.	52
" **Quarter 'tween Dks.,** " "				
" " **in Hold** Oil tanks "	middle line bulkhead and transverse frames		as per plan.	

KEELSONS & STRINGERS.

	Inches in Ship	Inches in Ship	Inches in Ship.	Inches per Rule Or as	Inches per Rule as Approved	Inches per Rule Approved.
CENTRE LINE KEELSON, Vertical Plate above fore & after hold floors, Through Plate, ~~or Intercostal Plate~~	43	5	54 ·40	43	5	54 ·40
" ~~Rider Plate~~ double top angles	6	3½	·44	6	3½	·44
" Flat Plate Keel Angles ... double	5	5	·56	4½	4½	·56
" ~~Horizontal Plates on Floors~~						
" ~~Angles or Bulb Angles~~						
SIDE KEELSONS, Number after hold	one			one		
" ~~Angles or Bulb Angles~~						
" ~~Plate above floors, for length~~						
" Intercostal Plate, ~~for top flanged 3½~~ length		36			36	
" Attached to outside Plating with Angle	3½	3½	·40	3½	3½	·40
~~**BILGE KEELSON,** Angles~~						
" Intercostal Plate for length						
~~" Attached to outside Plating with Angle~~						
SIDE STRINGERS, Number two						
" " Angle fore	6	3½	·60	6	3½	·60
" Intercostal Plate, for length		26	·46		26	·46
" Attached to outside plating with Angle	3½	3½	·48	3½	3½	·48
Upper Deck Stringer Plate, br'dth & thickness (clear of Bridge)	70	·70	✓	70 × ·70		
" " " " br'dth & thickness (in way of Bridge)	64	·44	✓	64 × ·44		
" " " Angle (clear of Bridge)	6	6	·56	6 × 6		·56
" " ~~Tie Plate at sides of Hatchways~~						
" Deck.* Iron or Steel, for full lng.						
" " Thickness (clear of Bridge)		·70	✓		·70	
" " " (in way of Bridge)		·40	✓		·40	
" Wood Deck. Material & thickness none.						
Second Deck Stringer Plate, br'dth & thickness fore hold	42 × ·44		✓	42 × ·44		
" Angles on ditto, No. 2.	3½	3½	·44	3½	3½	·44
" ~~Tie Plates outside Hatchways~~						
" Deck.* ~~Iron or~~ Steel, for fore hold lng.			·30			·30
" Wood Deck. Material & thickness none						
Third Deck Stringer Plate, br'dth & thickness Trunk	54 × ·70		✓	54 ·70		
" Angles on ditto, No. one (top).	6 × 6		·56	6 × 6		·56
" ~~Tie Plates, outside Hatchways~~						
" Deck.* Material and thickness Steel		·40	✓		·40	
~~**Fourth and Fifth Deck Stringer Plate,** breadth & thickness~~						
" " " Angles on ditto, No.						
" " " Tie Plates outside Hatchways						
" " Deck. Material & thickness			✓			
Poop Deck Stringer Plate, breadth & thickness	35		·30	35		·30
" Angle on ditto	3½	3½	·34	3½	3½	·34
" ~~Tie Plates~~						
" Deck. Material and thickness Steel		·25.			·25.	
Bridge Deck Stringer Plate, br'dth & thickness	55	✓	·54	55		·54
" Angle on ditto	6 × 6		·50	6 × 6		·50
" ~~Tie Plates~~						
" Deck. Material and thickness Steel		·40	✓		·40	
Forecastle Deck Stringer Plate, b'dth & th'kns	36		·30	36		·30
" Angle on ditto	3½	3½	·34	3½	3½	·34
" ~~Tie Plates~~						
" Deck. Material and thickness Steel			·30			·30

* If Iron or Steel Deck, state if whole or part, and if Wood Deck is laid thereon.

Form No. 1A.—1m,1,13. T.

W197-033111(2)
© 2019 Lloyd's Register Foundation

WEB FRAMES.

	Inches in Ship.	Inches in Ship.	Inches per Rule. Or as Approved.	Inches per Rule. Or as Approved.
WEB-FRAMES, In Fore Body, No. and spacing	5 @	8.8	5 @	8.8
,, ,, ,, brdth. & thickness	20 × .42		20	.42
,, No of Side Stringers ,, ,,	2	20 × .42	2. 20	× .42
WEB-FRAMES, In E. & B. Space, No.& spacing	Sherwood Longitudinal		System, see	
,, ,, ,, brdth. & thickness				
WEB-FRAMES, In After Body, No. and spacing	2 @	10-10	2 @	10-10
,, ,, ,, brdth. & thickness	26 × .46		26	.46
,, No. of Side Stringers ,, ,,	2	26 .46	2 26	.46
,, Size of Face Angles to **Web-Frames**.....	6 × 3½ × .6		6 × 3½ × .60	
BRACKET PLATES to Stringers between Web Frames, depth and thickness.....	15 × .42		15	.42

FORGINGS ~~or CASTINGS~~.

	Inches in Ship.	Inches per Rule. Or as Approved.
KEEL, Bar, depth and thickness	Flat plate Keel.	
STEM, moulding and thickness ..... welded bars	10½ × 2¾	10½ × 2¾
STERN-POST for Rudder do. do.....	9 × 7½	9 × 7½
,, for Propeller	10½ × 7½	10½ × 7½
RUDDER—A×D² Table 22. Speed 12	154 × 3·2 =	493
,, **Main-Piece,** diameter at head	10	10
,, ,, ,, at heel	7½	7½

RUDDER, how constructed Forging with arms shrunk on and keyed.

,, Thickness of Plates or Single Plate 1·10

Can the Rudder be unshipped afloat? yes.

BULKHEADS. STIFFENERS.

	Number. Vessel.	Number. Per Rule.	Thickness. Inches.	Horizontal. Size. Inches.	Horizontal. Spacing Inches.	Vertical. Size. Inches.	Vertical. Spacing Inches.	Single or Double Frames.	Height up, state deck.
W.T.BULKHEADS after peak 7 ft 11	3		40-30	6×3½×.46	96	6×3½×.46	24	Single	upper dk
OIL.T. ,,	8		30-40	6×3½×.46	30	6×3½×.46	90	double	Trunk ,,
W.T. Starboard Side 33.			46-26	6×3½×.46	30	3×3×.46	180	Single	Trunk dk
,, COLLISION ,, 38			40-30	25 inch beam	½	6×3½×.46	24	Single	upper
PARTITION ,,									
LONGITUDINAL ,,			43-40	15×3½×.76 to 5×3½×.46	30	6×3½×.46	123	double	Trunk dk

Are the outside Plates doubled two spaces of Frames in length? no. brackets in lieu.

Are the ~~Sluice Valves and~~ Watertight Doors in efficient working order? yes.

Manufacturer's name or trade mark of the ~~Iron or~~ Steel (state process of manufacture of Steel) used for Frames, Floors, Beams, Keelsons, Tie and Stringer Plates, Plating, &c.? Open hearth steel. Bolckow Vaughan & Co. Consett Iron Co. South Durham Steel & Iron Co for plates and Cargo Fleet, Consett, Dorman Long & Co, Frodingham, and Palmers S.F. & C. Co for angles.

Has the Steel been tested as required by the Rules? yes.

PLATING.

STRAKES.	AS IN SHIP. AMIDSHIP. Breadth. Inches.	AMIDSHIP. Thickness. Inches.	FORWARD. Thickness. Inches.	AFT. Thickness. Inches.	PER RULE OR AS APPROVED. AMIDSHIP. Breadth. Inches.	AMIDSHIP. Thickness. Inches.
FLAT PLATE KEEL..... (If Bar Keel, state Riveting.)	47	·94	·66	·66	47	·94
GARBOARD or A Strake	67	·60	·60	64	67	·60
State actual thickness in way of Double Bottom. B ,,	67	·60	48	64	67	·60
C ,,	67	·60	·50	·74	67	·60
D ,,	63	·60	·52	·62	63	·60
E ,,	63½	·60	·54	·58	63½	·60
F ,,	60	·60	·56	·62	60	·60
G ,,	68	·60	·44	·62	68	·60
H ,,	67½	·60	·44	·62	67½	·60
J ,,	68	·60	·44	·44	68	·60
K ,,	68	·60	·44	·44	68	·60
Upper dk Strake L ,,	70	·60	·48	·46	70	·60
Bulwark Strake M ,,	73	·60	·40	·38	73	·60
N ,,						
O ,,						
P ,,						
Q ,,						
R ,,	133 strakes from forward oil bulkhead					
S ,,	to collision bulkhead 64 thick.					
T ,,						
U ,,						
V ,,						
W ,,						
THICKNESS OF SHEERSTRAKE		·84				·84
CLEAR OF LONG BRIDGE		·70				·70
DO. OF STRAKE BELOW						
DBLG. of ~~Flat Plate Keel~~ Sheerstrakes Length and thickness.	ends of bridge, increased 6 to			6 to thickness of adjoining		
POOP SIDES				·38		·38
~~SHORT BRIDGE SIDES~~ ...			·40			·40
FORECASTLE SIDES						

* Where a long bridge is fitted the thickness of Upper Deck Sheerstrake and Strake below should also be stated clear of same.

RIVETING.

Upper EDGES, Ordinary or Joggled? Ordinary

	Single or Double.	Breadth of Lap. Inches.	RIVETS. Diam. Inches.	RIVETS. Spacing cr. to cr. Inches.
FLAT PLATE KEEL.....	double	6½	1⅛	4
GARBOARD or A Strake	.	5½	⅞	3⅜
B ,,	.	.	.	.
C ,,	.	.	.	.
D ,,	.	.	.	.
E ,,	.	.	.	.
F ,,	.	.	.	.
G ,,	.	.	.	.
H ,,	.	.	.	.
J ,,	.	.	.	.
K ,,	.	.	.	.
L ,,	.	.	.	.
M ,,				
N ,,				
O ,,				
P ,,				
Q ,,				
R ,,				
S ,,				
T ,,				
U ,,				
V ,,				
W ,,				
THICKNESS OF SHEERSTRAKE				
CLEAR OF LONG BRIDGE	double	6	1	3½
DO. OF STRAKE BELOW	.	.	1	4
DBLG. of ~~Flat Plate Keel~~ Sheerstrakes Length and thickness.	ends of bridge			
POOP SIDES	Single	3	⅞	3½
~~SHORT BRIDGE SIDES~~ ...	Single	3	⅞	3½
FORECASTLE SIDES				

BUTTS.

	Double or Treble and for what Length.	RIVETS. Diam. Inches.	RIVETS. Spacing cr. to cr. Inches.	STRAPS. Breadth. Inches.	STRAPS. Thickness. Inches.	IF LAPPED. Breadth. Inches.	IF LAPPED. For what Length. Feet.
FLAT PLATE KEEL.....	5R for 7	1⅛	4⅜	–	–	20	Full
GARBOARD or A Strake	3R Full	⅞	3⅜	–	–	9	.
B ,,	.	.	.	–	–	.	.
C ,,	.	.	.	–	–	.	.
D ,,	.	.	.	–	–	.	.
E ,,	.	.	.	–	–	.	.
F ,,	.	.	.	–	–	.	.
G ,,	.	.	.	–	–	.	.
H ,,	.	.	.	–	–	.	.
J ,,	.	.	.	–	–	.	.
K ,,	.	.	.	–	–	.	.
L ,,	.	.	.	–	–	.	.
M ,,							
N ,,							
O ,,							
P ,,							
Q ,,							
R ,,							
S ,,							
T ,,							
U ,,							
V ,,							
W ,,							
THICKNESS OF SHEERSTRAKE	4R	1	4	–	–	14	Full
CLEAR OF LONG BRIDGE	4R	1	4	–	–	14	Full
DO. OF STRAKE BELOW							
DBLG. of ~~Flat Plate Keel~~ Sheerstrakes Length and thickness.							
POOP SIDES	2.R.	¾	2⅝	–	–	5	Full
~~SHORT BRIDGE SIDES~~ ...	2.R.	¾	2⅝	–	–	5	Full
FORECASTLE SIDES							

Upper Deck Stringer Plate — **Butts,** 4.R. riveted for half length amidship. **Straps,** ~~single, double~~ or overlapped for full length amidship.

Second Deck Stringer Plate — **Butts,** 2.R. riveted for full length amidship. **Straps,** ~~single or~~ overlapped for full length amidship.

Butts of Side Stringers ✓ riveted.

,, **Tie Plates** ✓ riveted.

Inner Bottom Plating, riveting of **Edges** 2.R. ¾ I.R. **Butts** 2.R. ¾ I.R.

Centre Girder Butts, 3.R. riveted **Keelson Butts,** ✓ riveted.

Frames, in four % alternate holds riveted through Plates with ⅞ in. Rivets, about 6 apart.

Rivets, state whether Iron or Steel iron

FRAMES extend in one length from in after hold middle line to transt. recess, flat and from there to deck. State if ordinary or joggled joggled.

REVERSED FRAMES ,, ,, ,, ,, margin and from there to deck. in Fore hold middle line to tank top, lins in four hold. State if ordinary or joggled joggled

MASTS, SPARS, &c.

	Material.	Total Length.	DIAMETER AND THICKNESS. At Partners.	Heel.	Hounds.	Head.	No. of Plates in round.	ANGLES. Number.	ANGLES. Size.	RIVETING. Seams.	RIVETING. Butts
Wireless Fore mast...	steel	45-6	18 × 30	18 × 30		16 × 26	2	none		Single	double.
LOWER MASTS..... Main											
Mizen.....											

~~Bowsprit~~

Topmasts, ~~Yards and Remainder of~~ **Spares**

Rigging, Material and Size, **Shrouds** ✓ **Stays** 3" S.W.

Sails. ✓ Suit of ✓ Sails, and the following spare sails ✓

Forms 830–140

White Bridge Sheer Strake" and "Upper Deck Sheer Strake" signals the corresponding letter.

EQUIPMENT No. 35504. LETTER Z. ANCHORS. TONNAGE U.DK. OR PLATING No. FOR TRAWLERS

Number of Certificate.	Anchors.	WEIGHT, EX. STOCK. Cwts.	qrs.	lbs.	WEIGHT OF STOCK Cwts.	qrs.	lbs.	TEST, PER CERTIFICATE. Tons.	cwts.	qrs.	lbs.	WEIGHT REQUIRED BY TABLE 31. Cwts.	qrs.	lbs.	Description of Anchor.	Makers.	Where and when tested and Superintendent.
23097	1st Bower ...	64	3	0	✓			50	17	2	0	63	3	0	Byers Stockless.	not stated.	S.L. 19-6-18. R.Hopper.
23061	2nd ,, ...	64	0	14	✓			50	12	2	0	63	3	0	. .	.	. 3-6-18. .
23014	3rd ,, ...	55	1	14	✓			45	12	0	21	54	2	0	. .	.	. 27-5-18. .
	4th ,, ...										✓	182	0	0	mechanical tests by J.B. Seaby and	C.C. Wilks.	
	Collective weight	184	1	0													
79204	Stream	14	1	16	5	0	10	18	12	2	0	14	2	0	ordinary	A. Hingley & Sons	Rejected. 14-3-18. H. Green.
	Kedge.....	not supplied.															

If Patent state Name of Patentee. If Stockless, state Mechanical Tests.

CHAIN CABLES. HAWSERS AND WARPS.

Number of Certificate.	Length and size supplied. Length. Fathoms.	Diam. Ins.	Test per Certificate. Statutory. Tons.	Breaking. Tons.	WEIGHT OF CHAIN CABLE Supplied. Cwts. qrs. lbs.	Per Rule. Cwts. qrs. lbs.	Length and Size per Table 31. Length. Fathoms.	Diam. Ins.	Description.	Makers of Cables.	Where and when tested, and Superintendent.
61989	105	2½	9⅛	13½	26 X 1-2	26 S. 1-13	105	2½	Stud Link	A. Hingley & Sons	A. Green. 12-3-18. H. Green.
61990	105	2½	9⅛	13½	26 X 2-0	26 S. 1-13	105	2½	,,	,,	,, 14-3-18. ,,
Iron Stream Chain or Steel Wire	90	Cir. 6½		47			90	Cir. 4½	Steel wire		

Material	Length and Size supplied. Length. Fathoms.	Ins.	Breaking Test of Steel Wire Towline. Tons.	Length and Size per Table 31. Length. Fathoms.	Cir. Ins.
TOWLINE	120	5	59	120	5
HAWSERS & WARPS	90	2¾	15½	90	2¾
,, ,,	90	2¾	15½	90	2¾
,, ,,	90	2½	12½	90	2½
	90	2½	12½	90	2½

Boats 2 Lifeboats 28-0. 2 dinghys 18-0. **Steering Gear, Steam** Hastie & Co **Steering Gear, Hand** none, ~~or two means of steering.~~ Whether ~~Double~~ yes.

Pumps, Number dispensed with. (except 6 chain pumps) Diameter of Barrel 3½ State whether they are in efficient working order yes.

Windlass is Steam Emerson Walker & Rowntree Bros. **Capstan** none.

Engine Room Skylights.—How constructed? steel plates & angles. What arrangements for deadlights in bad weather? Steel flaps & bulls eyes.

Coal Bunker Openings.—How constructed? plates and angles. How are lids secured? battens & cleats Height above deck? 1-6.

Number of **Scuppers,** and numbers and dimensions of **Freeing Ports, &c.** Six scuppers each side, open bulwarks.

Ceiling in Holds, thickness and material none **Cargo Battens,** thickness and material none

Cargo Hatchways.—How formed? plates and angles **Hatches,** If strong and efficient? yes.

State size **No. 1 Hatch** (Forward) 23-0 × 18-0. No. 2 Hatch 2 No. 3 Hatch No. 4 Hatch

Number of **Web Plates, ~~Shifting Beams~~ and ~~Fore~~ and ~~Afters~~** to ~~each~~ Hatch 4 @ 181 and 2 @ 137 No 266 inclusive Other Hatches, no webs.

No. of Breasthooks five **No. of Crutches** deep floors

Bulwarks, height above deck and description none, rails and stanchions Main Rail, material and size

The foregoing is a correct description. *Surveyor's Signature* A. Turnbull.

Builder's Signature (here enter) Hugh Laing *Surveyor to Lloyd's Register of British and Foreign Shipping.*

Correspondence.—State dates and initials of letters respecting this case (*Reference should be made in any correspondence connected with the case*)

Workmanship. Are the butts of plating planed or otherwise fitted? yes.

Is the riveted work properly closed? yes.

Are the liners between the frames and plates solid single pieces? frames joggled, no liners. Do the holes for riveting plate to frames, butt straps, or plate to plate, &c., conform well to each other? yes. Are the rivet holes well and sufficiently countersunk in the plate and punched from the faying surfaces? yes. Do any rivets break into or through the seams or butts of the plating? a few.

Are the butts of Plating, Stringers, &c., properly shifted and strapped? yes.

Have all the upper and weather decks been tested as required by the Rules (Sec. 26, par. 20)? yes. State results of tests satisfactory.

Have all the gutterways been tested as required by the Rules (Sec. 26, par. 20)? yes. State results of tests satisfactory.

General Remarks (State quality of workmanship, &c.) This vessel has been built in accordance with the approved plans and the rules. The materials and workmanship are good. As a war emergency measure the length of the cable has been reduced as per circular No 1304 and the Downton pump and Kedge anchor have been dispensed with as per the Secretary's letter dated 10-8-17. The vessel is of the 8000 ton tanker 2 class with transverse framing in fore, after holds and peaks, Longitudinal framing elsewhere, and is designed to carry oil in bulk. The oil tanks and oil fuel bunker have been tested (on the stocks) in accordance with the Secretary's letter dated 10-6-18.

A midship Section (as built) and forging reports are forwarded herewith.

The Surveyor should state the Number of Report and Name of any Sister Vessel. Plans to be forwarded with F.E. Report showing vessel as built.

The amount of Entry Fee ~~Special Fee~~ £ 15. 0. 0 Fees applied for, 1.10.18

Special Survey Fee.... £ 476 8. 0 Received by me. 11.10.18

Travelling Expenses, if any £ : : Certificate to be sent to SUNDERLAND. Date of Issue 14.10.18

14.10.18

State whether the Vessel has been built under Special Survey yes.

I am of opinion this Vessel should be Classed ✠ 100 A1. Carrying oil fuel in bulk FP 150°F

With, or without Freeboard, as condition of Class *Surveyor to Lloyd's Register of British and Foreign Shipping.*

The Surveyors are requested not to write on or below the Committee's Minute.

Committee's Minute TUE. 8 OCT. 1918

Character assigned 100 A1 Carrying oil fuel in bulk FP Palms 150° F Lloyds O & G P. + S.M. 6.9.18. F.D. passed for oil fuel 9.18. F.P. above 150° F.

Tanks Std.

© 2019 Lloyd's Register Foundation

S.S. "War Jemadar."

SUNDERLAND RPT. NO. 27346

PARTICULARS OF LONGITUDINAL FRAMING.

FRAMING.	AMIDSHIPS & THROUGHOUT. OIL TANKS. In Ship.	ENDS. AMIDSHIPS. E & B SPACE. In Ship.	AMIDSHIPS & THROUGHOUT. OIL TANKS. Per Rule or as approved.	ENDS. AMIDSHIPS. E & B SPACE. Per Rule or as approved.	RIVETING IN OIL TANKS. Rivets in Longitudinl. Frames. Diam.	Spacing.	Spacing of Rivets on each side of Transverses and Bulkheads. Inches.	Rivets in Brackets to Bulkheads. Number.	Diameter. Inches.
	Ins. Ins. Ins.	Ins. Ins. Ins.	Ins. Ins. Ins.	Ins. Ins. Ins.	Ins.	Ins.			
Framing of L, L or C	L & C	L	L & C	L					
Frames in Bridge 'tween Decks	9 3½ ·44	9 3½ ·44	9 3½ ·44	9 3½ ·44	⅞	5¼	5¼	4	⅞
Frames from Uppermost Continuous Deck No. 1	. . .	. . .	. . .	. . .				8	
" 2	. . .	. . .	. . .	. . .				8	
" 3	. . .	. . .	. . .	. . .				8	
" 4	. . .	Bunker flat	. . .	Bunker flat				8	
" 5	10 3½ ·44	9 3½ ·44	10 3½ ·44	9 3½ ·44			3 15/16 ✓	8	
" 6	. . ✓·46	. . .	. . ·46	. . .				8	
" 7	. . ✓·50	. . .	. . ·50	. . .				8	
" 8	12 3½ 3½ ·50	10 3½ ·44	12 3½ 3½ ·50	10 3½ ·44				10	
" 9	. . ✓	. . ✓·50	. . .	. . ·50				10	
" 10	. . .	. . ✓·54	. . .	. . ·54			3 1/16	10	
" 11	. . .	9 3½ ·44	. . .	9 3½ ·44				16 ✓	
" 12	15 4 4 ✓·63	. . .	15 4 4 ·63	. . .			3 15/16	16	
" 13		margin plate		margin plate				✓	
" 14									
" 15 (Bottom Longitudinals)	15 4 4 ·63	9 3½ ✓·44	15 4 4 ·63	9 3½ ·44	⅞	5¼	3 15/16	13	⅞
" 16									
Spacing of Longitudinal Frames — Amidships	30 ✓	30	30	30			an additional rivet to those in aft. body oil tanks.		
Spacing of Longitudinal Frames — At Ends	30	30	30	30					
Double Bottoms L, L or C — Tank Top Longitudinals	✓	8-3-·375-4⅞ ✓	✓	8-3-·375-4⅞	⅞	5¼			
Double Bottoms L, L or C — Bottom "	✓	9 3½ ✓·44		9 3½ ·44	-	-			
Spacing of Longitudinals — Amidships		30 ✓		30					
Spacing of Longitudinals — At Ends		30 ✓		30					

Transverses.		AMIDSHIPS & THROUGHOUT. OIL TANKS. In Ship.	ENDS. AMIDSHIPS. E & B SPACE. In Ship.	AMIDSHIPS & THROUGHOUT. OIL TANKS. Per Rule or as approved.	ENDS. AMIDSHIPS. E & B SPACE. Per Rule or as approved.	Rivets in Lugs to Shell. Diam.	Spacing.
		Ins. Ins. Ins.	Ins. Ins. Ins.	Ins. Ins. Ins.	Ins. Ins. Ins.	Ins.	Ins.
In Bridge 'tween Decks	Depth and Thickness		18 ·40 ✓		15 ·40		
	Face Angles		3½ 3½ ✓·44		3½ 3½ ·44		
	Lugs to Shell* joggled		3½ 3½ ✓·40		3½ 3½ ·40	⅞	4⅜
In ~~Awning, Shelter or~~ Upper 'tween Decks.	Depth and Thickness		27 ·50 ✓		27 ·50		
	Face Angles L		9 3½ ✓·50		9 3½ ·50		
	Lugs to Shell* joggled		6 6 ✓·46		6 6 ·46	⅞	3 15/16
In Hold.	Depth and Thickness	31 ✓·46	27 ·50 ✓	31 ·46	27 ·50		
	Face Angles	9 ✓3½ ·66	9 3½ ✓·50	9 3½ ·66	9 3½ ·50		
	Lugs to Shell* joggled	6 ✓6 ·46	6 6 ✓·46	6 6 ·46	6 6 ·46	⅞	3 15/16
	Brackets	✓·46	·50 ✓	·46	·50		
Spacing of Transverse Frames		9-08 ✓10-3	12-08 ✓11-1½	9-0 & 10-3	12-0 & 11-1½		

* State if joggled or liners.

Longitudinal Beams of L, L or C		Spacing.	In Ships. Plate.	In Ships. Angles.	As approved. Plate.	As approved. Angles.
L	Bridge Deck	36-39	11 × ·38	6-3½-4	11 × ·38	6-3½-4
L	~~Awg. or Shltr.~~ TRUNK Dk.	30	18 × ·40	5 ✓ Flange	18 × ·40	5 Flange
L	Upper "	-	18 × ·40	✓ 4-3-·40	18 × ·40	4-3-·40
L	Second "	-	10 × ·60		10 × ·60	
	~~Third~~		12-3½-3½-·6 ✓		12-3½-3½-·60	

Transverse Beams. STRONG BEAMS IN OIL TANKS.

The particulars of framing in peaks (if ordinary), Floors, Centre Girder, Side Girders and Margin Plate and their angle attachments, etc., to be entered in their respective places provided for on the Report Forms.

NOTE:—*This slip to be pasted on the fourth page of the Report, and reference to same to be made under framing, etc., on the first page.*

5c.12,15. T.

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop 49·4 ft., ~~R.Q.D.~~ ft., Bridge 120·0 ft., Forecastle 39·0 (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated poop and forecastle are joined to bridge by a trunk.

No. and Material of Decks (~~if Iron or~~ Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (*this information is to be given as should appear in the Register Book*) 1 D^K (Str.) 2 TR BKTS. F. FRAMES. PART LONGITUDINAL & TRANSVERSE FRAMING.

Official No. 142,650. ; Signal Letters

State if Machinery is fitted aft NO.

How are the surfaces preserved from oxidation? Inside Cement in E & B and fore tank also in peaks. Bituminastic enamel in Bunkers (coal) Nothing on Oil tanks, paint or cement wash elsewhere. Outside paint.

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors. Double bottom forward E & B spaces. Otherwise Longitudinal

Where Fitted.	*Length. Feet.	Water Capacity. Tons.
Double bottom, aft, none		
Double bottom, under Engines and Boilers,	59·1	251
Double bottom, if under Engines only, ✓		
Double bottom, if under Boilers only, ✓		
Double bottom, forward,	49·8	64
	Total capacity of double bottom	315

Where Fitted.	*Length. Feet.	Water Capacity. Tons.
Fore peak tank, none.		
After peak tank, none.		
Deep tank, aft, none.		
Deep tank, forward, none.		
Other tanks, if fitted, ✓		
(If necessary, furnish further information by sketch.)		

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules Yes ✓

Order for Special Survey No. 5308

Date 20.9.17

No. 672 in builder's yard.

Dates of Surveys held while building: 1917. Oct. 31 Nov. 14. 21. 27. 28. Dec. 10. 14. 19. 28. Jan. 15. 22. 29. Feb. 1. 19. 28. Mar. 7. 11. 18. 25. Apr. 4. 5. 9. 10. 15. 23. May 2. 14. 22. 31. Jun. 12. 18. 25. Jul. 1. 2. 4. 5. 12. 22. Aug. 3. 8. 9. 10. 12. 13. 14. 15. 16. 19. 20. 21. 23. 27. 28. Sep. 9. 17. 18. 20. 23. 24. 26. 27. 30.

Total No. of Visits 64.

Surveyor's Signature S. Turnbull.

© 2019 Lloyd's Register Foundation