

To class 100A.1 at Lloyds. Rules 01/02

21.8.01
9.9.01
24.9.01
2.10.01

Equipment.		
Anchors and Chains.		
1 Bower Anchor	10 1/4 cwt.	Sp. Blackless
1 " " "	10 " "	" "
1 " " "	9 " "	" "
1 Stream Anchor	8 1/2 " "	EX. Stock
1 Kedge " "	1 1/4 " "	" "
165 Fathoms Cable	1 1/6	Stud Chain.
60 " "	2 3/4	Steel Wire.
75 " "	2 1/2	Hemp Rope
90 " "	5 1/2	Manilla.

RG. 15.8.01

— Principal Dimensions. —		
Length between Perpendiculars	•	153' 0"
Breadth Moulded.	•	25' 0"
Depth	•	12' 16"

Riveling.

{ See amended
numerals
on 1st Entry
Report.

	<u>Lloyds Numerals</u>	<u>Brackets</u>
Half Circle	28.12	$\frac{L}{D} = 11.98$
Half Beam	12.50	
Total Depth	12.68	

$\frac{15}{17} = 48.30\%$ Loyds $45/52$

$$48.30 \times 151.94 = 7338.70 = 2^{\text{nd}} \text{ } N^R \text{ Lloyds}$$
$$\frac{1}{8} \text{ of } 7338.70 \times \frac{1}{151.94 + 7338.70} = 2.00160 = \text{Equip. } 125$$

paced 21° centre M_0 centre.

Reverse Frames $2\frac{1}{2} \times 2\frac{1}{2} \times \frac{5}{20}$ side strip

Boors outside Tank. $13\frac{1}{2} \times \frac{6}{20}$ to $5\frac{1}{2}$. Floors in Tank

doors in Engine Room. $\frac{7}{20}$ in Boiler space $\frac{8}{20}$

em $6\frac{1}{4} \times 1\frac{5}{8}$. Stern. Post $6\frac{1}{2} \times 3\frac{1}{4}$.

Order:- Head $4\frac{1}{4}$ " Dia^r. Rims. $2\frac{1}{2}$ " Dia^r

7' 0" — Ceiling 2 1/2" Thick — 7' 10"

$$2\frac{1}{2} \times 2\frac{1}{2} \times \frac{3}{20}$$

3/20 Manhole. 6/20. 0
0

24×18
 $3 \times 3 \times 6$

$3 \times 3 \times 6/20$

$5\frac{1}{4}$ Lap. $4\frac{1}{2}$ — C's bank 20 for $\frac{1}{2}$ Len

BS stake/20 for 1/2 L. — 10/20 at ends
— 10/20 at ends.

12 - 6

18

© 2019
Lloyd's Register
Foundation

Midships Section
 for
 The Dundee S.B. Co.
 S.S. "no 136"
 "Abercraig"
 Dundee Rpt. No. 6820

THE REGISTER OF SHIPBUILDING
 RECEIVED
 SEP 10 1901
 LONDON

THE REGISTER OF SHIPBUILDING
 RECEIVED
 SEP 10 1901
 LONDON

THE REGISTER OF SHIPBUILDING
 RECEIVED
 SEP 10 1901
 LONDON

THE REGISTER OF SHIPBUILDING
 RECEIVED
 SEP 10 1901
 LONDON

3/8 x 1/2 Double ended
 Keel and Deck 1/2 inch
 Side stringers 1/2 inch
 Single stringers
 Remains of 1 inch top rails on
 Margin 1/2 inch and 1/4 inch
 Rails of 1 inch top middle line 2 1/2
 lined 1/2 inch
 Rails of Deck 1/2 inch and 1/4 inch
 lined 1/2 inch and 1/4 inch
 Rails of Deck 1/2 inch and 1/4 inch
 lined 1/2 inch and 1/4 inch

3/8 x 1/2 Double ended
 Keel and Deck 1/2 inch
 Side stringers 1/2 inch
 Single stringers

© 2019
 Lloyd's Register
 Foundation

W498-0315