

Do all the Frames extend to the top height in the Poop? **YES** Shelter Deck? **YES** Raised Quarter Deck? Bridge House? Forecastle?

To what height do the Reverse Frames extend? **BULB ANGLE FRAMING!**

Has the Poop or Raised Quarter Deck an efficient Iron Bulkhead at the fore end?

Give particulars of the means for closing the openings in Bulkhead

Is the Poop or Raised Quarter Deck connected with the Bridge House? Has the Bridge House an efficient Bulkhead at the fore end?

Give particulars of the means for closing the openings in Bulkhead

What is the thickness of the Bridge Front plating? and Coaming plate?

Give scantlings and spacing of the Stiffeners

Are bracket plates fitted at each end of the Stiffeners? Are hor'l. brackets fitted connecting Bridge Bulk'd. with Bulwarks?

Has the Bridge House an efficient Iron Bulkhead at the after end?

How are the openings closed?

Is the Forecastle at least as high as the main or top-gallant rail? Has the Forecastle an efficient Iron or Wood Bulk'd. at after end?

Are the Engine and Boiler openings covered by a Bridge, Poop, Raised Quarter Deck, or enclosed by a Strong Iron or Steel Deckhouse? **YES**

If the openings are not so protected are the exposed parts of the Casings efficiently constructed?

Give thickness of plating; scantlings and spacing of Stiffeners

What is the height of the exposed Casings? Are suitable means provided for closing all openings in them in bad weather?

Are the Weather Deck Hatchways efficiently constructed and at least equal to the requirements of Section 28 of the Rules for 1904-5? Give particulars below:— **YES**


Position and Size.	No. 1. 25x19		No. 2. 29-2x19-0		No. 3. 29-2x19-0		No. 4. 27-1x19-0		Ship.	Rule.
	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.		
Height above top of DECK	30	18	30	18	30	18	30	18		
COAMING Thickness	Sides.....	.44	.44	.44	.44	.44	.44	.44		
	Ends.....	.44	.44	.44	.44	.44	.44	.44		
SHIFTING BEAMS OR WEB PLATES	Number.....	FOUR	FIVE	FIVE	FIVE	FIVE	FIVE	FIVE		
	Section and Scantlings.....	IF PLATE 1/8" x 3/8"	SAME	SAME	AS	AS	Nº 1	Nº 1		
	Material.....	JL FOUR ANGLES 4x3x.44								
* FORE AND AFTERS	Number.....	NONE FITTED								
	Section and Scantlings.....									
	Material.....									
HATCHES Thickness.....	2 1/2	2 1/2	2 1/2	2 1/2	2 1/2	2 1/2	2 1/2	2 1/2		
Remarks.....										

* When the Fore and Afters are of wood the depth should be stated from the underside of the hatches.
 (If the sill of the lowest side scuttle will be less than 6 inches above the Indian Summer Load Line if assigned under the tables, state vertical distance from top of deck at side amidships to lower edge of lowest side scuttle.)

The following information is to be given in all Cases of vessels dealt with under Paras. 11, 12 (under 15 feet Moulded depth) and under Shelter Deck Rules.
 What is the thickness of the Bridge Sheerstrake? **.64** Strake between Main and Bridge Sheerstrakes? **.58**

Delete the words { The Crew are, are not, berthed in the bridge house.
 that do not apply { The arrangements to enable them to get backwards and forwards from their quarters are, are not satisfactory.

Length of Bulwarks in well = _____ Sq. ft.
 Area of Freecing Ports required by Para. 11 (e) each side of vessel = _____ Sq. ft.
 Ft. Tenths. Ft. Tenths. No. } IN Freecing Ports TONNAGE OPENING (each side of vessel) = _____ Sq. ft.
 1. 67 x 1. 5 x ONE }
 Total deficiency or excess = _____ Sq. ft.



Show hereon line of Floors or Tank Top with position of any Breaks in same; also height of Peak Tank tops, &c., &c.

State any special features in the construction of the Vessel *The approved plans of the vessel, four in number are enclosed for reference. Request form attached. Displacement scale and scale of tons per inch forwarded for fresh water allowance. This vessel is similar to the same Builders N° 248 S.S. 'nascent' Sld.*
 Owners _____
 Address _____
 Rpt. N° 2629H

Fee £ _____
 Received by me _____

