

COPY.

Lloyd's Register of Shipping,

71, Fenchurch Street, E.C. 3.

Enclosures.

26th April, 1921.

Sir,

With reference to your letter of the 13th instant submitting for the consideration of the Committee a plan, duplicate, shewing the steam superheating arrangements proposed to be fitted in the S.S. "WESTMINSTER ABBEY" ex "ROLPH WOERMANN", I have to acquaint you that it is noted Manufacturers propose to use material which they have stock, of which the collectors have been made by Messrs. J. Jager, of Elberfeld, and tested by the Surveyors to Germanischer Lloyd, and the elements have been made by Messrs. A.G. Lanchhammer, and have been tested by them to an hydraulic pressure of 100 kilogrammes per square centimetre.

With regard thereto I am directed to inform you that provided a safety valve be fitted to every portion of the superheater which can be shut off from the boiler, and after fitting on board the vessel the whole be found tight and satisfactory under an hydraulic test of 42 kilogrammes per square centimetre, they will be accepted, in this instance, for an intended working pressure of 14 kilogrammes per square centimetre.

One copy of the plan is returned herewith, together with a test certificate, and the duplicate copy has been retained in this Office for reference.

I am, Dear Sir,
Yours faithfully,

Secretary.

H. C. Bahr, Esq.,
BREMEN.



© 2020

Lloyd's Register
Foundation