

REPORT ON ELECTRIC FITTINGS.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

THU 25 MAY 1924

Received at London Office

Date of writing Report 19 20.4.1924 When handed in at Local Office 20.4.1924 Port of Middlesbrough

No. in Survey held at South Bank Date, First Survey whole Last Survey building 19 Reg. Book. (Number of Visits.....)

on the S.S. 'PEGAWAY' Tons { Gross 1825.41 Net 1073.35

Built at South Bank By whom built Smith's Dock Co. Yard No. 782 When built 1924

Owners Hill Shipping Co. Port belonging to Newcastle

Electric Light Installation fitted by James R. Pickersgill & Smith. Contract No. When fitted

As above

System of Distribution

Double Wire

Pressure of supply for Lighting 100 volts, Heating - volts, Power - volts.

Direct or Alternating Current, Lighting Direct Power

If alternating current system, state frequency of periods per second

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off *yes*

Generators, do they comply with the requirements regarding overload *yes*, are they compound wound *yes*
are they over compounded 5 per cent. *yes*, if not compound wound state distance between each generator -

Where more than one generator is fitted are they arranged to run in parallel - , is an adjustable regulating resistance fitted in series with each shunt field *yes*

Are all terminals accessible and clearly marked *yes*, are they so spaced or shielded that they cannot be accidentally earthed, or short circuited *yes*

Position of Generators *Starboard side Engine Room*, are they clear of all inflammable material *yes*

if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the generators *12"* and *yes*, are the generators protected from mechanical injury and damage from water, steam or oil *yes*

are their axis of rotation fore and aft *yes*

Earthing, are the bedplates and frames of the generating plant efficiently earthed *yes* are the prime movers and their respective generators in metallic contact *yes*

Main Switch Boards, where placed *Fore end Engineers Store Starboard Side near Generator* If the generators and main switchboard are not placed in the same compartment, is each generator provided with a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard -

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes *yes*

are they protected from mechanical injury and damage from water, steam or oil *yes*, if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards *12"* and -

are they constructed wholly of durable, incombustible non-absorbent materials *yes*, is all insulation of high dielectric strength and of permanently high insulation resistance *yes*, if semi-insulating material is used, are all conducting parts connected to one pole insulated from the slab with mica or micaite and the slab similarly insulated from its framework *yes*, and is the frame effectively earthed *yes*

Are the following fittings as per Rule, viz. :- spacing or shielding of live parts *yes*, accessibility of all parts *yes*, absence of fuses on back of board *yes*, proportion of omnibus bars *yes*, individual fuses to voltmeter, pilot or earth lamp *yes*, connections of switches *yes*

Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches


A.S. main switches & fuses with A.S. circuit switches & A.S. fuses to various Distribution Boards.

Instruments on main switchboard *One* ammeters *One* voltmeters - synchronising device for paralleling purposes.

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system *2 lamps connected in series across main fuses*

Switches, Circuit Breakers and Fusible Cut-outs, do these comply with the requirements of the Rules *yes*

Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule *yes*
All asbestos lined



Insulation of Cables, state type of cables, single or twin *Single* are the cables insulated and protected as per Tables III or IV of the Rules *Yes*

Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load *.5 Volt (approx)*

Cable Sockets and other connections, are the ends of all cables having a sectional area of 0.007 square inch and above provided with soldering sockets *Yes*

Paper Insulated Cables. If cables are paper covered, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound *Yes*

Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage *Yes*

Support and Protection of Cables, state how the cables are supported and protected *Lead covered & armoured*

If cables are run in wood casings, are the casings and caps secured by screws *-*, are the cap screws of brass *-*, are the cables run in separate grooves *-*. If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VI *Yes*

Refrigerated Chambers, if lights are fitted, are the cables and fittings in accordance with the special requirements *-*

Joints in Cables, state if any, and how made, insulated, and protected *None*

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands *Yes*

Bushes in Beams and Non-watertight Positions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed *Yes* state the material of which the bushes are made *Lead Bushes*

Earthing Connections, state what earthing connections are fitted and their respective sectional areas *Main Switchboard & Generator*

are their connections made as per Rule *-*

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule *-*

Emergency Supply, state position and method of control of the emergency supply and how the generator is driven *-*

Navigation Lamps, are these separately wired *Yes*, controlled by separate switch and separate fuses *Yes*

are the fuses double pole *Yes*, are the switches and fuses grouped in a position accessible only to the officers on watch *Yes*

has each navigation lamp an automatic indicator as per Rule *No*, are separate screens provided for the use of oil and electric side lights *Yes*

are separate oil lanterns provided for the mast head lights and side lights *Yes*

Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight *Yes*

are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected *No*

are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected *No*

how are the cables led *-*

where are the controlling switches situated *-*

Searchlight Lamps, No. of *-*, whether fixed or portable *-*, are their fittings as per Rule *-*

Arc Lamps, other than searchlight lamps, No. of *-*, are their live parts insulated from the frame or case *-*, are their fittings as per Rule *-*

Motors, are their working parts readily accessible *-*, are the coils self-contained and readily removable for replacement *-*

are the brushes, brush holders, terminals and lubricating arrangements as per Rule *-*, are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material *-*

are they protected from mechanical injury and damage from water, steam or oil *-* are their axis of rotation fore and aft *-*

if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type *-*

if not of this type, state distance of the combustible material horizontally or vertically above the motors *-* and *-*

Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed as per Rule *-*

Lightning Conductors, where lightning conductors are required, are these fitted as per Rule *Shel masts*

Ships carrying Oil having a Flash Point less than 150° F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings *-*

If portable lamps for use in dangerous spaces are supplied, are they of a type approved by the Home Office *-*

PARTICULARS OF GENERATING PLANT.

| DESCRIPTION OF GENERATOR. | No. of | RATED AT | | | | DRIVEN BY. | WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE. | |
|---------------------------|--------|------------|--------|----------|----------------|-------------|--|----------------------|
| | | Kilowatts. | Volts. | Ampères. | Revs. per Min. | | Fuel Used. | Flash Point of Fuel. |
| MAIN ... | ... | 6 | 100 | 60 | 350 | Ruby Engine | | |
| AUXILIARY ... | ... | | | | | | | |
| EMERGENCY ... | ... | | | | | | | |
| ROTARY TRANSFORMER | | | | | | | | |

LIGHTING AND HEATING CONDUCTORS.

| Ref. No. | DESCRIPTION. | No. of Conductors. | Effective Area of each Conductor. Sq. Ins. | COMPOSITION OF STRAND. | | Total Maximum Current. Amperes. | Approximate Length. (Lead and Return.) Feet. | Insulated with | HOW PROTECTED. |
|----------|----------------------------|--------------------|--|------------------------|-----------|---------------------------------|--|----------------|----------------|
| | | | | No. | Diameter. | | | | |
| | MAIN GENERATOR... | 2 | .060 | 19 | .064 | 60 | 15 ft | Rubber | Asbestos |
| | AUXILIARY GENERATOR | | | | | | | | |
| | EMERGENCY GENERATOR | | | | | | | | |
| | ROTARY TRANSFORMER... | | | | | | | | |
| | AUXILIARY SWITCHBOARDS ... | | | | | | | | |
| | ENGINE ROOM ... | 2 | .0100 | 4 | .044 | 12.3 | 22 ft | As | As |
| | BOILER ROOM ... | 2 | .0015 | 1 | .044 | 2.3 | 40 ft | As | As |
| | Enginers | 2 | .0100 | 4 | .044 | 11.5 | 56 ft | As | As |
| | WIRELESS ... | 2 | .0100 | 4 | .044 | | 10.3 ft | As | As |
| | SEARCHLIGHT ... | 2 | .0015 | 1 | .044 | 1.3 | 32 ft | As | As |
| | MASTHEAD LIGHT... | 2 | .0015 | 1 | .044 | 1.3 | 85 ft | As | As |
| | SIDE LIGHTS ... | 2 | .0015 | 1 | .044 | 1.3 | 18 ft | As | As |
| | COMPASS LIGHTS ... | 2 | .0015 | 1 | .044 | 1.3 | | As | As |
| | POOP LIGHTS ... | | | | | | | | |
| | CARGO LIGHTS ... | 2 | .0145 | 4 | .052 | 8.5 | 34 ft | As | As |
| | ARC LAMPS ... | | | | | | | | |
| | HEATERS ... | | | | | | | | |

MOTOR CONDUCTORS.

| Ref. No. | DESCRIPTION. | No. of Motors. | Effective Area of each Conductor. Sq. Ins. | COMPOSITION OF STRAND. | | Total Maximum Current. Amperes. | Approximate Length. (Lead and Return.) Feet. | Insulated with | HOW PROTECTED. |
|----------|-----------------------------|----------------|--|------------------------|-----------|---------------------------------|--|----------------|----------------|
| | | | | No. | Diameter. | | | | |
| | BALLAST PUMP ... | | | | | | | | |
| | MAIN BILGE LINE PUMPS ... | | | | | | | | |
| | GENERAL SERVICE PUMP ... | | | | | | | | |
| | EMERGENCY BILGE PUMP ... | | | | | | | | |
| | SANITARY PUMP ... | | | | | | | | |
| | CIRC. SEA WATER PUMPS ... | | | | | | | | |
| | CIRC. FRESH WATER PUMPS ... | | | | | | | | |
| | AIR COMPRESSOR ... | | | | | | | | |
| | FRESH WATER PUMP ... | | | | | | | | |
| | ENGINE TURNING GEAR ... | | | | | | | | |
| | ENGINE REVERSING GEAR ... | | | | | | | | |
| | LUBRICATING OIL PUMPS ... | | | | | | | | |
| | OIL FUEL TRANSFER PUMP ... | | | | | | | | |
| | WINDLASS ... | | | | | | | | |
| | WINCHES, FORWARD ... | | | | | | | | |
| | WINCHES, AFT ... | | | | | | | | |
| | STEERING GEAR ... | | | | | | | | |
| | WORKSHOP MOTOR ... | | | | | | | | |
| | VENTILATING FANS ... | | | | | | | | |

All Conductors are of annealed copper conforming to British Standard Specification No. 7.
 The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.
 The foregoing is a correct description.

RICHARD PICKERSGILL & SONS, LTD.

Electrical Engineers.

Date May 24/24

COMPASSES.

Distance between electric generators or motors and standard compass 160 ft.

Distance between electric generators or motors and steering compass -

The nearest cables to the compasses are as follows:—

A cable carrying 1/2 Ampères 2 feet from standard compass 2 feet from steering compass.

A cable carrying 5.5 Ampères 12 feet from standard compass 8 feet from steering compass.

A cable carrying 6 Ampères 50 feet from standard compass 45 feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power. yes

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted. none

The maximum deviation due to electric currents was found to be - degrees on - course in the case of the standard

compass, and - degrees on FOR SMITH'S DOCK course in the case of the steering compass.

J. W. Cairns
 Shipyard Manager.

Builder's Signature.

Date 26th May 1924

Is this installation a duplicate of a previous case no If so, state name of vessel -

General Remarks (State quality of workmanship, opinions as to class, &c. This installation has been fitted)

in accordance with the Rules: is of good materials and workmanship

and on completion was examined under full working conditions and found satisfactory

THE RECORD.

Elec. Light.

R.M. 2/6/24.

Total Capacity of Generators 6 Kilowatts

| | | | |
|--------------------------------|-----------|-------------------|-----------------|
| The amount of Fee ... | £ 6 : 0 0 | When applied for, | 28.5 19.24 |
| Travelling Expenses (if any) £ | ✓ : | When received, | See debit book. |

A. D. Morrison

Surveyor to Lloyd's Register of Shipping.

Committee's Minute

Assigned

1111.22.—Transfer.
 (The Surveyors are requested not to write on or below the space for Committee's Minute.)



© 2020

Lloyd's Register Foundation