

STEEL STEAMER.

No. 2999

Port of Glasgow Date of completion of Report 20 Feb 1911 Received at London Office 1 MAR 1911
Survey held at Sumbarton Date, First Survey 4th March 1910 Last Survey 10th Feb 1911

TONNAGE under } 2864.78
Tonnage Deck..}

CLASS *+ 100 A.1. Shade 02* FEET.

Master John W. Robinson

Year of Appointment	(1) As Master in service of	
	owner of present vessel:—19	
	(2) As Master of this	
	vessel:—19	

Built at *Dumbarton*

When built 1911 Launched 1st Dec 1910

By whom built. *W Denny Bro*

Owners. *British India S. N. Coy.*

Managers.

Residence

Port belonging to Glasgow.

Register Tonnage } 1925.59
as cut on Beam.... }

Destined Voyage

If Surveyed while Building, Afloat, or in Dry Dock Yes

LENGTH on Deck as per Rule	Ft. 390	Ins. 0	BREADTH Moulded ..	Ft. 44	Ins. 11 1/2	DEPTH, ACTUAL Do.	Top of Floors to top of Awn. or Shelter Dk. Beams	Ft. 22	Ins. 0 1/2	No. of Decks with flat laid	22
							do. Upper Deck Beams			No. of Tiers of Beams	4
Dimensions of Ship per Register,						Awn. or Shelter Dk.	Moulded depth, ft. 32 ins. 6 1/2	To Awning or Shelter Dk.		Round up of Uppermost Dk. Beam, Actual ..	12 1/2 ins.
Length	390.8		breadth	50.18		depth.	22.0	Upper Deck.	Moulded depth, ft. 24 ins. 6	To Upper Dk.	

FRAMING.		Inches in Ship.	Inches in Ship.	Inches in Ship.	Inches per Rule Or as Approved.	Inches per Rule Or as Approved.
FRAME, Angles, or E L Bars, amidships . . .		8	3½	48	8	3½
Do. in peaks . . .	angle	5½	3½	24	5½	3½
Do. in way of Double Bottoms at Solid Floors . . .		3½	3½	40	3½	3½
Spacing of "Frames from centre to centre amidships . . .		24½			24½	
" length to collision bulkhead . . .		24½			24½	
" of Frames from centre to centre in peaks . . .		24			24	
REVERSED FRAME, Angles . . .	in peaks	3½	3½	40	3½	3½
FRAMING, depth of girder . . .	in double bottom	8			8	
FLOORS, depth and thickness of Floor Plate } at mid-line for ¾ length amidships . . . }						
" in way of Engine and Boiler spaces . . .						
" thickness at the ends of vessel . . .						
" depth at ¾ the half-bdth. as per Rule . . .						
" height extended at the Bilges . . .						
FLOORS & BRACKETS, in Cell Dble Bottoms state if flanged (top & bottom) . . .				40		40
" spacing . . .		24½			24½	
CENTRE GIRDER, in Dbl. bottom, dpth & thicknss Angles, Top . . .		42		50	42	50
" Bottom . . .		4½	3½	50	4½	3½
" to Floors . . .		4½	4½	60	4½	4½
SIDE GIRDERS, number and thickness . . .		3½	3½	40	3½	3½
" state if flanged (top & bottom) . . .		one	38	one	38	38
" Angles . . .		3½	3½	40	3½	40
MARGIN PLATE, depth (exclusive of flange) } and thickness . . . }		30		46	30	46
" Angles to outside plating . . .		3½	3½	46	3½	46
" to floors . . .		3½	3½	40	3½	40
" Height of Brackets above at bilge . . .		24		24		
INNER BOTTOM PLATING, breadth and thickness of Middle Line Strake . . .		42		56	42	56
" thickness in Engine and Boiler space . . .		E 48	8	56		
" Remainder in Holds . . .		48		48		48
BEAMS, Angle or Single Dk, Single Angle } Bulb Angle, Plate, Tee Bulb or Channel }		8½	3½	50	8½	3½
" Angles on upper edge . . .						
" Spacing . . .		49		49		
BEAMS, Upper or Second Deck, Single Angle } Bulb Angle, Plate, Tee Bulb or Channel }		9½	3½	52	9½	3½
" Angles on upper edge . . .						
" Spacing . . .		49		49		
BEAMS, Third or Fourth Deck, Single Angle } Bulb Angle, Plate, Tee Bulb or Channel }		10	6	44	10	6
" Angles on upper edge . . .						
" Spacing . . .		49		49		
BEAMS, Fourth or Fifth Deck, Plate, Tee } Bulb or Channel . . . }						
" Angles on upper edge . . .						
" Spacing . . .						
BEAMS, Poop Deck, Angle, Bulb Angle, Plate, } Tee Bulb or Channel . . . }						
" Angles on upper edge . . .						
" Spacing . . .						
BEAMS, Bridge Deck, Angle, Bulb Angle, Plate, } Tee Bulb or Channel . . . }		8½	3½	50	8½	3½
" Angles on upper edge . . .						
" Spacing . . .		49				
BEAMS, Forecastle Deck, Angle, Bulb Angle, } Plate, Tee Bulb or Channel . . . }						
" Angles on upper edge . . .						
" Spacing . . .						
PILLARS, In 'tween Deck, size and spacing Hold . . .		2 1/4 x 8		2 1/4 x 8		
" Quarter, 'tween Dks., " "		2 3/4 x 8		2 3/4 x 8		
" in Hold . . .		3 3/4		3 3/4		
WEB-FRAMES, In Fore Body, No. and spacing br'dth. & thicknss . . .		-		-		
" No. of Side Stringers . . .		-		-		
WEB FRAMES, In E. & B. Space, No. & spacing br'dth. & thicknss . . .		8	6	8 1/2	18	40
WEB FRAMES, In After Body, No. and spacing br'dth. & thicknss . . .		-		-		
" No. of Side Stringers . . .		-		-		
" Size of Face Angles to Web Frames . . .		6 1/2	3 1/2	60	6 1/2	3 1/2
BRACKET PLATES to Stringers between Web Frames, depth and thickness . . .		18		48	18	48

W512-0285(2)2) Cto issued 4/3/11. Found