

# Lloyd's Register of Shipping.

## SURVEYS FOR FREEBOARD.—STEAM SHIPS.

PARTICULARS RELATING TO ALL STEAM SHIPS EITHER FLUSH DECKED, OR WITH TOP GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, OR WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.

Port of Survey  
Date of Survey 19th Sept 1932  
Name of Surveyor

*Complete Shade Deck*

Ship's Name. ANGORA  
Number in Register Book 57136  
Port of Registry and Nationality. Glasgow  
British  
Official Number. 129535  
Gross Tonnage. 4298  
Date of Build. 1911-2  
Particulars of Classification. +100-A.1. Shade deck.

Registered Dimensions from Ship's Register.	LENGTH.	BREADTH.	DEPTH.	UNDER DECK TONNAGE.
	<u>390.8</u>	<u>50.18</u>	<u>22.0</u>	<u>2864.78</u>
Length on LOADLINE.	<u>390.0</u>	Frame Depth <u>8</u> Rule <u>52</u>	Ceiling <u>+20</u> Sheer <u>+4</u> <i>drop in T.T.</i> <u>6" = +25</u>	Peak Tanks <u>✓</u>
CORRECTED DIMENSIONS.	<u>390.0</u>	<u>49.46</u>	<u>23.21</u>	<u>2864.78</u>

Co-efficient of fineness..... .636  
Any modification necessary } all O.B.  
[Para. 4 (a) to (e)]\* }  
Co-efficient as corrected ..... found in Tables 68 & 66

Sheer { Stem..... 108 } 156 ÷ 2 = 78 ...Mean  
at { Sternpost ... 48 }  
Sheer at  $\frac{1}{2}$  of the length from { Stem 61 } 84 ÷ 2 = 42 ...Mean  
Sternpost 23 } 55 = 76.36  
Gradual mean Sheer ..... 76.36  
Standard mean Sheer [Table, Para. 18] ..... 49.00 Correction  
Difference..... 24.36 ÷ 4 = -6.34  
§ If limited as Para. 18 (f) .....

Rise in Sheer { At front of bridge house.....  
from amidships {  
[Para. 18 (e)] { At after end of forecastle .....

Fall in Sheer }  
Para. 18 (d) } ÷ 2 =  
Length uncovered ..... Correction

### ALLOWANCE FOR DECK ERECTIONS:—

Freeboard, Table C..... 2' 3"  
Correction for Length, if required (Para. 12, 13, and 14) .....  
Freeboard by Table A, corrected for sheer, and for length, if required (Para. 11, 12, 13, and 14) } 4' 6 1/4"  
Difference ..... 2' 3 1/4"  
Percentage as below..... 41.3

Correction for R. Q. Dk. if engine and boiler openings not covered by bridge house (Para. 11) }

Allowance for Deck Erections ..... 11 1/4"

	Length.	Length allowed.	Height.
Forecastle..... <i>open</i>	<u>59.0</u>	<u>53.875</u>	} <u>8' 0"</u>
Bridge House..... <i>open</i>	<u>23.5</u>	<u>11.75</u>	
..... <i>closed</i>	<u>104.16</u>	<u>104.16</u>	
† Raised Q. Dk. <i>open</i>	<u>57.08</u>	<u>42.81</u>	
..... <i>closed</i>	<u>6.16</u>	<u>3.08</u>	
Poop..... <i>open</i>	<u>41.16</u>	<u>20.58</u>	
Total .....		<u>239.255</u>	<u>.613</u>
Length of Ship .....		<u>390</u>	

Corresponding percentage }  
(Para. 11, 12, 13, or 14) } 41.3

Moulded Depth as measured..... 24' 6"

Addition for Keel below base line for draught record..... inches.

NOTE.—If the depth is measured when vessel is afloat, the details of measurement should be reported.

### CORRECTION FOR LENGTH.

Length of Ship on Loadline..... 390  
Length in Table ..... 294  
Difference ..... 96  
Correction for 10ft., Table A. .... 1.3 Table C. ✓  
× Difference divided by 10 ..... 12.48 (if required.)  
If  $\frac{1}{10}$ ths length covered divide by 2 +6 1/4"

### CORRECTION FOR IRON DECK.

Proportion covered, if less than  $\frac{7}{10}$ ths length covered ..... .613  
Thickness of usual wood deck, less stringer ..... 3 1/2"  
2 1/2" Peak sheathing fitted off 1" = - 1/2"

### CORRECTION FOR ROUND OF BEAM.

Breadth at Gunwale amidships..... 49' 1 1/2"  
Round of Beam ..... 12  
Normal round..... 12 1/4  
Difference ..... 1/4 ÷ 2 = 1/8"  
Proportion of Deck uncovered (Para. 19) ..... ✓

NOTE.—The round of beam should be reported on the full breadth of vessel at the gunwale.

Freeboard, Table A ..... 5' 1"  
Correction for Sheer ..... - 6 3/4"  
4' 6 1/4"  
Correction for Length ..... + 6 1/4"  
5' 0 1/2"  
Allowance for Deck Erections ..... - 11 1/4"  
4' 1 1/4"  
Correction for Round of Beam.....  
Correction for fall in Sheer (if any).....  
Correction for Steel Deck (if required) 2 1/2" wood sheathing - 1/2"  
4' 0 3/4"  
Additions for non-compliance with provisions of }  
Para. 11 (d) and (e) † }  
Other Corrections (if any) .....

Winter Freeboard ..... 4' 0 3/4"  
Summer Freeboard ..... 3' 8 1/4"  
Indian Summer Freeboard ..... 3' 3 3/4"  
N. A. Winter Freeboard .....

Correction necessary because clearside amidships, measured in accordance with the Statute is not taken at the intersection of the wood or steel deck with side.

Winter Freeboard from deck line .....  
Summer " " " " .....  
Indian Summer " " " " .....  
N. A. Winter " " " " .....

### SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, Wood, ~~Steel~~, Deck:—

Tropical Fresh Water Line above Centre of Disc ... 9 1/4"  
Fresh Water Line " " ... 5 1/4"  
Tropical Line " " ... 4 1/2"  
Winter Line below " " ... 4 1/2"  
Winter North Atlantic Line " " ... ✓

Tropical Fresh Water Freeboard ... 3' 8 1/4"  
Fresh Water " " ... 2' 10 1/2"  
Tropical " " ... 3' 3"  
Winter " " ... 3' 3 1/4"  
Winter North Atlantic " " ... 4' 0 1/4"

21 SEP 1932