

HATCHWAYS ON FREEBOARD AND SUPERSTRUCTURE DECKS											
FREEBOARD DECK.						SHelter DECK.					
Description of Hatchway ... ..	No. 1	No. 2	No. 3	No. 4	No. 5	No. 1	No. 2	No. 3	No. 4	No. 5	
Dimensions of Hatchway ... ..	24'-3" x 14'-3"	33'-0" x 18'-1"	24'-9" x 18'-1"	20'-7" x 18'-1"	24'-9" x 18'-1"	24'-3" x 14'-3"	33'-0" x 18'-1"	24'-9" x 18'-1"	33'-0" x 18'-1"	24'-9" x 18'-1"	
COAMINGS {	Height above Deck ... ..	9'-3 1/2" x 44'	9'-3 1/2" x 55'	9'-3 1/2" x 44'	9'-3 1/2" x 44'	9'-3 1/2" x 44'	31' ✓	31' ✓	31' ✓	31' ✓	
	Thickness { Ends ... ..	✓	✓	✓	✓	✓	.50	.46 ✓	.50	.46 ✓	
	Stiffeners ... ..	✓	✓	✓	✓	✓	.40	.40	.40	.40	
	Brackets, Stays ... ..	✓	✓	✓	✓	✓	10'-3 1/2" x 6 L	10'-3 1/2" x 6 L	10'-3 1/2" x 6 L	17'-3" x 4 L	
HATCH BEAMS {	Number ... ..	5	4	5	4	5	5	4	6	7	
	Spacing ... ..	4'-0 1/2" ✓	4'-1 1/2" ✓	4'-1 1/2" ✓	4'-1 1/2" ✓	4'-1 1/2" ✓	4'-1 1/2" ✓	4'-1 1/2" ✓	4'-1 1/2" ✓	4'-1 1/2" ✓	
	Scantling and Sketch ... ..	F 3 x 3 x .42 L 15 x .30 F 3 x 3 x .42	F 4 x 3 x .44 L 16 x .34 F 4 x 3 x .44	SAME AS No. 2	SAME AS No. 2	F 3 x 3 x .42 L 15 x .30 F 3 x 3 x .42	F 3 x 3 x .44 L 16 x .34 F 4 x 3 x .44	SAME AS No. 2	SAME AS No. 2	SAME AS No. 2	
	Bearing Surface ... ..	3' ✓									
FORE AND AFTERS {	Number ... ..										
	Spacing ... ..										
	Unsupported Lengths ... ..										
	Scantling* and Sketch ... ..										
No FORE AND AFTERS FITTED ✓											
HATCH COVERS {	Bearing Surface ... ..										
	Material ... ..	N.P. ✓					N.P. ✓				
	Thickness ... ..	3' ✓					3' ✓				
	How fitted ... ..	F.E.A. ✓					F.E.A. ✓				
SAME AS NO. 1 HATCH ✓											
Spacing of Cleats ... ..	24' ✓					24' ✓					
Number of Tarpaulins ... ..	None					3					

\*Are wood fore and afters steel shod at all bearing surfaces? ☒ YES

Are battens and wedges efficient and in good condition? ☒ YES

Are tarpaulins in good condition and in accordance with rule requirements? ☒ YES - ON SHELTER DO ONLY

Are lashings provided in accordance with rule requirements? ☒ NO

ODD HATCHES

DECK YARD HATCHES

2-7-9' x 9'-4'

10' x 3' x 5' coamings

45 0.7. Steel covers

hooking bars fitted to Yacht Hatch

2, 3, 4, 5 on Shelter DO

2, 3, 4, 5 on Shelter DO

2, 3, 4, 5 on Shelter DO

Particulars of fiddley, funnel and ventilator coamings:—

Particulars of Flush Bunker Scuttles:—

Particulars of Companionways :—

Particulars of Ventilators in exposed positions on freeboard and superstructure decks :—

Particulars of Air Pipes in exposed positions on freeboard, raised quarter, or superstructure decks :—

Particulars of Gangway Cargo and Coaling Ports:—

Particulars of Scuppers and Sanitary Discharge Pipes —  
Scuppers draining Upper Deck led overboard 24" below deck with S.V.s fitted at Ships Sewerage

Lloyd's Register of Shipping.  
COPY OF FREEBOARD REPORT.

Ship's Name **ITALIAN PRINCE** Official 1  
Type **Complete Superstructure with Tonnage Opening**  
**PARTICULARS OF SUPERSTRUCTURES.**

	Mean covered length.	Height.
Poop enclosed - - - - -	31.25	8.75
„ overhang - - - - -		
R.Q.D. enclosed - - - - -		
„ overhang - - - - -		
Bridge enclosed - - - - -		
„ overhang aft - - - - -	327.75	8.75
„ overhang forward - - - - -		
F'cle enclosed - - - - -		
„ overhang - - - - -		
Trunk aft - - - - -		
„ forward - - - - -		
Tonnage opening aft - - - - -	4.00	
„ „ forward - - - - -		
TOTAL - - - - -	363.00	

W515-0199