

Lloyd's Register of Shipping.
SURVEYS FOR FREEBOARD. STEAM SHIPS.PARTICULARS RELATING TO ALL STEAM SHIPS EITHER FLUSH DECKED, OR WITH
TOP GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, OR
WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS
CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.

Port of Survey

Date of Survey

Name of Surveyor

Ship's Name.
SAND GATE CASTLEPort of Registry
and Nationality.
London
BritishOfficial
Number.
146633Gross
Tonnage.
7634Date of Build
1922

Particulars of Classification.

+ 100 A1 Shelter Deck
with Freeboard.

Register Book

LENGTH. BREADTH. DEPTH. UNDER DECK
TONNAGE.

75 56.35 36.45 7032.39

Frame Depth 7 Ceiling fitted Peak
Rule " 7 Sheer +1.05 Tanks } Inch- .33 Tank free
4" = +.16

75 56.02 37.66 7032.39

784

essary } C.D.B

ed 76

119 } 199 ÷ 2 = 99.5...Mean

Length from Stem 59 Sternpost 40.5 99.5 ÷ 2 = 49.75...Mean

er [Table, Para. 18] 52.47 Correction

Difference 37.98 ÷ 4 =

ra. 18 (f) - 9 1/2"

At front of bridge house..... ✓

At after end of forecastle ✓

÷ 2 =

ed ✓ Correction ✓

ALLOWANCE FOR DECK ERECTIONS :-

le C..... 11'-0" 60.3'-2" 7'-10"

Length, if required (Para. 12, 13, and 14) 3
7'-7"Table A. corrected for sheer, and for length, }
quired (Para. 11, 12, 13, and 14) } 9-8

..... 2-1

below..... 24.72%

6.18

or R. Q. Dk. if engine and boiler openings not }
d by bridge house (Para. 11) }

or Deck Erections - 6 1/4"

Length. Length allowed. Height.

..... 45.00 45.00 8'-0"

ouse 130.00 130.00 8'-6"

Qr. Dk.....

.....

.....

Total 175

f Ship 424.75 = 412

ading percentage }

11, 12, 13, or 14) } 24.72% ✓

Moulded Depth as measured..... 38'-7 1/2"

Addition for Keel below base line
for draught record..... inches.NOTE. - If the
depth is measured
when vessel is
adroit, the details
of measurement
should be reported.

CORRECTION FOR LENGTH.

Length of Ship on Loadline..... 424.75
Length in Table 463.50
Difference 38.75
Correction for 10ft., Table A. 1.7 Table C. . 8
× Difference divided by 10 6.59 (if required.) 3.1
If 1/10ths length covered divide by 2 - 6 1/2" - 3

CORRECTION FOR IRON DECK.

Proportion covered, if less than 1/10ths length covered 412
Thickness of usual wood deck, less stringer 3 1/2" - 1 1/2"

CORRECTION FOR ROUND OF BEAM.

Breadth at Gunwale amidships..... 55'-0"
Round of Beam 17 1/2"
Normal round..... 13 3/4"
Difference 3 3/4" ÷ 2 = 1 7/8"
Proportion of Deck uncovered (Para. 19) 58.8
- 1"NOTE. - The
round of beam
should be report-
ed on the full
breadth of vessel
at the gunwale.Freeboard, Table A 11'-0"
Correction for Sheer 9 1/2"
10'-2 1/2"
Correction for Length 6 3/4"
9'-8 1/4"
Allowance for Deck Erections 6 1/4"
9'-1 3/4"
Correction for Round of Beam..... 1
9'-0 3/4"
Correction for fall in Sheer (if any)..... ✓
Correction for Steel Deck (if required) 1 1/2"
8'-11 1/4"
Additions for non-compliance with provisions of }
Para. 11 (d) and (e) † } ✓
Other Corrections (if any) ✓Winter Freeboard 8'-11 1/4"
Summer Freeboard 7 1/2" 8'-3 3/4"
Indian Summer Freeboard 7'-8 1/4"
N. A. Winter FreeboardCorrection necessary because clearside amidships, measured
in accordance with the Statute is not taken at the
intersection of the wood or steel deck with side.Winter Freeboard from deck line
Summer " " " "
Indian Summer " " " "
N. A. Winter " " " "

SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, Wood, Steel, Deck :-

Tropical Fresh Water Line above Centre of Disc ... 15 3/4" Tropical Fresh Water Freeboard ...
Fresh Water Line " " ... 8 1/4" Fresh Water " " ...
Tropical Line " " ... 7 1/2" Tropical " " ...
Winter Line below " " ... 7 1/2" Winter " " ...
Winter North Atlantic Line " " ... ✓ Winter North Atlantic " " ...

8'-3 3/4" ✓

7'-0 1/2"

7'-7 1/2"

7'-8 1/4"

8'-11 1/4"

29 MAR 1933

WS16-0266

RECEIVED

RECEIVED

Lloyd's Register
Foundation
29 MAR 1933