

COPY.

Lloyd's Register of Shipping.

Port BOMBAY.

30TH MAY 1933.



This is to Certify that

the Committee of this Society have approved on behalf of the
~~the undersigned Surveyor to this Society did at the request of~~

Board of Trade, the position of the centre of the disc and of the
lines to be used in connection therewith on the Steel Twin Screw
Steamer

" N U D D E A "

No. 68692 in Register Book, and hereby certify -

That the centre of such disc is placed at 11 feet and 0 1/2 inch
below the upper deckline (Steel Shelterdeck) marked under the
provisions of International Loadline Convention of 1930.

That the maximum Loadline in Tropical Fresh Water to be 15
inches above the centre of the disc.

That the maximum Loadline in Fresh Water to be 7 3/4 inches above
the centre of the disc.

That the Tropical Loadline to be 7 1/2 inches above the centre of
the disc.

That the maximum Loadline in Winter to be 7 1/2 inches below the
centre of the disc.

This certificate is to remain in force until
a new Loadline certificate is issued.

H. P. Southwell

Surveyor to Lloyd's Register.

Certificate is issued upon the terms of the Rules and Regulations of the Society, which provide that:—
While the Committee use their best endeavours to ensure that the functions of the Society are properly executed, it is
understood that neither the Committee nor the Society are under any circumstances whatever to be held responsible for
any inaccuracy in any report or certificate issued by the Society or its Surveyors, or in any entry in the Register Book or other
publication of the Society, or for any error of judgment, default, or negligence of the Surveyors, or other Officers or Agents
of the Society."