

Trieste Rpt 8532

Lloyd's Register of Shipping.

Order: 19978
Post: 2181
Komm: 33480/Pr
Best: 1863/4No: 1024
3405

Surveyors' Office, VIENNA.

is to certify, that Hans Kolbow the undersigned surveyor to this Society tested in
works of Messrs. Witkowitz Bergbau & Eisenhütten Gew. of Witkowitz
annealed Siemens Martin Boiler steel specified hereunder, ordered
Messrs. Stabilimento Tecnico Triestino of Trieste
Motor No: 2165/66
the ship No. 206 Boiler No. and that the results of tests were as are set forth below.

Dimensions. in millimeters			Intended for	sample number	Charge- number	Tensile tenacity in Kg/mm ²			Elongation in 200 mm. in %.	Bending tests.		Reg. Ital. LLOYDS 3405 Remarks HK.7.12.28 9061	
Length.	Breadth.	Thick- ness.				As per rules.	Ord- ered.	By test.		Cold.	Tem- pered		
370	470	35	manhole cover	301	8651	41	41	42.5	27	g	o	d	No: 9061
						47	47	43.0	23	"			
V i e n n a, 17th December 1928													
<i>Hans Kolbow</i>													



This Certificate is issued upon the terms of the Rules and Regulations of the Society, which provide that:—

"While the Committee use their best endeavours to ensure that the functions of the Society are properly executed, it is to be understood that neither the Committee nor the Society are under any circumstances whatever to be held responsible for any inaccuracy in any report or certificate issued by the Society or its Surveyors, or in any entry in the Register Book or other publication of the Society, or for any error of judgment, default, or negligence of the Surveyors, or other Officers or Agents of the Society."

N.B.—Material with less than 26 Tons tensile strength may not be used in the construction of boilers for classed vessels, unless specially sanctioned by the Committee.

1 Ton per square inch = 1,574 Kilo per square millimeter. 1 Kilo per square millimeter = 0,635 Tons per square inch.