

Friese Rpt 8532

## Lloyd's Register of Shipping.

Order: 19978  
Post: 2181  
Comm: 33480/Pr  
Est: 1863/4

No: 1022  
3405

Surveyors' Office, VIENNA.

Hans Kolbow

to certify, that the undersigned surveyor to this Society tested in

works of Messrs. Witkowitzer Bergbau &amp; Eisenhütten Gew. of Witkowitz

sealed Siemens Martin Boiler steel

Messrs. Stabilimento Tecnico Triestino specified hereunder, ordered

Motor No: 5160/61

of Trieste

ship No. 205 Boiler No.

and that the results of tests were as are set forth below.

Dimensions millimeters			Intended for	Sample number	Charge- number	Tensile tenacity in Kg/mm <sup>2</sup>			Elongation in 200 mm. In %	Bending tests.		LLOYDS Reg. Ital. 3405 Remarks HK.7.12.28 9061
Width.	Breadth.	Thickness.		Stamped on the material.	As per rules.	Ord- ered.	By test.	Cold.		Tem- pered		
0	470	35	manhole cover	301	8651	41 47	41 47	42.5 43.0	27 23	good	"	No:9061

Vienna, 17th December 1928

Hans Kolbow.




This Certificate is issued upon the terms of the Rules and Regulations of the Society, which provide that:—  
While the Committee use their best endeavours to ensure that the functions of the Society are properly executed, it is to be understood that the Committee nor the Society are under any circumstances whatever to be held responsible for any inaccuracy in any report made issued by the Society or its Surveyors, or in any entry in the Register Book or other publication of the Society, or for any error, default, or negligence of the Surveyors, or other Officers or Agents of the Society."

Material with less than 26 Tons tensile strength may not be used in the construction of boilers for classed vessels, unless specially sanctioned by the Committee.

1 Ton per square inch = 1,574 Kilo per square millimeter. 1 Kilo per square millimeter = 0.635 Tons per square inch.

WS 33 - 0120

Lloyd's Register  
Foundation