



No action necessary, matter dealt with on first entry report.

N.B.—If this Report is copied by Copying Press, especial care must be taken that the copying paper is not so much damped as to spread the ink, or to cause it to show through to the other side.

When Anchors or Cables are supplied, the particulars are to be reported in the following form:—

Number of Certificate.	Anchors #	WEIGHT, EL STOCK		WEIGHT OF STOCK		TEST, PER CERTIFICATE		WEIGHT REQUIRED BY TABLE 30 or 31.		Description of Anchor.	Makers.	Where and when tested and Superintendent.
		Owts. qrs. lbs.	Owts. qrs. lbs.	Owts. qrs. lbs.	Owts. qrs. lbs.	Owts. qrs. lbs.	Owts. qrs. lbs.					
	1st Bower ...											
	2nd "											
	3rd "											
	Collets Weight.											
	Stream .....											
	Kedge.....											

\* When a bower anchor is supplied it must be clearly stated whether it is a 1st, 2nd, or 3rd bower.

CHAIN CABLES.

Number of Certificate.	Length and size supplied.		Test per Certificate.		WEIGHT OF CHAIN CABLE.		Length and size per Table 30 or 31.		Description.	Makers of Cables.	When and where tested and Superintendent.
	Length.	Diam. Ins.	Statio- lory. Tons.	Breaking. Tons.	Supplied. Owts. qrs. lbs.	Per Table 30 or 31. Owts. qrs. lbs.	Length. Fathoms.	Diam. Ins.			

Iron Stream Chain of Steel Wire...

M  
2.2.

THE SURVEYORS ARE REQUESTED NOT TO WRITE ACROSS THIS MARGIN.



© 2020

Register of Engineers and Surveyors  
 Rpt. No. ...  
 Date of ...  
 Name of ...  
 Rank ...  
 Master ...  
 Register ...  
 No. of ...  
 Dia. of ...  
 collars ...

This is ...  
 required ...  
 the ...  
 the ...