


Name of Vessel *"City of Salisbury"*

No. in Register Book

	FEET.	INCHES.
Moulded Depth	33	0
Stringer Plate		$\frac{1}{2}$
Thickness of wood sheathing if required		-
Statutory deck line above intersection of <u>actual</u> deck at side		$1\frac{3}{4}$
Total depth from top of statutory deck line to top of keel	33	$2\frac{1}{4}$
Freeboard recorded	6	$4\frac{1}{2}$
Moulded Draft	26	$9\frac{3}{4}$
Add for keel—Flat or Bar		$2\frac{1}{2}$
Draught	27	$0\frac{1}{4}$

Draught for record

Disale 27' 0 1/4"



© 2020

Lloyd's Register
Foundation

RETAIN



© 2020

Lloyd's Register
Foundation

(Stem..... 120
(Stempost ... 60
at $\frac{1}{2}$ of the length fr
al mean Sheer 90
ard mean Sheer [Ta
Di
limited as Para. 18 (6)
e in Sheer { At fro
amidships {
18 (6) { At aft
all in Sheer }
18 (d) {
uncovered
ALLO
board, Table C.....
ction for Length, i
board by Table A.
if requi
rence
ntage as below.....
ction for R. Q. D
covered by bridg
ance for Deck En
castle.....
ge House
ised Qr. Dk.....
Total
th of Ship
sponding percent
ara. 11, 12, 18-
HEBOARD rec
7 - APR
the frames, skin pl
of ceiling should b
vessels obtaining an
ships the height of t
flush-decked vessels
post. In vessels h
one-eighth of the v