

50,716.

F.E.

Received by Chief Ship Surveyor

Received from Chief Ship Surveyor

VESSEL'S NAME STEEL S.S. "COMERIC" Rpt. Sld. No. 27609

The remarks of the Chief Ship Surveyor are desired on this case for the consideration of the Classing Committee.

("The endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case, so that the Classing Committee may have all the salient points presented in the endorsement."—Extract from Sub-Committee's Report, 24/5/92.)

Transverse No. 34.16 Depth "d" 25.4

Framing: Table No. 3 page 16 Description Channels as approved

Longitudinal No. 34631

Proportions $\frac{\text{Length}}{\text{Depth}} = \frac{11.13}{1}$

Shelter
Deck Sheerstrake as approved.

The Downton Pump has been dispensed with for the present. It is concluded the owners are agreeable to fit the Downton Pump if requested to do so.

This vessel appears to have been built in accordance with the Rules and the approved plans, and it is submitted she is eligible to be classed ☒ 100 A.1. (steel). "Shelter Deck with freeboard," as recommended. The Summer freeboard of 8'-11 1/2" from centre of disc to top of statutory deck line at Shelter deck, now marked on the vessel's sides, to be inserted in the classification certificate, and recorded in the Register Book, and further, the remaining freeboards, as shown on the accompanying verification form to be inserted in the certificate of classification.

1 Dk. (steel) and Shelter Dk (steel)
Cul DB 366' 1334t. Ota 26' 1019t. FPT 148t. APT 292t.
FK. 6 BH to Shelter Dk. 2 BH to Upper Dk. pl. com. Lloyd's A+C.P. F on Shelter Dk 36'
~~Carrying Oil Fuel 100°F in DB. AEB.~~

The Surveyors should be requested to state whether the Gulls of bottom plating (from keel to upper turn of Bridge) are freely riveted as given in reports or quadruple riveted as shown in midships section sketch. They should also state whether Oil Fuel is being carried as cargo in Double Bottoms.

Angles of
Spacing
BEAMS, Forecas
Plating, etc.
Angles on

Lloyd's Register
Foundation
3541-0247