

MON. 12 JUN. 1916

Lloyd's Register of British & Foreign Shipping.
SURVEYS FOR FREEBOARD. STEAM SHIPS.

PARTICULARS RELATING TO ALL STEAM SHIPS EITHER FLUSH DECKED, OR WITH TOP GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, OR WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.

Port of Survey Osaka
Date of Survey April 1916
Name of Surveyor A. L. JonesShip's Name Kifunezan Maru Port of Registry and Nationality Kagasaki Japanese Official Number 18965 Gross Tonnage 3187 Date of Build 1916-4 Particulars of Classification ÷ 100A1 recomd.
Number in Register Book 46 Suph

| Registered dimensions from Ship's Register. | LENGTH. | BREADTH. | DEPTH. | UNDER DECK TONNAGE. |
|---|---------|--------------|--------------------|---------------------|
| | 305.0 | 43.75 | 27.25 | 2757 |
| Length on LOADLINE. | 305 | 44.1 British | 24.9 | Peak |
| | | Rule " 5 1/2 | Ceiling + .20 | Tanks |
| | | " 2.2 | Sheer + .88 | |
| | | " .37 | Drop in Deck + .20 | |
| CORRECTED DIMENSIONS. | 305 | 43.75 | 26.18 | 2665 |

Moulded Depth as measured..... 27' 3"

NOTE.— If the depth is measured when vessel is afloat, the details of measurement should be reported.

CORRECTION FOR LENGTH.

| | | |
|---------------------------------------|------|---------------------|
| Length of Ship on Loadline..... | 305 | |
| Length in Table | 327 | |
| Difference | 22 | |
| Correction for 10ft., Table A. | 1.4 | Table C. .7 |
| × Difference divided by 10 | 3.08 | (if required.) 1.54 |
| If 1/10ths length covered divide by 2 | -3 | -1 1/2 |

CORRECTION FOR IRON DECK.

| | | |
|---|-------|---------|
| Proportion covered, if less than 1/10ths length covered | 43 | 44 1/4 |
| Thickness of usual wood deck, less stringer | 3 1/2 | - 1 1/2 |

CORRECTION FOR ROUND OF BEAM.

| | | |
|---|--------|---------|
| Breadth at Gunwale amidships..... | 42.75 | |
| Round of Beam | 10 3/4 | |
| Normal round..... | 10 3/4 | |
| Difference | - | ÷ 2 = - |
| Proportion of Deck uncovered (Para. 19) | | |

NOTE.— The round of beam should be reported on the full breadth of vessel at the gunwale.

| | | |
|---|--------|-------|
| Freeboard, Table A | 6 | 4 1/4 |
| Correction for Sheer | -8 | |
| | 5 | 8 1/4 |
| Correction for Length | -3 | |
| | 5 | 5 1/4 |
| Allowance for Deck Erections | -7 3/4 | |
| | 4 | 9 1/2 |
| Correction for Round of Beam..... | | |
| Correction for fall in Sheer (if any)..... | | |
| Correction for Iron Deck (if required) | -1 1/2 | |
| | 4 | 8 |
| Additions for non-compliance with provisions of } Para. 11 (d) and (e) ‡ | | |
| Other Corrections (if any) | | |

| | | |
|-------------------------------|---|--------|
| Winter Freeboard | 4 | 8 |
| Summer Freeboard | 4 | 3 1/4 |
| Indian Summer Freeboard | 3 | 10 1/2 |
| N. A. Winter Freeboard | 4 | 10 |

Correction necessary because clearside amidships, measured in accordance with the Statute is not taken at the intersection of the wood or iron deck with side. 1 1/2

| | | |
|---------------------------------------|---|--------|
| Winter Freeboard from deck line | 4 | 9 1/2 |
| Summer " " " " | 4 | 4 1/2 |
| Indian Summer " " " " | 4 | 0 |
| N. A. Winter " " " " | 4 | 11 1/2 |

As assigned to 'Peking Maru' & 'Nanking Maru' same particulars Feb. marked and verification form is inclosed

† State dimensions of freeing port area on back of this form.

‡ The Surveyor should state whether the fall in sheer as reported is measured relatively to the straight line of keel or to the water line. If measured relatively to water line the vessel's draft at time of survey, and also the usual load draft forward and aft should be reported.

MARKING REPORT.

MARKING REPORT
RECEIVEDLloyd's Register
P.T.O.
Navigation

WS43-0194

Do all the Frames extend to the top height in the Poop? *yes*
 To what height do the Reverse Frames extend? *Longitudinal system*
 Has the Poop or Raised Quarter Deck an efficient Iron Bulkhead at the fore end? *yes*
 Give particulars of the means for closing the openings in Bulkhead *2 W.T. steel doors*
 Is the Poop or Raised Quarter Deck connected with the Bridge House? *no*
 Give particulars of the means for closing the openings in Bulkhead *2 W.T. steel doors*
 What is the thickness of the Bridge Front plating? *.38* and Coaming plate? *.42*
 Give scantlings and spacing of the Stiffeners *8x3x56 B.A. Special*
 Are bracket plates fitted at each end of the Stiffeners? *yes*
 Has the Bridge House an efficient Iron Bulkhead at the after end? *yes*
 How are the openings closed? *2 W.T. steel doors*
 Is the Forecastle at least as high as the main or top-gallant rail? *yes*
 Are the Engine and Boiler openings covered by a Bridge, Poop, Raised Quarter Deck, or enclosed by a Strong Iron or Steel Deckhouse? *Bridge*
 If the openings are not so protected are the exposed parts of the Casings efficiently constructed? *yes*
 Give thickness of plating; scantlings and spacing of Stiffeners
 What is the height of the exposed Casings? *yes*
 Are the Weather Deck Hatchways efficiently constructed and at least equal to the requirements of Section 28 of the Rules for 1904-5? Give particulars below:—

| Position and Size. | Ship. | Rule. | Ship. | Rule. | Ship. | Rule. | Ship. | Rule. |
|-------------------------------|----------|----------|-------|-------|-------|-------|-------|-------|
| Item. | | | | | | | | |
| COAMING. | | | | | | | | |
| Height above top of DECK | .30 | 24 | | | | | | |
| Thickness { Sides..... | .44 | .44 | | | | | | |
| { Ends..... | .40 | .40 | | | | | | |
| SHIFTING BEAMS OR WEB PLATES. | | | | | | | | |
| Number..... | 4 | 4 | | | | | | |
| Section and Scantlings..... | 23-18x34 | 9-14x34 | | | | | | |
| Material..... | 3-3x40 | 23x40 | | | | | | |
| | 4 angles | 4 angles | | | | | | |
| * FORE AND AFTERS. | | | | | | | | |
| Number..... | none | none | | | | | | |
| Section and Scantlings..... | | | | | | | | |
| Material..... | | | | | | | | |
| HATCHES Thickness..... | 3" | 3" | | | | | | |
| Remarks..... | | | | | | | | |

* When the Fore and Afters are of wood the depth should be stated from the underside of the hatches.
 (If the sill of the lowest side scuttle will be less than 6 inches above the Indian Summer Load Line if assigned under the tables, state vertical distance from top of deck at side amidships to lower edge of lowest side scuttle.)
 The following information is to be given in all Cases of vessels dealt with under Paras. 11, 12 (under 15 feet Moulded depth) and under Shelter Deck.
 What is the thickness of the Bridge Sheerstrake?

Delete the words { The Crew are, are not, berthed in the bridge house.
 that do not apply { The arrangements to enable them to get backwards and forwards from their quarters are, are not satisfactory.
 Length of Bulwarks in well _____ Sq. ft.
 Area of Freeing Ports required by Para. 11 (e) each side of vessel _____ Sq. ft.
 Ft. Tenths. Ft. Tenths. No. Freeing Ports (each side of vessel) _____ Sq. ft.
 Total deficiency or excess _____ Sq. ft.

Show hereon line of Floors or Tank Top with position of any Breaks in same; also height of Peak Tank tops, &c., &c.
 State any special features in the construction of the Vessel
 Duplicate of steamers "Peking Maru", "Hankow Maru", Kobe Reps. Nos.
 Freeboard request and verification forms now enclosed

Owners

Address

Fee £

Received by me



© 2020

Lloyd's Register Foundation