

## (LLOYDS REGISTER.)

G. R. 130  
Lloyds.

## VESSELS OF 100 TONS AND UPWARDS.

These particulars are supplied by the Registrar General of Shipping and Seamen for the sole use of Lloyds Register of British and Foreign Shipping.

Signal Letters (if any) *H.G.Q.N.*

Official Number.	Name of Ship.	No., Date, and Port of Registry.
123645	<i>St. David</i>	<i>118 m. 1906 London</i>
No., Date, and Port of Previous Registry (if any).		
Whether British or Foreign Built.	Whether a Sailing or Steam Ship; and if a Steam Ship how propelled.	Where Built.
<i>British</i>	<i>Steam Ship Turbines Three screws</i>	<i>Glydebank</i>
When Built.		Name and Address of Builders.
<i>1906</i>		<i>John Brown &amp; Co Ltd Glydebank</i>
Number of Decks	Length from fore part of stem, under the bowsprit, to the aft side of the head of the stern post	Feet. Tentshs.
<i>Three</i>	<i>350</i>	<i>8</i>
Number of Masts	Length at quarter of depth from top of weather deck at side amidships to bottom of keel	<i>350 25</i>
<i>Two</i>	<i>41 15</i>	<i>5</i>
Rigged	Main breadth to outside of plank	<i>16</i>
<i>Fore &amp; aft</i>	Depth in hold from tonnage deck to ceiling at midships	<i>18 27</i>
<i>Elliptical</i>	Depth in hold from upper deck to ceiling at midships, in the case of three decks and upwards	<i>7 73</i>
Stern	Depth from top of beam amidships to top of keel	<i>126 0</i>
<i>Raised &amp; Sunken Strake</i>	Round of beam	
Build	Length of engine room (if any)	
<i>None</i>		
Galleries		
<i>Straight</i>		
Head		
Framework and description of vessel		
<i>Steel</i>		
Number of Bulkheads		
<i>None</i>		
Number of water ballast tanks and their capacity in tons		
<i>Three 239 Tons Total</i>		

## PARTICULARS OF DISPLACEMENT.

Total to quarter the depth from weather deck at side amidships to bottom of keel	<i>2805</i> tons.	Ditto per inch immersion at same depth	<i>22.5</i> tons.
--	-------------------	--	-------------------

## PARTICULARS OF ENGINES (if any).

No. of Engines.	Description.	Whether British or Foreign made.	When made.	Name and Address of Makers.	No. of and Diameter of Cylinders.	Length of Stroke.	N.H.P. I. H. P. Speed of Ship.
<i>Three</i>	<i>Turbines</i>	<i>British</i>	<i>1906</i>	<i>John Brown &amp; Co Ltd</i>	<i>Turbines</i>	<i>9500</i>	<i>22 1/2 knots.</i>
	<i>Boilers</i>		<i>1906</i>	<i>Glydebank</i>			
	<i>Pressure when loaded 185 lb</i>						

## PARTICULARS OF TONNAGE.

GROSS TONNAGE.	No of Tons.	DEDUCTIONS ALLOWED.	No. of Tons.
Under Tonnage Deck	<i>1319.63</i>	On account of space required for propelling power	<i>1559.32</i>
Closed-in spaces above the Tonnage Deck, if any	<i>12.84</i>	On account of spaces occupied by Seamen or Apprentices, and appropriated to their use, and kept free from goods or stores of every kind, not being the personal property of the Crew	<i>144.24</i>
Space or spaces between Decks	<i>179.23</i>	These spaces are the following, viz.:— <i>Lower Deck, Fore, Bridge &amp; Poop</i>	
Poop	<i>484.69</i>		
Forecastle & Bridge	<i>226.33</i>		
Round House	<i>523</i>		
Other closed-in spaces, if any, as follows:— <i>Chart House</i>			
Spaces for machinery, and light, and air, under Section 78 (2) of the Merchant Shipping Act, 1894, if required.	<i>159.32</i>	Deductions under Section 79 of the Merchant Shipping Act, 1894, as follows:— <i>Master 565</i> <i>Chart 5.23</i> <i>(Lower) Boats Store 6.54</i> <i>(Upper) 5.11</i>	<i>22.56</i>
Gross Tonnage	<i>2384.27</i>	Cubic Metres	
Deductions, as per Contra	<i>1429.12</i>	<i>4893.41</i>	
Registered Tonnage	<i>658.15</i>	<i>1862.56</i>	<i>1429.12</i>
Name of Master		Certificate of { Service Competency	No. No.

Name of Owners

Residence, and Description of Managing Owner if there are more owners than one.

*Sheward & Rosslare Railways & Harbours Co. Head Office at Paddington Station (County) Sixty four of London**Charles Inglis, Great Western Railway Co. Paddington Station, London; Manager.*

Note: Spaces above the Upper Deck etc are:—

*Open Space between main & running decks - 45 90 Tons Less Hatch & Trunk (Total) 301. Total 22.89 tons**" Spaces under Forecastle (Less Companion & Skylight Trunk)**4th July 1906*

(830)—20917—2000-11-4

If stiffened with rings

Area of safety valves to superheater

Are they fitted

W564-0105

Lloyd's Register  
Foundation