

at intermdt. Bkts.

KEELSONS & STRINGERS.

from centre to centre amidships

Upper Deck, Single Angle, Bulb Angle, Plate, Tee Bulb, or Channel	8.65	5.3	.48
In way of Long Bridge			
Spacing	alternate frames		
Second Deck, Single Angle, Bulb Angle, Plate, Tee Bulb, or Channel	9 1/2	5 1/2	.46
Spacing	alt. frames		
Third and Fourth Deck, Single Angle, Bulb Angle, Plate, Tee Bulb, or Channel	8 1/2	3 1/2	.58
Angles on upper edge	in Bunkers		
Spacing	every frame		
Roop Deck, Angle, Bulb Angle, Plate, Tee Bulb, or Channel	7.8	3.5	.55
Angles on upper edge	64 in Bunkers		
Spacing	alternate frames		
Bridge Deck, Angle, Bulb Angle, Plate, Tee Bulb, or Channel			
Angles on upper edge			
Spacing			
Forecastle Deck, Angle, Bulb Angle, Plate, Tee Bulb, or Channel			
Angles on upper edge			
Spacing			

3-1m, 3.20. T.

ockets at intermdt. frmg., width & thickness

ERS, number on each side & thickness

if flanged (top and bottom)

10 72 10 8 1/2
2 flanged top

Vertical Plate above
Fourth and Fifth Deck Stringer Plate, breadth & thickness

" "	Angles on ditto, No.	63	.44
" "	Tie Plates outside Hatchways	3 1/2	3 1/2 .46
" "	Deck. Material & thickness	O.P.	2 1/5
" "	Deck. Material & thickness	O.P.	3.
" "	Deck Stringer Plate, breadth & thickness	64	.55
" "	Angle on ditto	3.9	3.9 .55
" "	Tie Plates	O.P.	.51
" "	Deck. Material and thickness	O.P.	3.
" "	Bridge Deck Stringer Plate, br'dth & thickness	39-35 in Holdo.	
" "	Angle on ditto	5 1/2	5 1/2 .64
" "	Tie Plates	Same as str	
" "	Deck. Material and thickness	✓	
" "	Forecastle Deck Stringer Plate, b'dth & th'kns		
" "	Angle on ditto		
" "	Tie Plates		
" "	Deck. Material and thickness		


* If Iron or Steel Deck, state if whole or part, and if Wood Deck is laid thereon.

" " Angle (clear of Bridge) ...

" " Tie Plate at sides of Hatchways.....

" Deck. * Iron or Steel, for full lng.

59
strake with etc double



© 2020

Lloyd's Register Foundation

572-0044 (2/3)

WEB FRAMES. Inches in Ship. Inches in Ship. Inches per Rule. Inches per Rule. Forgings or Castings. Inches in Ship. Inches per Rule. Or as Approved. WEB-FRAMES, In Fore Body, No. and spacing. No. of Side Stringers. WEB-FRAMES, In E. & B. Space, No. & spacing. WEB-FRAMES, In After Body, No. and spacing. No. of Side Stringers. Size of Face Angles to Web-Frames. BRACKET PLATES to Stringers between Web Frames, depth and thickness. BULKHEADS. Number. Thickness. STIFFENERS. Single or Double Frames. Height up, state deck. W.T. BULKHEADS. COLLISION. PARTITION. LONGITUDINAL. RUDDER, how constructed. Thickness of Plates or Single Plate. Can the Rudder be unshipped afloat? Manufacturer's name or trade mark of the Iron or Steel (state process of manufacture of Steel) used for Frames, Floors, Beams, Keelsons, Tie and Stringer Plates, Plating, &c. Has the Steel been tested as required by the Rules?

PLATING. STRAKES. AS IN SHIP. PER RULE OR AS APPROVED. EDGES. RIVETING. STRAPS. IF LAPPED. FLAT PLATE KEEL. GARBOARD OR A Strake. B. C. D. E. F. G. H. J & K. L. M. N. O. P. Q. R. S. T. U. V. W. X. Y. Z. THICKNESS OF SHEER STRAKE. CLEAR OF LONG BRIDGE. DO. OF STRAKE BELOW. DBLG. of Flat Plate Keel. Sheerstrakes. Length and thickness. POOP SIDES. SHORT BRIDGE SIDES. FORECASTLE SIDES. Butts of Side Stringers. Tie Plates. Inner Bottom Plating, riveting of Edges. Centre Girder Butts. Frames, riveted through Plates with. Rivets, state whether Iron or Steel. FRAMES extend in one length from. REVERSED FRAMES on floors and frames extend from. MASTS, SPARS, &c. LOWER MASTS. Fore. Main. Mizzen. Bowsprit. Topmasts, Yards and Remainder of Spars. Riggings: Material and Size, Shrouds. Sails. Suit of. Stays. Sails, and the following spare sails.

Write "Bridge Sheer Strake" and "Upper Deck Sheer Strake" opposite the corresponding letter

Form No. 1A

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop ☒ ft., R.Q.D. ☒ ft., Bridge 400 ft., Forecastle ☒ (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated joined

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as should appear in the Register Book) 6 Decks steel

Official No. 144301; Signal Letters K.D.J.C.

State if Machinery is fitted aft no

How are the surfaces preserved from oxidation? Inside Paint and Portland Cement Outside Paint

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors

Where Fitted.	*Length. Feet.	Water Capacity. Tons.	Where Fitted.	*Length. Feet.	Water Capacity. Tons.
Double bottom, aft,			Fore peak tank,		
Double bottom, under Engines and Boilers,			After peak tank,		
Double bottom, if under Engines only,			Deep tank, aft,		
Double bottom, if under Boilers only,			Deep tank, forward,		
Double bottom, forward,			Other tanks, if fitted,		
			(If necessary, furnish further information by sketch.)		

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules Yes, in Boiler Space

Order for Special Survey No.	1921
Date	Nov. 16, 18, 21, 23, 28, 29. Dec. 1, 2, 5, 7, 9, 13, 14, 15, 16, 19, 20, 21, 22, 23, 27, 29, 30. Jan. 2, 5, 6, 9, 10, 13, 17, 18, 20, 23, 25, 27, 30, 31. Feb. 1, 2, 3, 6, 7, 9, 10, 13, 14, 15, 16, 17, 18, 20, 22, 23, 24, 27, 28. Mar. 1, 2, 3, 6, 7, 8, 10, 12, 14, 15, 18, 20, 21, 23, 24, 27, 28, 29, 30, 31. Apr. 3, 4, 5, 6, 7, 8, 10, 11, 12, 13, 14, 17, 18, 19, 20, 21, 22, 24, 25, 26.
No. in builder's yard.	

Surveyor's Signature

R. Langlands
Lloyd's Register Foundation

© 2020
Total No. of Visits 98