

Safety valves to each boiler *2 direct spring* Area of each valve *3.98* Pressure to which they
 are they fitted with easing gear *yes* In case of ~~donkey~~ *any* boilers, state whether steam from main boilers can enter the
 smallest distance between boilers or uptakes and brakers or woodwork *8"* Mean dia. of boilers *11'-0"*

No. *A 70* Made by *S. Central Co of*

This Report No. *10220*

It is submitted that further action in the case is
 necessary until ^{as} this boiler is ~~not intended for~~ *fitted on* a
 ed vessel.

Date *1-2-16*

Entered in "Unclassed" Boiler Book.

Working pressure by rules *191* Superheater or Steam chest; how connected to boiler

Separately	Diameter	Length	Thickness of shell plates	Material	Description of longitud
Pitch of rivets	Working pressure of shell by rules	Diameter of flue	Material of flue plate		

shell plates wel

ng. seams *1 1/8*

102

85.6

No. and De

70

Thickn

100

nace by the rule

stays to ditto:

Material

m space: Ma

ys

om

n pitch of sta

Material

and pitch of

n pitch of sta

n pitch of sta

n pitch of sta

n pitch of sta

n pitch of sta

n pitch of sta

n pitch of sta

n pitch of sta

n pitch of sta

n pitch of sta

n pitch of sta

n pitch of sta

n pitch of sta

n pitch of sta