

PARTICULARS RELATING TO STEAM SHIP, EITHER FLUSH DECKED, OR WITH TOP GALLANT FORECASTLES, SHORT POOP, AND BRIDGE HOUSE, DISCONNECTED, OR WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS, CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.

Port of Survey

Date of Survey

Name of Surveyor

Glasgow

White Building

Henry A. Ellis

Ship's Name.

Port of Registry and Nationality.

Official Number.

Gross Tonnage.

Date of Build.

Particulars of Classification.

Number in Register Book

KINTAIL

Glasgow

124245

3537

1907

100 A1 Spar Deck

(contemplated)

Registered dimensions from Ship's Register.	LENGTH.	BREADTH.	DEPTH.	UNDER DECK Tonnage.
	349.2	46.2	25.8	3339.83
Length on LOADLINE	348.12	Frame Depth 9 Rule „ 56 3 2	Coiling Sheer +.88	Peak Tanks
	348.12	45.62	26.68	3339.83

Moulded Depth as measured

28.25

NOTE.—If the depth is measured when vessel is afloat, the details of measurement should be reported.

efficient of fineness ..... .788  
modification necessary [Para. 4 (a) to (e) \*] - .02 6813  
efficient as corrected ..... .77 bare

Stem... 102  
Sternpost... 52  
Mean  $154 \div 2 = 77$   
Stem 55  
Sternpost 29  
Mean  $84 \div 2 = 42$   
dual mean Sheer ..... 76.36  
Standard mean Sheer (Table, Para. 18) ..... 44.81  
Difference .....  $31.55 \div 4 = -8$   
limited as Para. 18 (f).....

At front of bridge house.....  
At after end of forecastle.....

At front of bridge house.....  
At after end of forecastle.....

## ALLOWANCE FOR DECK ERECTIONS:—

board, Table C..... 3-8.53  
Correction for Length, if required (Para. 12, 13, and 14) ..... 3-8.53  
board by Table A, corrected for sheer, and for length, if required (Para. 12, 13, and 14) ..... 3-9.30  
Difference ..... 2-6.41  
stage as below..... 9.73  
Total ..... 32.9%

Correction for R. Q. Dk. if engine and boiler openings not covered by bridge house (Para. 11) ..... -9.3%

	Length.	Length allowed.	Height.
Castle.....	40.0	40.0	7.3
Bridge House.....	106.0	106.0	"
Deck Or Dk.....	28.92	28.92	"
Total.....		174.92	
Length of Ship.....		348.12	.50

Responding percentage [Para. 11, 12, 13, and 14] 32.9%

Freeboard recommended amidships from centre of Disc to top of Statutory Deck Line, Wood (Iron) Deck:—

Fresh Water Line above centre of Disc .....  
Indian Summer Line " " " " .....  
Winter Line below " " " " .....  
Winter North Atlantic Line " " " " .....

CORRECTION FOR LENGTH.  
Length of Ship on Loadline..... 348.12  
Length in Table ..... 338.5  
Difference ..... 9.62  
Correction for 10ft., Table A ..... 1.44 Table C. .7  
× Difference divided by 10 ..... 1.38 (if required.)  
If 1/10ths length covered divide by 2 + 1 1/2 + 3/4

CORRECTION FOR IRON DECK.  
Proportion covered, if less than 1/10ths length covered ..... .50  
Thickness of usual wood deck, less stringer..... 3 1/2 - 1 1/4

CORRECTION FOR ROUND OF BEAM.  
Breadth at Gunwale amidships..... 44.11  
Round of Beam..... 13  
Normal round ..... 11.25  
Difference ..... 1.75  
Proportion of Deck uncovered (Para. 19) ..... .5 - 1/2

NOTE.—The round of beam should be reported on the full breadth of vessel at the gunwale.

Freeboard, Table A ..... 6-10.12  
Correction for Sheer ..... -7.89  
Correction for Length ..... 1.38  
Allowance for Deck Erections ..... 9.73  
Correction for Round of Beam..... 4.4  
Correction for fall in Sheer (if any) .....  
Correction for Iron Deck (if required) ..... 1.75  
Additions for non-compliance with provisions of Para. 11 (d) and (e) † .....  
Other Corrections (if any).....

Winter Freeboard ..... 5-3 1/2  
Summer Freeboard ..... 4-10 3/4  
Indian Summer Freeboard ..... 4-5 3/4  
N.A. Winter Freeboard .....

Correction necessary because clearside amidships, measured in accordance with the Statute, is not taken at the intersection of the wood or iron deck with side. 2"

Winter Freeboard from deck line ..... 5-5 1/2  
Summer " " " " ..... 5-0 3/4  
Indian Summer " " " " ..... 4-7 3/4  
N.A. Winter " " " " .....

Amended Tables March 1906.

State dimensions of freeing port area on back of this form.  
The Surveyor should state whether the fall in sheer as reported is measured relatively to the straight line of keel or to the water line. If measured relatively to water line the vessel's draft at time of survey, and also the usual load draft forward and aft, should be reported.

MARKING FORM  
RECEIVED 28 AUG 1924

† If the frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside of ceiling should be reported if possible.  
‡ In vessels obtaining an allowance for deck erections under Para. 11 where the sheer drops abaft amidships the height of the R.Q.D. is to be taken from the level of the top of the amidship beam.  
§ In flush-decked vessels the total standard mean sheer means the sheer measured at the stem and sternpost. In vessels having poops and forecastles, it means the sheer measured at points distant one-eighth of the vessel's length from stem and sternpost.




Do all the Frames extend to the top height in the Poop? *yes* Raised Quarter Deck? *yes* Bridge House? *yes* Forecastle? *yes*  
 To what height do the Reverse Frames extend? *alternate to Spar + Main Dhs.*  
 Has the Poop ~~on Raised Quarter Deck~~ an efficient Iron Bulkhead at the fore end? *yes*  
 Give particulars of the means for closing the openings in Bulkhead *Storm boards full height in permanent channels*  
 Is the Poop ~~on Raised Quarter Deck~~ connected with the Bridge House? *No* Has the Bridge House an efficient Bulkhead at the fore end? *yes*  
 Give particulars of the means for closing the openings in Bulkhead *No openings*  
 What is the thickness of the Bridge Front plating? *8/20* and Coaming plate? *9/20*  
 Give scantlings and spacing of the Stiffeners *Bullb angles 7 1/2 x 3 1/2 spaced 30" apart.*  
 Are bracket plates fitted at each end of the Stiffeners? *yes* Are hor'l. brackets fitted connecting Bridge Bulk'd. with Bulwarks? *yes*  
 Has the Bridge House an efficient Iron Bulkhead at the after end? *yes*  
 How are the openings closed? *Storm boards 1/2 height in permanent channels*  
 Is the Forecastle at least as high as the main or top-gallant rail? *yes* Has the Forecastle an efficient Iron ~~or Wood~~ Bulk'd. at after end? *yes*  
 Are the Engine and Boiler openings covered by a Bridge, Poop, Raised Quarter Deck, or enclosed by a Strong Iron or Steel Deckhouse? *yes*  
 If the openings are not so protected are the exposed parts of the Casings efficiently constructed? *✓*  
 Give thickness of plating; scantlings and spacing of Stiffeners *✓*  
 What is the height of the exposed Casings? *✓* Are suitable means provided for closing all openings in them in bad weather? *✓*  
 Are the Weather Deck Hatchways efficiently constructed and at least equal to the requirements of Section 28 of the Rules for 1904-5? Give particulars below:— *yes*

Position and Size.	No. 1. 19-11 x 16-11		No. 2. 23-11 x 16-11		No. 4. 7-11 x 16-11		No. 4. 27-11 x 15-11		No. 5. 19-11 x 16-11	
Item.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.
COAMING. Height above top of DECK	30	2 1/4	30	2 1/4	30	18	30	2 1/4	30	2 1/4
Thickness	Sides.....	9/20	9/20	9/20	7/20	7/20	9/20	9/20	9/20	9/20
	Ends.....	8/20	8/20	8/20	7/20	7/20	8/20	8/20	8/20	8/20
SHIFTING BEAMS OR WEB PLATES.	Number.....	7 1/2	7 1/2	7 1/2	7 1/2	7 1/2	7 1/2	7 1/2	7 1/2	7 1/2
	Section and Scantlings.....	8/20	8/20	8/20	8/20	8/20	8/20	8/20	8/20	8/20
	Material.....	steel	steel	steel	steel	steel	steel	steel	steel	steel
FORE AND AFTERS.	Number.....	3	3	3	3	3	3	3	3	3
	Section and Scantlings.....	12 8 x 7	12 10 x 10	12 8 x 7	12 10 x 10	12 8 x 7	12 10 x 10	12 8 x 7	12 10 x 10	12 10 x 10
	Material.....	pine	steel	pine	steel	pine	steel	pine	steel	steel
HATCHES Thickness.....	2 1/2	2 1/2	2 1/2	2 1/2	2 1/2	2 1/2	2 1/2	2 1/2	2 1/2	2 1/2
Remarks.....										

\* When the Fore and Afters are of wood the depth should be stated from the underside of the hatches.  
 (If the sill of the lowest side scuttle will be less than 6 inches above the Indian Summer Load Line if assigned under the tables, state vertical distance from top of deck at side amidships to lower edge of lowest side scuttle.)

The following information is to be given in all Cases of vessels dealt with under Paras. 11, 12 (under 15 feet Moulded depth) and under Shelter Deck Rules.

What is the thickness of the Bridge Sheerstrake? \_\_\_\_\_ Strake between Main and Bridge Sheerstrakes? \_\_\_\_\_  
 Delete the words { The Crew are, are not, berthed in the bridge house.  
 that do not apply { The arrangements to enable them to get backwards and forwards from their quarters are, are not satisfactory.  
 Length of Bulwarks in well \_\_\_\_\_  
 Area of Freeing Ports required by Para. 11 (e) each side of vessel = \_\_\_\_\_ Sq. ft.  
 Ft. Tenths. Ft. Tenths. No. }  
 { Freeing Ports (each side of vessel) = \_\_\_\_\_ Sq. ft.  
 Total deficiency or excess = \_\_\_\_\_ Sq. ft.



Show hereon line of Floors or Tank Top with position of any Breaks in same; also height of Peak Tank tops, &c., &c.

State any special features in the construction of the Vessel *Vessel classed 100 A1 Spar Dh but scantling & construction equivalent to 1885 Rules for 3 Dh. vessel of same dimensions. Preliminary report 96 of 25104*  
 Owners *Midship Section Profile enclosed.*  
 Address \_\_\_\_\_  
 Fee £ \_\_\_\_\_

Received by me \_\_\_\_\_

