

(On starboard side) No 3 and 4 plates in H and No 3 and 5 plates in J strake removed joined & replaced; No 4 plate in J strake and 2 frames joined in place; (On port side) No 8 plate in H and No 5 in J strake removed joined & replaced; 7 plates and 2 frames joined in place. (Wear House) The wood hatches, ceiling & cargo battens made complete minor repairs carried out.

JWR.
H/BF.

When Anchors or Cables are supplied, the particulars are to be reported in the following form:—

ANCHORS.

Number of Certificate.	Anchors.*	WEIGHT, EX. STOCK.			WEIGHT OF STOCK.			TEST, PER CERTIFICATE.			WEIGHT REQUIRED by TABLE 30 or 31.			Description of Anchor.	Makers.	Where and when tested and Superintendent.
		Cwts.	qrs.	lbs.	Cwts.	qrs.	lbs.	Tons.	Cwts.	qrs.	lbs.	Cwts.	qrs.	lbs.		
26386	1st Bower ...	82	1	14	-	-	-	60	0	0	0	81	1	0	By's stockless	324/20 L. Hoffman
	2nd "															
	3rd "															
	Collective Weight.															
	Stream															
	Kedge															

* When a bower anchor is supplied it must be clearly stated whether it is a 1st, 2nd, or 3rd bower.

CHAIN CABLES.

Number of Certificate.	Length and size supplied.		Test per Certificate.		WEIGHT OF CHAIN CABLE.		Length and size per Table 30 or 31.		Description.	Makers of Cables.	When and where tested and Superintendent.
	Length.	Diam.	Statutory.	Breaking.	Supplied.	Per Table 30 or 31.	Length.	Diam.			
	Fathoms.	Inch.	Tons.	Tons.	Cwts. qrs. lbs.	Cwts. qrs. lbs.	Fathoms.	Inch.			
69486	45	2½	112½	157½	139.2.9	140.1.15	2½	Stud link	—	20/12/20. N. J. L. Green.	
Iron Stream Chain } or Steel Wire... }											



© 2021

Lloyd's Register
Foundation