MON. DEC 9 1901

~~IRON OR~~ STEEL STEAMER. — 3 Decks.

Received at London Office 511.

State if Report is also sent on the Machinery of the Vessel Yes

Date of completion of report 4.12.01 Port of Sunderland No. 20772

Survey held at Sunderland Date, First Survey 12th July Last Survey 25th Nov. 1901.

In the "CORINTHIA" Rig Schooner

TONNAGE under Tonnage Deck	3427.36
Do. between Tonnage Dk. and 3rd and 4th Dk.	✓
Total under Upper Dk.	✓
Do. of Poop	✓
Do. of Bridge House	
Do. of Forecastle	40.6
Do. of Houses on Dk.	100.68
Do. of excess of Hatchways	56.73
Do. above Crown of Engine Room	✓
Gross Tonnage	3625.37
Do. Crew Space	80.75
Do. above Crown of Engine Room	✓
DEDUCTIONS FOR FEES	3544.62
Do. Engine Room	1160.12
Do. Navigation Spaces	25.59
Register Tonnage	2358.91

THREE DECKED VESSEL. 3DK. RULE

CLASS +100 A1

	FEET.
Half Breadth (moulded)	24.60
Depth from upper part of Keel to top of Upper Deck Beams (with the normal round up of beam)	28.5
Girth of Half Midship Frame (as per Rule)	49.75
	102.85
No. FOR SHELL = 34.969. deduct 7 feet	-7
1st Number	95.85
Length on deck from after part of stem to fore part of stern post	340.0
2nd Number DECKS & FORGINGS	32589.
Proportions—Breadth to Length	6.91
Depth to Length—Upper Deck to top of Keel	11.92
Main Deck ditto	✓

Destined Voyage Cardiff

Master — Miller

Year of appointment (1) As Master in service of owner of present vessel:—18 ✓ (2) As Master of this vessel No. 1901

Built at Sunderland

When built 1901 Launched 30th September 1901

By whom built J. L. Thompson & Sons Ltd

Owners The International Line Steamship Co. Ltd

Managers " "

(Where necessary to be entered in Reg. Book.)

Residence Whitby

Port belonging to Whitby

If Surveyed while Building, Afloat, or in Dry Dock building & afloat.

	Feet.	Inches.		Feet.	Inches.		Feet.	Inches.		
LENGTH on Deck per Rule	340	0	BREADTH— Moulded	49	2½	DEPTH, ACTUAL—Top of Floors to top of Upper Dk. Beams	24	10	No. of Decks with flat laid	One
						Do. do. do. do. ~~Main Dk. Beams~~	✓		No. of Tiers of Beams	One

Dimensions of Ship per Register, Length 342 breadth 49.5 depth 25.0 Moulded depth, ft. 27 ins. 6 To Upper Dk. Round of Upper Dk. Beam, Actual 12 ins.

FRAMING.

	Inches in Ship	Inches in Ship.	16ths or 20ths in Ship.	Inches per Rule Or as	Inches per Rule Approved.	16ths or 20ths per Rule
ANGLE, ~~Angles, or~~ ⌐, ~~⊏ or ⊏~~ Bars for ⅗ length amidships	8	3½x3½	12	8	3½x3½	12
" for ½ at each end	"	"	11	"	"	11
Floors in way of Double Bottoms at Solid Floors	3½	3½	9.8	3½	3½	9.8
" " ~~at intermdt. Plts.~~	—	—	—	—	—	—
Distance of Frames from moulding edge to moulding edge, all fore and aft	25	—	—	25	—	—
REVERSED FRAME, Angles IN. AFT. PK.	4	3½	9	4	3½	9
~~CELL FRAMING, depth of girder~~	—	—	—	—	—	—
FLOORS, depth and thickness of Floor Plate at mid-line for ⅗ length amidships	Cellular double bottom					
" in way of Engines and Boilers						
" thickness at the ends of vessel						
" depth at ¾ the half breadth, as per Rule						
" height extended at the Bilges						
FLOORS & BRACKETS in Cell Dble Bottoms	—	—	8	—	—	8
" " Distance apart	25	—	—	25	—	—
CENTRE GIRDER, in Double bottom, depth and thickness	44	—	10.9	44	—	10.9
" " Angles, Top	4	4	9.8	4	4	9.8
" " " Bottom	6½	4½	10.9	6½	4½	10.9
SIDE GIRDERS, number on each side & thickness	2	—	8	2	—	8
" " Angles	3½	3½	8	3½	3½	8
ENGINE PLATE, depth (exclusive of flange) and thickness	37	—	10	37	—	10
" " Angles to Outside Plating	4	4	9	4	4	9
CENTRE BOTTOM PLATING, breadth and thickness of Middle Line Strake	48	—	10.8	48	—	10.8
" " in Engine and Boiler space	ER 9/16	BR 9/16		ER 9/16	BR 9/16	
" " Remainder in Holds	—	—	7/16	—	—	7/16
SIDE FRAMES, Upper Deck, ~~Single Angle~~, Bulb Angle, ~~Plate or Tee Bulb~~	9	3	11.10	9	3	11.10
~~Angles on upper edge~~	—	—	—	—	—	—
Average space	25	—	—	25	—	—
SIDE FRAMES, ~~Middle Deck, Single Angle, Bulb Angle, Plate or Tee Bulb~~	Semi-box Beams 150" moe.					
~~Angles on upper edge~~	⌐ 13/20 ¬					
~~Average space~~						
SIDE FRAMES, ~~Lower Deck, Single Angle, Bulb Angle, Plate or Tee Bulb~~	12	—	10	12	—	10
~~Angles on upper edge~~ PLATE BULBS ANGLES	4	4	10	4	4	10
~~Average space~~	Spaced as per profile					
SIDE FRAMES, ~~Hold, or Orlop, Plate or Tee Bulb~~						
~~Angles on upper edge~~						
~~Average space~~						
SIDE FRAMES, Poop Deck, ~~Angle~~, Bulb Angle, ~~Plate or Tee Bulb~~	7	3	8	7	3	8
~~Angles on upper edge~~	—	—	—	—	—	—
Average space	25	—	—	25	—	—
SIDE FRAMES, Bridge Deck, ~~Angle~~, Bulb Angle, ~~Plate or Tee Bulb~~	7	3	8	7	3	8
~~Angles on upper edge~~	—	—	—	—	—	—
Average space	25	—	—	25	—	—
SIDE FRAMES, Forecastle Deck, ~~Angle, Bulb Angle, Plate or~~ Tee Bulb	9	6	10	9	6	10
Angles on upper edge	—	—	—	—	—	—
Average space	50	—	—	50	—	—
PILLARS, In ~~'tween Deck,~~ size and spacing	Longitudinal BHD. with bulb angle stiffeners 8½x3x13/16 spaced 50" apart					
" " Hold " "						
" Quarter ~~'tween Dks.~~, " "						
" " in Hold GIRDER IN LIEU "						
WEB-FRAMES, In Fore Body, No. and spacing	12 as per profile					12
" " " brdth. & thickness	24	—	9.8			
" No. of Side Stringers " "	THREE			THREE		
WEB-FRAMES, In E. & B. Space, No. & spacing	5 as per profile					5
" " " brdth. & thickness	24	—	9.8	24	—	9.8
WEB-FRAMES, In After Body, No. and spacing	9 as per profile					9
" " " brdth. & thickness	24	—	9.8	24	—	9.8
" No. of Side Stringers " "	THREE			THREE		
" Size of Angles ~~or Tee Bars~~ to Web-Frames	6½	4	12.11	6½	4	12.11
BRACKET PLATES to Stringers between Web Frames, depth and thickness ~~Size of~~	18	—	10	18	—	10

FORGINGS or CASTINGS.

	Inches in Ship.	Inches per Rule. Or as Approved.
KEEL, Bar or Side Plates, depth and thickness	Flat plate	
STEM, moulding and thickness	11 x 2 7/8	11 x 2 7/8
STERN-POST for Rudder do. do.	11 x 6 3/4	11 x 6 3/4
" for Propeller	" "	" "
MAIN PIECE of Rudder, diameter at head	9	9
" " do. at heel	7 x 4½	7 x 4½

RUDDER, how constructed Forging & pick plates

Can the Rudder be unshipped afloat? yes

KEELSONS & STRINGERS.

	Inches in Ship.	Inches in Ship.	16ths or 20ths in Ship.	Inches per Rule Or as	Inches per Rule Approved.	16ths or 20ths per Rule
CENTRE LINE KEELSON, Vertical Plate above floors, Through Plate, or Intercostal Plate						
" Rider Plate						
" Bulb Plate to Intercostal Keelson						
" Horizontal Plates on Floors						
" Angles		Cellular double bottom deep framing and web frames.				
SIDE KEELSON, Angles						
" Bulb or Plate above floors, for lng.						
" Intercostal Plate, for length						
" Attached to outside Plating with Angle						
BILGE KEELSON, Angles						
" Bulb or Plate above floors, for lng.						
" Intercostal Plate for length						
" Attached to outside Plating with Angle						
BILGE STRINGER Angles						
" Bulb Plate for length						
" Intercostal Plate for length						
" Attached to outside Plating with Angle				FACE BAR 6½	4	12
SIDE STRINGER Angles. FACE BARS 6½x4x12/20	4	3½	9.8	4	3½	9.8
2 IN Bulb or Intercostal Plate, for full lng.	24	—	9.8	24	—	9.8
N2 Attached to outside plating with Angle	4	3½	9.8	4	3½	9.8
Upper Deck Stringer Plates, br'dth & thickness	55-43		10.8	55-43		10.8
" Angle on ditto	6 x 6		12	6 x 6		12
" ~~Tie Plates fore and aft, outside Hatchways~~	—		—	—		—
" Deck.* Iron ~~or Steel~~, for full lng.	—	8	7/16	—		8.7/16
" ~~Wood Deck, Material & thickness~~	—		—	—		—
Middle Deck Stringer Plate, br'dth & thickness	72-44		10.8	72-44		10.8
" Angles on ditto, No.	4 x 4		9.8	4 x 4		9.8
" ~~Tie Plates outside Hatchways~~	—		—	—		—
" ~~Diagonal Tie Plates on Bms., No. of prs.~~	—		—	—		—
" ~~Deck.* Iron or Steel, for lng.~~	Fitted on wide spaced semi-box beams, with face bar					
" ~~Wood Deck, Material & thickness~~						
~~Lower Deck Stringer Plate~~, br'dth & thickness	12 x 3½ x 3½ x 15-14/20 channel.					
" Angles on ditto, No.						
" Tie Plates, outside Hatchways						
" Deck.* Material and thickness						
~~Hold, or Orlop Stringer Plate~~, br'dth & thckn's						
" Angles on ditto, No.						
" Tie Plates outside Hatchways						
" Deck. Material and thickness						
Poop Deck Stringer Plate, breadth & thickness	4.6	6		4.6		6
" Angle on ditto	3½ x 3½	7		3½ x 3½		7
" ~~Tie Plates~~	—	—		—		—
" Deck. Material and thickness	IRON	5/16		—		5/16
Bridge Deck Stringer Plate, br'dth & thickness	50	8		50		8
" Angle on ditto	3½ x 3½	10		3½ x 3½		10
" ~~Tie Plates~~	—	—		—		—
" Deck. Material and thickness	IRON	5/16		—		5/16
Forecastle Deck Stringer Plate, b'dth & th'kns	48	6		48		6
" Angle on ditto	3½ x 3½	7		3½ x 3½		7
" ~~Tie Plates~~ IRON D.K.	—	5/16		—		5/16
" Deck. Material and thickness Y. P.	6 x 3			6 x 3		

* If Iron or Steel Deck, state if whole or part, and if Wood Deck is laid thereon.

BULKHEADS.

	Number. In Vessel.	Number. Per Rule.	Thickness.	STIFFENERS. Horizontal. Size. Inches.	Horizontal. Spacing Inches.	Vertical. Size. Inches.	Vertical. Spacing Inches.	Single or Double Frames.	Height up.
			16ths or 20ths.						
W. T. BULKHEADS	6	6	7.6	9x3x12/20 ⌐	48	5½x3½x9	30	Double	Deck
PARTITION "									
LONGITUDINAL "	—	—	IRON 5/16	—	—	8½x3x12	50	—	Deck

Are the outside Plates doubled two spaces of Frames in length? Diamond plate

Are the ~~Sluice Valves and~~ Watertight Doors in efficient working order? yes.

Form No. 1B. 9-96

Lloyd's Register Foundation
W630-0101

PLATING.

STRAKES.	AS IN SHIP. AMIDSHIP. Breadth. (Inches.)	AMIDSHIP. Thickness. (16ths or 20ths)	FORWARD. Thickness. (16ths or 20ths)	AFT. Thickness. (16ths or 20ths)	PER RULE OR AS APPROVED. AMIDSHIP. Breadth. (Inches.)	AMIDSHIP. Thickness. (16ths or 20ths)
FLAT PLATE KEEL (If Bar Keel, state Riveting)	42	20	14	14	42	20·14
GARBOARD or A Strake	54	15	13	13	54	15·13
B „	46	12	12	10	—	13·10
C „ IN TANK	66	11	9	9	—	12·10
D „	46	12	10	10	—	13·10
E „	54	12	9	9	—	12·9
F „	54½	13	10	10	—	13·10
G „	61	12	9	9	—	12·9
H „	54½	13	10	10	—	13·10
J „	60	12	9	9	—	12·9
K „	51	13	10	10	—	13·10
L „	61	14	9	9	—	14·9
SHEER M „	46	16	11	11	46	16·11
N „						
O „	Midship thickness of Strakes B & C continued to Collision bulkhead.					
P „	After end plates and Strakes A, B, C & D = 14/20					
Q „	" " " " E & G = 13/20					
R „	" " " " F = 12/20					
DOUBLING of Flat Plate Keel	Keel & garboards increased in lieu thereof.					
Length and thickness of Bilges / of Sheerstrakes. / of Strake below	Doubling from 10 ft. within the Bridge each end to ½ length.					
POOP SIDES	7/20					
BRIDGE SIDES	10+9/20 Lower edge of Bridge sheer					
FORECASTLE SIDES	7/20 double riveted each end of Bridge					

Write "Sheer Strake" opposite its corresponding letter.

RIVETING.

EDGES.

STRAKES.	Single or Double.	Breadth of Lap. (Inches.)	RIVETS. Diam. (Inches.)	RIVETS. Spacing cr. to cr. (Inches.)
FLAT PLATE KEEL	Double	6	1	4½
GARBOARD or A Strake	"	"	1	"
B „	"	5¼	⅞	4
C „	"	"	"	"
D „	"	"	"	"
E „	"	"	"	"
F „	"	"	"	"
G „	"	"	"	"
H „	"	"	"	"
J „	"	"	"	"
K „	"	6	1	4½
L „	"	6	1	4½
SHEER M „				
N „				
O „				
P „				
Q „				
R „				
DOUBLING of Flat Plate Keel				
Length and thickness				
POOP SIDES	Single	3	¾	3⅜
BRIDGE SIDES	"	"	"	"
FORECASTLE SIDES	"	"	"	"

BUTTS.

STRAKES.	Double or Treble and for what Length.	RIVETS. Diam. (Inches.)	RIVETS. Spacing cr. to cr. (Inches.)	STRAPS. Breadth. (Inches.)	STRAPS. Thickness. (16ths or 20ths)	IF LAPPED. Breadth. (Inches.)	IF LAPPED. For what Length. (Feet.)
FLAT PLATE KEEL	Quad & Treble	1	3½	—	—	12·10½	full
GARBOARD or A Strake	Treble	1	"	—	—	10½	"
B „	"	⅞	3⅛	—	—	9	"
C „	2 & Treb.	"	"	—	—	10½-9	"
D „	Treble	"	"	—	—	9	"
E „	"	"	"	—	—	"	"
F „	2 & Treb.	"	"	—	—	10½-9	"
G „	"	"	"	—	—	"	"
H „	Quad.	"	"	—	—	10½	"
J „	"	"	"	—	—	"	"
K „	"	1-⅞-¾	3½-2⅞	—	—	12·10½-9	"
L „	Treble	1	3½	19	12-10	"	Double for 3/4 L.
SHEER M „							
N „							
O „							
P „							
Q „							
R „							
DOUBLING of Flat Plate Keel							
Length and thickness							
POOP SIDES	Double	¾	2⅝	9¾	7/20	—	—
BRIDGE SIDES	Treble & double	¾	" 1⅝-9¼		11/20	—	—
FORECASTLE SIDES	Double	¾	"	9¾	7/20	—	—

Manufacturer's name or trade mark of the Iron or Steel (state process of manufacture of Steel) used for Frames, Floors, Beams, Keelsons, Tie and Stringer Plates, Plating, &c.? Consett. Palmers I. C°. Dorman Long. Bolckow Vaughan Colville. S° Durham St & I C°. Siemens Martin Process.

Has the Steel been tested as required by the Rules? yes

Upper Deck / Stringer Plate — Butts, ~~treble~~ riveted ~~for~~ Quad ½ length amidship. Straps, ~~single, double or~~ overlapped for full length amidship.

Middle Deck / Stringer Plate — Butts, treble riveted for full length amidship. Straps, ~~single, double or~~ overlapped for full length amidship.

Butts of Bilge & Side Stringers and Tie Plates, treble or double riveted? ✓

Inner Bottom Plating, riveting of Edges Double & Single Butts Double

Centre Girder Butts, Treble riveted **Keelson Butts,** ✓ riveted.

Frames, riveted through Plates with 1-⅞ & ¾ in. Rivets, about 6 ins apart.

Rivets, state whether Iron or Steel Iron

FRAMES extend in one length from Tank margin to deck & to Top of erections

REVERSED FRAMES ~~or floors and frames extend from~~ 3ed bays, except in after peak where reverse bars extend to Upper deck.

MASTS, SPARS, &c.

	Material.	Total Length.	DIAMETER AND THICKNESS. At Partners.	Heel.	Hounds.	Head.	No. of Plates in round.	ANGLES Number.	ANGLES Size.	RIVETING. Seams.	RIVETING. Butts.
LOWER MASTS Fore	Steel	66·0	20 × 7/16	16 × 9/16	—	16 × 9/16	Two	—	—	Single	Treble
LOWER MASTS Main	"	54·0	"	"	—	"	"	—	—	"	"
LOWER MASTS Mizen											
Bowsprit											

Topmasts, Yards and Remainder of **Spars** Pine

Rigging, Material and Size, **Shrouds** Steel Wire 3¼ & 3½ . **Stays** 4" Wire

Sails. One Suit of fore & aft Sails, ~~and the following spare sails~~

EQUIPMENT No. 37040 LETTER W. ANCHORS.

Number of Certificate.	Anchors.	WEIGHT, EX. STOCK. Cwts.	qrs.	lbs.	WEIGHT OF STOCK. Cwts.	qrs.	lbs.	TEST, PER CERTIFICATE. Tons.	cwts.	qrs.	lbs.	WEIGHT REQUIRED BY TABLE 22. Cwts.	qrs.	lbs.	Description of Anchor.	Makers.	Where and when tested and Superintendent.
39 799	1st Bower	50	1	7	—	—	—	42	12	0	21	50	0	0	Bull ~~Dog~~ Patent	Tyzack & C°	Sld. 29/11/00
89	2nd „	50	0	0	—	—	—	42	7	2	0	50	0	0	"	"	" 13/12/01
152	3rd „	43	0	21	—	—	—	38	1	1	0	42	2	0	"	"	" 23/12/01
	4th „																H. T. Welford
	Collective weight	143	2	0								142	2	0			
550	Stream	12	0	0	3	0	14	13	17	2	0	12	0	0	Rodgers Patent	S. Hanbotham & C°	Sld. 30/10/01
507	Kedge	6	0	0	1	2	7	8	5	0	0	6	0	0	"	"	" 25/10/01
	Mechanical Tests & Mc Clelland, W. Addison & "R. Hilston.																H. T. Welford

If Patent, state name of Patentee. By Stockless, state Mechanical Tests.

CHAIN CABLES.

Number of Certificate.	Fathoms.	Size.	Test per Certificate. Tons.	WEIGHT OF CHAIN CABLE. Supplied.	Per Table 22.	Fathoms and Size per Table 22.	Description.	Makers of Cables.	When and where tested, and Superintendent.
96	270	2⅛	107·0 / 76·10	576·1·24	578·2·14	270-2⅛	Steel Link	S. Hanbotham & C°	Sld. 30/10/01 H. T. Welford
Iron ~~Stream Chain~~ or Steel Wire	90	4½	29	—	—	90-4½	Steel Wire	Craven & Speeding Bros	By Makers 1/11/01

HAWSERS AND WARPS.

Material.	Fathoms.	Size.	Breaking Test of Steel Wire Towline.	Fathoms and Size per Table 22.
TOWLINE	120	4½	39	120-4½
HAWSER 2 @	90	3½	22	2 @ 90·7
WARP	90	2¾		2 @ 90·7
	90	2½		

Boats Four

Pumps, Number One Downton Diameter of Barrel 4½ State whether they are in efficient working order yes

Windlass is Emerson Walker & Thompson Bros. ~~Capstan~~

Engine Room Skylights.—How constructed? Steel plates & bars

What arrangements for deadlights in bad weather? Lids & bulls eyes

Coal Bunker Openings.—How constructed? Steel Coamings How are lids secured? Tarpaulins & clips Height above deck? 18"

Number of **Scuppers,** and numbers and dimensions of **Freeing Ports, &c.** 6 scuppers, F. Pts 8 @ 2·9" × 1·11"

Ceiling in Holds, thickness and material W. Pine 2½ **Ceiling 'tween Decks,** thickness and material Spanning 2"

Cargo Hatchways.—How formed? Steel plates & bars **Hatches,** If strong and efficient? yes

State size **No. 1 Hatch** (Forward) 25' × 18' **No. 2 Hatch** 27·1" × 19' **No. 3 Hatch** 27·1" × 19' **No. 4 Hatch** 25' × 18'

Number of **Web Plates, Shifting Beams** and **Fore** and **Afters** to each Hatch No 1 = 2 W. 3 F.A. No 2 & 3, = 2 W. 5 F.A. No 4 = 2 W. 3 F.A.

No. of Breasthooks 6 **No. of Crutches** Deep floors

Bulwarks, height above deck and description Steel 3·11, Stays 1¾ dia. with ~~Iron~~ Rail, material and size 6 × 3 bulb angle

The above is a correct description.

Builder's Signature (here only) JOSEPH THOMPSON & SONS, Limited. SHIPBUILDING AND WORKS MANAGER.

Surveyor's Signature J. Allan

Surveyor to Lloyd's Register of British and Foreign Shipping.

Form No. 1B.

Correspondence.—State dates and initials of letters respecting this case (*Reference should be made to any correspondence connected with this case*) M. 25/7/00. 2/8/00. 10/8/00. 26/10/00. 19/1/01. 14/5/01. E. 11/12/00

Workmanship. Are the butts of plating planed or otherwise fitted? Planed

Is the riveted work properly closed? yes

Are the liners between the frames and plates solid single pieces? yes Do the holes for riveting plate to frames, butt straps, or plate to plate, &c., conform well to each other? yes Are the rivet holes well and sufficiently countersunk in the plate and punched from the faying surfaces? yes Do any rivets break into or through the seams or butts of plating? one or two

Are the butts of Plating, Stringers, &c., properly shifted and strapped? yes

Have all the upper and weather decks been tested as required by the Rules (Sec. 23, par. 24)? yes State results of tests Satisfactory

Have all the gutterways been tested as required by the Rules (Sec. 23, par. 25)? yes State results of tests Satisfactory

General Remarks (State quality of workmanship, &c.) This vessel has been built in accordance with the approved plans & Secretarys letters and generally in accordance with the Rules. The workmanship throughout is good.

The approved Midships Section, Profile, & deck plans are enclosed herewith, together with forging report for stem & stem frame.

The vessel is a duplicate of the same builders S.S. Roma. Yard No. 390. Sld. Report No. 20,685

The Surveyor should state the Number of Report and Name of any Sister Vessel.

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop 29 ft., ~~R.Q.D. or Break~~ ✓ ft., Bridge Dk. 100 ft., F'castle 32 ft. (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated not joined

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as it should appear in the Register Book) 1 DK (Iron) 2 tr B. Deep framing & web frames.

Official No. ; Signal Letters

How are the surfaces preserved from oxidation? Inside Paint & Cement Outside Paint.

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors Cellular

Where fitted.	*Length. Feet.	Water Capacity. Tons.
Double bottom, aft,	104·2 ✓	298 ✓
~~Double bottom, under Engines and Boilers,~~	✓	✓
Double bottom, if under Engines only,	22·11 ✓	79 ✓
Double bottom, if under Boilers only, Well	✓	✓
Double bottom, forward,	150	455

Where fitted.	*Length. Feet.	Water Capacity. Tons.
~~Fore peak tank~~,	✓	✓
After peak tank,	12·5 ✓	58 ✓
~~Midship deep tank~~,	✓	✓
~~Other tanks, if fitted~~,	✓	✓
(If necessary, furnish further information by sketch.)		

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules yes.

Order for Special Survey No. 4301

Date 7th July 1900

No. 391 in builder's yard.

Dates of Surveys held while building: 1901.– Feb 12.16.20.25.27 Mar 1.4.8.16.22. Apr 3.18.23 May 6.10.15.24.30.31 June 10.14.20 July 5.8.11.23.25 Aug 1.9.16.24.29 Sept 18.24.25.26.28. Oct 4.8.10.11.14.22.29.31 Nov 1.4.5.8.11.14.15.19.20.22.25

Total No. of Visits 57.

The amount of Entry Fee £ 5 : :

Special Survey Fee £ 113 : 12 : 6

Travelling Expenses, if any £ : :

Fees applied for, 7/12/01

Received by me, 10/12/01 £8 £12/12/01

Certificate to be sent to Sunderland.

State whether the Vessel has been built under Special Survey yes

I am of opinion this Vessel should be Classed +100 Al

With, or without Freeboard, as condition of Class Without.

Surveyor to Lloyd's Register of British and Foreign Shipping.

The Surveyors are requested not to write on or below the Committee's Minute.

Committee's Minute TUES. 10 DEC 1901

Character assigned Lloyds + LMC 11.01 100 A1 Steel

Conditional

11/12/01.

© 2021 Lloyd's Register Foundation