

REPORT ON MACHINERY.


Port of *Sunderland*

Received at London Office **TUES. 5 AUG 1902**

No. in Survey held at *Sunderland* Date, first Survey *22nd April* Last Survey *11th July, 1902*
 Reg. Book. *Screw Steamer "Benarty"* (Number of Visits *6*)
 on the *Screw Steamer "Benarty"* Tons { Gross *3910.10* Net *2510.30*
 Master *John Sarchet* Built at *Sunderland* By whom built *Bartholomew & Sons* (187) When built *1902*
 Engines made at *Sunderland* By whom made *J. Dickinson & Sons Ltd* (570) when made *1902*
 Boilers made at *Sunderland* By whom made *J. Dickinson & Sons Ltd* when made *1902*
 Registered Horse Power _____ Owners *William Thomson & Co* Port belonging to *Keith*
 Nom. Horse Power as per Section 28 *352* Is Electric Light fitted *No*

ENGINES, &c.—Description of Engines *Triple Expansion* No. of Cylinders *3* No. of Cranks *3*
 Diameter of Cylinders *25" - 42" - 68"* Length of Stroke *48* Revolutions per minute *70* Diameter of Screw shaft *as per rule 14.16*
 Diameter of Tunnel shaft *as per rule 13.7* Diameter of Crank shaft journals *13 1/2* Diameter of Crank pin *14* Size of Crank webs *patent*
 Diameter of screw *17'-0"* Pitch of screw *18'-0"* No. of blades *4* State whether moveable *yes* Total surface *84 sqft*
 No. of Feed pumps *2* Diameter of ditto *4"* Stroke *24"* Can one be overhauled while the other is at work *yes*
 No. of Bilge pumps *2* Diameter of ditto *4 1/2"* Stroke *24"* Can one be overhauled while the other is at work *yes*
 No. of Donkey Engines *2* Sizes of Pumps *vertical 7 1/2 x 4 1/2 x 10 Feed* No. and size of Suctions connected to both Bilge and Donkey pumps
 in Engine Room *2 of 3 1/2 in Engine Room. 2 of 3 1/2 in Bilge Room* In Holds, &c. *2 of 3 1/2" in each hold, 3 1/2 to aft well and peak*
 No. of bilge injections *1* sizes *5"* Connected to *condenser, or to circulating pump C.P* Is a separate donkey suction fitted in Engine room & size *4 in 3 1/2 in each wing*
 Are all the bilge suction pipes fitted with roses *yes* Are the roses in Engine room always accessible *yes* Are the sluices on Engine room bulkheads always accessible
 Are all connections with the sea direct on the skin of the ship *yes* Are they Valves or Cocks *Both.*
 Are they fixed sufficiently high on the ship's side to be seen without lifting the stokehold plates *yes* Are the discharge pipes above or below the deep water line *above*
 Are they each fitted with a discharge valve always accessible on the plating of the vessel *yes* Are the blow off cocks fitted with a spigot and brass covering plate *yes*
 What pipes are carried through the bunkers *None* How are they protected *✓*
 Are all pipes, cocks, valves, and pumps in connection with the machinery and all boiler mountings accessible at all times *yes*
 Are the bilge suction pipes, cocks, and valves arranged so as to prevent any communication between the sea and the bilges *yes*
 When were stern tube, propeller, screw shaft, and all connections examined in dry dock *new keel* Is the screw shaft tunnel watertight *yes*
 Is it fitted with a watertight door *yes* worked from *top platform*

BOILERS, &c.— (Letter for record *S*) Total Heating Surface of Boilers *5500 sqft* Is forced draft fitted *No*
 No. and Description of Boilers *Two cyl. multitubular* Working Pressure *180 lb* Tested by hydraulic pressure to *360 lb*
 Date of test *9.6.02* Can each boiler be worked separately *yes* Area of fire grate in each boiler *84 sqft* No. and Description of safety valves to
 each boiler *two direct Spring* Area of each valve *9.60* Pressure to which they are adjusted *185 lb* Are they fitted
 with easing gear *yes* Smallest distance between boilers or uptakes and bunkers or woodwork *18"* Mean diameter of boilers *17'-0"*
 Length *11'-0"* Material of shell plates *Steel* Thickness *1 3/8* Description of riveting: circum. seams *D.P. Cap* long. seams *Tri Riv. D.P.S*
 Diameter of rivet holes in long. seams *1 1/16"* Pitch of rivets *9 7/8"* Lap of plates or width of butt straps *1'-9 1/4"*
 Percentages of strength of longitudinal joint rivets *88.9%* Working pressure of shell by rules *182 lb* Size of manhole in shell *16" x 12"*
 plate *85.4%*
 Size of compensating ring *8 7/8 x 1 3/8* No. and Description of Furnaces in each boiler *4 Dightons* Material *Steel* Outside diameter *3'-10"*
 Length of plain part top *9 1/16"* Thickness of plates crown *9 1/16"* Description of longitudinal joint *welded* No. of strengthening rings *✓*
 bottom *9 1/16"*
 Working pressure of furnace by the rules *191 lb* Combustion chamber plates: Material *Steel* Thickness: Sides *1 1/16"* Back *1 1/16"* Top *1 1/16"* Bottom *7/8"*
 Pitch of stays to ditto: Sides *9 1/2 x 9"* Back *9 1/2 x 9"* Top *10 x 9"* If stays are fitted with nuts or riveted heads *Nuts* Working pressure by rules *180 lb*
 Material of stays *Steel* Diameter at smallest part *2.03"* Area supported by each stay *10 x 9"* Working pressure by rules *203 lb* End plates in steam space:
 Material *Steel* Thickness *1 1/8"* Pitch of stays *19 1/2 x 16 1/2"* How are stays secured *8 Nuts* Working pressure by rules *184 lb* Material of stays *Steel*
 Diameter at smallest part *6.1"* Area supported by each stay *19 1/2 x 16 1/2"* Working pressure by rules *189 lb* Material of Front plates at bottom *Steel*
 Thickness *7/8"* Material of Lower back plate *Steel* Thickness *29/32"* Greatest pitch of stays *15" x 9"* Working pressure of plate by rules *186*
 Diameter of tubes *3 1/4"* Pitch of tubes *4 1/2"* Material of tube plates *Steel* Thickness: Front *15/16"* Back *7/8"* Mean pitch of stays *9"*
 Pitch across wide water spaces *13 1/4"* Working pressures by rules *180 lb* Girders to Chamber tops: Material *Steel* Depth and
 thickness of girder at centre *7 1/2 x 1 1/4 x (2)* Length as per rule *32 5/16"* Distance apart *10"* Number and pitch of Stays in each *3 of 9" pitch*
 Working pressure by rules *189 lb* Superheater or Steam chest; how connected to boiler *None* Can the superheater be shut off and the boiler worked
 separately _____ Diameter _____ Length _____ Thickness of shell plates _____ Material _____ Description of longitudinal joint _____ Diam. of rivet
 holes _____ Pitch of rivets _____ Working pressure of shell by rules _____ Diameter of flue _____ Material of flue plates _____ Thickness _____
 if stiffened with rings _____ Distance between rings _____ Working pressure by rules _____ End plates: Thickness _____ How stayed _____
 Working pressure of end plates _____ Area of safety valves to superheater _____ Are they fitted with easing gear _____



DONKEY BOILER— Description *One G. Claudreux Multitubular 2 flame furnaces*
 Made at *Stockton* By whom made *Riley Bros* When made *5-6-02* Where fixed *on deck*
 Working pressure *120 lb* tested by hydraulic pressure to *240 lb* No. of Certificate *2764* Fire grate area *32 sq ft* Description of safety valves *two direct Spring*
 No. of safety valves *2* Area of each *7 sq in* Pressure to which they are adjusted *120 lb* If fitted with easing gear *yes* If steam from main boilers can enter the donkey boiler *no* Diameter of donkey boiler *10'-0"* Length *10'-0"* Material of shell plates *Steel* Thickness *1/16*
 Description of riveting long. seams *Stutt Shack* Diameter of rivet holes *15/16* Whether punched or drilled *drilled* Pitch of rivets *3 15/16*
 Lap of plating *9 1/2-13-3* Percentage of strength of joint Rivets *76.7%* Thickness of shell *ENOS* plates *29 x 4 1/2 in* Radius of do. *pitch* No. of Stays to do. *18*
 Dia. of stays *2 1/2 eff 5* Diameter of furnace Top *38"* Bottom *38"* Length of furnace *6-2 1/2* Thickness of furnace plates *9/16* Description of joint *welded* Thickness of furnace crown plates *C. chr 17 to 19/32* Stayed by *1 1/2 eff 8-8 to 10 pitch, nuts* Working pressure of shell by rules *124.5 lb*
 Working pressure of furnace by rules *120 lb* Diameter of *uptake* tubes *3 1/4* Thickness of *uptake* plates *F 29 10 9/16* Thickness of *stay* tubes *9/16*

SPARE GEAR. State the articles supplied: *Two top end bolts and nuts, two bottom end bolts and nuts, two main bearing bolts and nuts, spare coupling bolt and nuts, spare feed and bilge pump valves assorted iron bolts and nuts - Spare single throw crank shaft tail shaft two propeller blades - 4 P & M P piston packing rings, various feed & donkey pump valves.*
 The foregoing is a correct description,
John G. Meek Manufacturer.

Dates: During progress of work in shops - *1902 - April 22, 25. May 17. June 13, 15. July 11.*
 During erection on board vessel -
 building
 Total No. of visits *6.*

General Remarks (State quality of workmanship, opinions as to class, &c.)

ENGINES—Length of stern bush *5'-1"* Diameter of crank shaft journals *as per rule 13 1/2"* Diameter of thrust shaft under collars *14"*
BOILERS—Range of tensile strength *28/32 T* Are they welded or flanged *no* **DONKEY BOILERS**—No. *one* Range of tensile strength *28/32*
 Is the approved plan of main boiler forwarded herewith *yes* Is the approved plan of donkey boiler forwarded herewith *yes*
 Material of screw shaft *wrought iron* Is the screw shaft fitted with a continuous liner the whole length of the stern tube *yes*
 Is the after end of the liner made water tight in the propeller boss *yes* If the liner is in more than one length are the joints burned ✓
 If the liner does not fit tightly at the part between the bearings in the stern tube, is the space charged with a plastic material insoluble in water and non-corrosive ✓ If two liners are fitted, is the shaft lapped or protected between the liners ✓

The machinery built under Special Survey the material and workmanship found good and efficient—
The main boilers and steam pipes tested under hydraulic pressure to 360 lbs " and found sound and efficient in every respect at that pressure—
The engines tried under steam at their working pressures and found satisfactory—
In our opinion this vessel is worthy of the notification of R M C. 7. 02 to be made in the Register Book—

It is submitted that this vessel is eligible for THE RECORD - L M C 7:02

The amount of Entry Fee £ *3* : : When applied for, *2.8.02*
 Special £ *37* : *12* : :
 Donkey Boiler Fee £ : : :
 Travelling Expenses (if any) £ : : :
 Leonard's Hallcross, W. F. W. Moore
 Engineer Surveyor to Lloyd's Register of British & Foreign Shipping.

Committee's Minute *FRI. 8 AUG 1902*
 Assigned *+ L Meyer, 02*
 MACHINERY CERTIFICATE WRITTEN



Certificate (if required) to be sent to the Surveyors are requested not to write on or below the space for Committee's Minute.