

GENERAL REMARKS—(continued).

pt. 4.

te of writing Report

p. in Survey held
eg. Book.

on the Steel

aster J. O.

gines made at Jam

ilers made at

registered Horse Pow

m. Horse Power as p

GINES, &c.—

a. of Cylinders 21

the screw shaft fitted

the propeller boss

ween the bearings in

ers are fitted, is the

as per

ia. of Tunnel shaft

as fit

lars 11 5/8" Dia. of

. of Feed pumps

. of Bilge pumps

. of Donkey Engines

Engine Room JH

Tunnel W

. of Bilge Injections

re all the bilge suction p

re all connections with

re they fixed sufficiently

re they each fitted with

that pipes are carried

re all Pipes, Cocks, V

re the Bilge Suction L

the Screw Shaft Tu

ILERS, &c.—

otal Heating Surface

orking Pressure

on each boiler be work

ch boiler Two Spru

allest distance between

ickness 1 3/16" Rang

g. seam Double Riv

er centages of strength

ze of compensating rin

ngth of plain part

orking pressure of fun

itch of stays to ditto

aterial of stays steel

aterial Steel Thic

rea at smallest part

ickness 1" Materi

diameter of tubes 3"

itch across wide u

ickness of girder at

orking pressure by r

diameter

itch of rivets

PERHEATER

ale of Test

diameter of Safety Val

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop 26.0 ft., R.Q.D. ✓ ft., Bridge 66.0 ft., Forecastle 34.5 ft. (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as should appear in the Register Book). One Deck (Steel) one Tier of Beams

Official No. 27141; Signal Letters S.D.B.C. State if Machinery is fitted aft No.

How are the surfaces preserved from oxidation? Inside 3 coats of paint 8.6. + Bilge Cement Outside 3 coats paint

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors Cellular

Where Fitted.	*Length. Feet.	Water Capacity. Tons.	Where Fitted.	*Length. Feet.	Water Capacity. Tons.
Double bottom, aft,	86.0	169.11	Fore peak tank,	19.5	98.35
Double bottom, under Engines and Boilers,	36.0	105.70	After peak tank,	22.0	136.69
Double bottom, if under Engines only,	—	—	Deep tank, aft,	—	—
Double bottom, if under Boilers only,	—	—	Deep tank, forward,	—	—
Double bottom, forward,	116.0	289.63	Other tanks, if fitted,	—	—
Total capacity of double bottom		564.44	(If necessary, furnish further information by sketch.)		

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules.

Yes ✓

Order for Special Survey No.

Date

No. 57

in builder's yard.

DATES of Surveys held while building

Apr. 6. 11. 17. 29. May. 13. 20. 27. June 4. 8. 16. 24. 26
July 2. 11. 23. 27. Aug. 5. 12. 19. 24. 26. 28. Sept. 4. 9. 11. 16. 25. 30

Surveyor's Signature

A. F. House

© 2020
Total No. of Visits 28

Lloyd's Register
Foundation