

— S. S. No 356. —
List of Anchors, Chains & Hawser

Bower Anchors each $11\frac{1}{2}$ cwt. of Hall's latest improved Stockless Pattern with heads of Nickel Steel.

Bower Anchors each $\frac{1}{2}$ cwt. ex. stock Rodgers Patent, Rod Stock.

Stream Anchor 36 cwt. ex. stock } Rodgers Patent.
Kedge " 19 " }

3' dia. Steel Link Chain Cable of Best Iron - Minimum Weight 1482 cwt.

Steel Bow Line	$7\frac{1}{2}$ "	140 fms.	150 @ $6\frac{1}{2}$
" Hawser	$6\frac{1}{2}$ "	120	100 @ $7\frac{1}{2}$
"	4"	120 each	3 @ 120 @ $7\frac{3}{4}$ 8"
Manilla Hawser	9"	120	2 @ 120 @ 8"
"	8"	100	
"	7"	100	
Harping Lines	6"	100	



© 2020

Lloyd's Register Foundation

W682-0119

WEB-FRAMES, In After Body, No. and spacing	brdth. & thickness	24 1/2	12	24 1/2	12	BULKHEADS.	In Vessel.	Per Rule.	Thickness.	Horizontal Size.	Spa
		4 as per plan		4 as per plan							