

Are all cut outs fitted in easily accessible positions yes Are the fuses of standard dimensions yes If wire fuses are used  
are permanent instructions fitted on or near each switch board giving particulars of proper size of fuse for each circuit yes

Rpt. 13a.

Date 22<sup>nd</sup> July 1901

Supplement to Electric Lighting Installation Report No. 645  
on the Steam Ship S.S. Mongolia of Vladivostok.

### COMPASSES.

Distance between dynamo or electric motors and standard compass

41 feet

Distance between dynamo or electric motors and steering compass

68 --

The nearest cables to the compasses are as follows:—

A cable carrying	<u>25.6</u>	Amperes	<u>18</u>	feet from standard compass	<u>24</u>	feet from steering compass
A cable carrying	<u>6.8</u>	Amperes	<u>8</u>	feet from standard compass	<u>15</u>	feet from steering compass
A cable carrying	<u>2.</u>	Amperes		feet from standard compass	<u>3</u>	feet from steering compass

Have the compasses been adjusted with and without the electric installation at work at full power yes

The maximum deviation due to electric currents, etc., was found to be nil degrees on any course in the case of the  
standard compass and nil degrees on any course in the case of the steering compass.

Werk-Direction

Stabilimento Tecnico Triestino

Builder's Signature.

Date

22<sup>nd</sup> July 1901

Robt. Russick

Surveyor to Lloyd's Register.

Lloyd's Register  
Foundation  
W693-0178

Wires carried through metal & over verymann's tubes, where  
exposed to weather & through teak casing inside.